

MISSISSIPPI DEPARTMENT OF ENVIRONMENTAL QUALITY
Bureau of Land and Water Resources

P. O. Box 10631
Jackson, MS 39289-0631
WATER WELL DRILLERS LOG

COUNTY WELL LOCATED
Adams

WELL NUMBER
J 2036

CODED
36

DATE WELL COMPLETED
7-25-90

PERMIT NUMBER

NAME OF DRILLING FIRM
Harris Well Ser.

NAME & MAILING ADDRESS OF LANDOWNER
WT Drilling Co.

Po Drawer 1345

Natchez, MS 39120

WELL LOCATION: SEC **5** TOWNSHIP **N** RANGE **4**

DISTANCE **10** Miles **S** DIRECTION of **Vidalia, LA** NEAREST TOWN

OTHER LANDMARK
Glasscock Island

WELL PURPOSE: Home, Irrigation, Municipal, Industrial, Fish Pond, etc.
rig supply

PUMP DATA

PUMP TYPE (Circle One):
Submersible, Turbine, Jet, Flowing Well, Other (Describe) _____

POWER TYPE (Circle One):
Electric, Tractor, Diesel, Gasoline, Butane, Other (Describe) _____ H/P _____

Pump Capacity (GPM) _____ No. of Stages _____ Setting Depth _____ FT.

PUMP TEST

Well yielded _____ GPM with a drawdown of _____ ft. after _____ hours of pumping

WELL DATA

Well Depth 80ft	Casing Diameter (In.) 3	Casing Length (Ft.) 70ft
Type of Casing Pvc	Hole Depth 80 ft	Depth to Static Water Level 3ft above

TYPE OF COMPLETION: (Circle One or More):
Gravel Packed, Underreamed, Telescoped, Natural Development, Open Hole, Other (Describe) _____

Top of Lap Pipe or Reduction in Casing
FEET _____ IF TELESCOPED OR MORE THAN ONE SCREEN: USE BACK PAGE

LOG DATA

TYPE OF LOG RUN (Circle One):
Electric, Gamma Ray, Density, Sonic, Neutron, Other (Describe) _____ **No Log Run**

Name of Organization Running Log _____

SCREEN DATA

Diameter - Inches 3 in.	Length - Feet 10ft	Slot Size - Inches .020
Screen Type pvc	Depth to Bottom - Feet 80ft	

GEOLOGIC DATA (Office Use Only)

Surface Elev.	Geologic Unit	Unit Thickness	Depth to Top
Subs. SWL	Date	Analysis	Aquifer Test

Driller's Remarks

DESCRIPTION OF FORMATIONS ENCOUNTERED	FROM	TO
Gumbo	0	16
C. sand	16	45
silt	45	68
C. sand	68	80

FORMATIONS (Continued)

FROM	TO

RECEIVED

AUG 16 1991

Dept. of Environmental Quality
Bureau of Land & Water Resources

IF MORE SPACE IS NEEDED, USE BACK