MISSISSIPPI DEPARTMENT OF ENVIRONMENTAL QUALITY
Office of Land and Water Resources

P. O. Box 10631
Jackson, MS 39289-0631

WATER WELL DRILLERS LOG

COUNTY WELL LOCATED	ADAMS
WELL NUMBER	#1
CODED	
L-2012	
DATE WELL COMPLETED	6/21/01
PERMIT NUMBER	0-402
NAME OF DRILLING FIRM	Tom Griffith Water Well

NAME & MAILING ADDRESS OF LANDOWNER: ENERGY Drilling, Liberty Rd, Natchez, MS

WELL LOCATION — SEC: 15 TOWNSHIP: 3 (N) S RANGE: 1 (E) W

DISTANCE: 6½ Miles DIRECTION: NW NEAREST TOWN: of Crosby

OTHER LANDMARK:

WELL PURPOSE (Home, Irrigation, Municipal, Industrial, Fish Pond, etc.): Rig Supply

PUMP DATA

PUMP TYPE (Circle One): Submersible, Turbine, Jet, Flowing Well, Other (Describe)

POWER TYPE (Circle One): Electric, Tractor, Diesel, Gasoline, Butane, Other (Describe) H/P 5

Pump Capacity (GPM)	No of Stages	Setting Depth
65		315 FT.

PUMP TEST: Well yielded 35 GPM with a drawdown of Air Lift ft. after _____ hours of pumping

WELL DATA

Well Depth	Casing Diameter (in.)	Casing Length (Ft.)
410	4	370

Type of Casing	Hole Depth	Depth to Static Water Level
PVC	410	165

TYPE OF COMPLETION (Circle One or More): Gravel Packed, Underreamed, Telescoped, Natural Development, Open Hole, Other (Describe)

WELL GROUTED TO A DEPTH OF 10 FEET
Type Grout (circle one): Cement, Bentonite, or Mix

LOG DATA

TYPE OF LOG RUN (Circle One): No Log Run, Electric, Gamma Ray, Density, Sonic, Neutron, Other (Describe)

Name of Organization Running Log

GEOLOGIC DATA (Office Use Only)

Surface Elev	Geologic Unit	Unit Thickness	Depth to Top
Subs. SWL	Date	Analysis	Aquifer Test

Driller's Remarks

SCREEN DATA

Diameter - Inches	Length - Feet	Slot Size - Inches
4	40	20 Ft .010 / 20 Ft .020

Screen Type	Depth to Bottom - Feet
PVC	410

Top of Lap Pipe or Reduction in Casing: FEET

IF TELESCOPED OR MORE THAN ONE SCREEN: USE BACK PAGE

DESCRIPTION OF FORMATIONS ENCOUNTERED	FROM	TO
Sandy Clay	1	20
Sand & Gravel	20	75
Clay	75	360
Sand	360	410

FORMATIONS (Continued)	FROM	TO

REC'D JUL 02 2001

IF MORE SPACE IS NEEDED, USE BACK