

MISSISSIPPI DEPARTMENT OF ENVIRONMENTAL QUALITY

Office of Land and Water Resources

P. O. Box 10631
Jackson, MS 39289-0631

WATER WELL DRILLERS LOG

COUNTY WELL LOCATED
oleorn

WELL NUMBER CODED
E 2013

DATE WELL COMPLETED
8/12/96

PERMIT NUMBER

NAME OF DRILLING FIRM
Wilson well

NAME & MAILING ADDRESS OF LANDOWNER
Stanley Jones
30 CR 600
Walnut ms

WELL LOCATION SEC TOWNSHIP RANGE
7 2 N 5 E

DISTANCE DIRECTION NEAREST TOWN
6 Miles **E** of **walnut**

OTHER LANDMARK

WELL PURPOSE: Home Irrigation, Municipal, Industrial, Fish Pond, etc.

PUMP DATA

PUMP TYPE (Circle One):
 Submersible, Turbine, Jet, Flowing Well,
Other (Describe) _____

POWER TYPE (Circle One):
 Electric, Tractor, Diesel, Gasoline, Butane,
Other (Describe) _____ H/P _____

Pump Capacity (GPM) No. of Stages Setting Depth
10 **145** FT.

PUMP TEST
Well yielded _____ GPM with
a drawdown of _____ ft.
after _____ hours of pumping

WELL DATA

Well Depth 150	Casing Diameter (In.) 4"	Casing Length (Ft.) 140
Type of Casing PVC	Hole Depth 150	Depth to Static Water Level 100

TYPE OF COMPLETION: (Circle One or More):
 Gravel Packed, Underreamed, Telescoped,
 Natural Development, Open Hole, Other

WELL GROUTED TO A DEPTH OF _____ FEET
Type Grout (circle one): Cement, Bentonite, or Mix

LOG DATA

TYPE OF LOG RUN (Circle One):
 No Log Run, Electric, Gamma Ray, Density, Sonic, Neutron,
Other (Describe) _____

Name of Organization Running Log

SCREEN DATA

Diameter - Inches 4"	Length - Feet 10'	Slot Size - Inches .010
Screen Type PVC	Depth to Bottom - Feet 150	

GEOLOGIC DATA (Office Use Only)

Surface Elev.	Geologic Unit	Unit Thickness	Depth to Top
Subs. SWL	Date	Analysis	Aquifer Test

Driller's Remarks

Top of Lap Pipe or Reduction in Casing

FEET IF TELESCOPED OR MORE THAN ONE SCREEN USE BACK PAGE

DESCRIPTION OF FORMATIONS ENCOUNTERED	FROM	TO
Red clay	0	20
Red sand	20	40
Red & Brown sand	40	60
Brown sand	60	100
Brown sand & clay	100	120
Grey sand	120	150

RECEIVED

SEP 10 1996

Dept. of Environmental Quality
Office of Land & Water Resources

IF MORE SPACE IS NEEDED, USE BACK