MISSISSIPPI DEPARTMENT OF ENVIRONMENTAL QUALITY
Office of Land and Water Resources

P. O. Box 10631
Jackson, MS 39289-0631
WATER WELL DRILLERS LOG

COUNTY WELL LOCATED: Attala	PERMIT NUMBER:
WELL NUMBER: L 2026 — CODED:	NAME OF DRILLING FIRM: Thomas Drilling
DATE WELL COMPLETED: 8-1-97	

NAME & MAILING ADDRESS OF LANDOWNER: Gary Ellard

WELL LOCATION — SEC: 11 TOWNSHIP: 14 N/S RANGE: 6 E/W

DISTANCE: 3 Miles DIRECTION: NW of NEAREST TOWN: Kosciusko

OTHER LANDMARK: 1 mile S of Sugar Creek

WELL PURPOSE: Home, Irrigation, Municipal, Industrial, Fish Pond, etc.

PUMP DATA

PUMP TYPE (Circle One): Submersible, Turbine, Jet, Flowing Well, Other (Describe) ____

POWER TYPE (Circle One): Electric, Tractor, Diesel, Gasoline, Butane, Other (Describe) ____ H/P ____

Pump Capacity (GPM)	No. of Stages	Setting Depth
10	2	30 FT.

PUMP TEST

Well yielded 10 GPM with a drawdown of N/A ft. after 1 hours of pumping

WELL DATA

Well Depth	Casing Diameter (In.)	Casing Length (Ft.)
40	2"	35
Type of Casing	**Hole Depth**	**Depth to Static Water Level**
PVC	40	12

TYPE OF COMPLETION: (Circle One or More): Gravel Packed, Underreamed, Telescoped, Natural Development, Open Hole, Other (Describe) ____

WELL GROUTED TO A DEPTH OF 0 FEET
Type Grout (circle one): Cement, Bentonite, or Mix

LOG DATA

TYPE OF LOG RUN (Circle One): Electric, Gamma Ray, Density, Sonic, Neutron, No Log Run, Other (Describe) ____

Name of Organization Running Log

GEOLOGIC DATA (Office Use Only)

Surface Elev.	Geologic Unit	Unit Thickness	Depth to Top
Subs. SWL	Date	Analysis	Aquifer Test

Driller's Remarks

Top of Lap Pipe or Reduction in Casing: FEET — IF TELESCOPED OR MORE THAN ONE SCREEN: USE BACK PAGE

SCREEN DATA

Diameter - Inches	Length - Feet	Slot Size - Inches
2"	5	.010
Screen Type		**Depth to Bottom - Feet**
PVC		40

DESCRIPTION OF FORMATIONS ENCOUNTERED	FROM	TO
Clay	0	7
Sand & Clay	7	10
Red Sand	10	15
Sand	15	40

FORMATIONS (Continued)	FROM	TO

RECEIVED
AUG 20 1997
Dept. of Environmental Quality
Office of Land & Water Resources

IF MORE SPACE IS NEEDED, USE BACK