MISSISSIPPI DEPARTMENT OF ENVIRONMENTAL QUALITY
Office of Land and Water Resources

P. O. Box 10631
Jackson, MS 39289-0631
WATER WELL DRILLERS LOG

COUNTY WELL LOCATED: Benton	
WELL NUMBER: H2103	CODED:
DATE WELL COMPLETED: 11-24-99	
PERMIT NUMBER:	
NAME OF DRILLING FIRM: Wilson Well Co., Inc	
Whiteville, TN 38075	

NAME & MAILING ADDRESS OF LANDOWNER
William Parks
PO Box 180
New Albany, MS 38652

WELL LOCATION: SEC 31 TOWNSHIP 3 N (S) RANGE 1 (E) W

DISTANCE 2 Miles DIRECTION W of NEAREST TOWN Ashland

OTHER LANDMARK

WELL PURPOSE: (Home) Irrigation, Municipal, Industrial, Fish Pond, etc.

PUMP DATA

PUMP TYPE (Circle One): (Submersible) Turbine, Jet Flowing Well, Other (Describe)

POWER TYPE (Circle One): (Electric) Tractor, Diesel, Gasoline, Butane, Other (Describe) H/P

Pump Capacity (GPM)	No. of Stages	Setting Depth
10		70 FT.

PUMP TEST

Well yielded _____ GPM with a drawdown of _____ ft. after _____ hours of pumping

WELL DATA

Well Depth	Casing Diameter (In.)	Casing Length (Ft.)
80	4	70

Type of Casing	Hole Depth	Depth to Static Water Level
PVC	80	5

TYPE OF COMPLETION: (Circle One or More): (Gravel Packed) Underreamed, Telescoped, Natural Development, Open Hole, Other (Describe)

WELL GROUTED TO A DEPTH OF 10 FEET
Type Grout (circle one): Cement, (Bentonite) or Mix

LOG DATA

TYPE OF LOG RUN (Circle One): (No Log Run) Electric, Gamma Ray, Density, Sonic, Neutron, Other (Describe)

Name of Organization Running Log

GEOLOGIC DATA (Office Use Only)

Surface Elev.	Geologic Unit	Unit Thickness	Depth to Top
Subs. SWL	Date	Yield	Drawdown Test

Driller's Remarks

Top of Lap Pipe or Reduction in Casing
Depth To
IF TELESCOPED OR MORE THAN ONE SCREEN WAS USED

RECEIVED
DEC 10 1999
Dept. of Environmental Quality
Office of Water Resources

SCREEN DATA

Diameter - Inches	Length - Feet	Slot Size - Inches
4	10 ft	.010

Screen Type	Depth to Bottom - Feet
PVC	80

DESCRIPTION OF FORMATIONS ENCOUNTERED	FROM	TO	FORMATIONS (Continued)	FROM	TO
White Sand	0	20			
Fine White Sand	20	40			
White Sand (Medium)	40	60			
White Sand	60	80			
			IF MORE SPACE IS NEEDED, USE BACK		