

MISSISSIPPI DEPARTMENT OF ENVIRONMENTAL QUALITY
Office of Land and Water Resources

P. O. Box 10631
Jackson, MS 39289-0631
WATER WELL DRILLERS LOG

COUNTY WELL LOCATED Bolivar		PERMIT NUMBER
WELL NUMBER 2006	CODED	
DATE WELL COMPLETED 26 Aug 93		NAME OF DRILLING FIRM Lambert Drilling

NAME & MAILING ADDRESS OF LANDOWNER James M. Chunn			
At 1 Box 207			
Boyle, ms. 38730			
WELL LOCATION	SEC	TOWNSHIP	RANGE
	8	21	N 3 E
DISTANCE	DIRECTION	NEAREST TOWN	
10 Miles	W	Boyle	
OTHER LANDMARK			
WELL PURPOSE: Home, Irrigation, Municipal, Industrial, Fish Pond, etc. Home			

PUMP DATA		
PUMP TYPE (Circle One): <u>Submersible</u> Turbine, Jet, Flowing Well, Other (Describe)		
POWER TYPE (Circle One): Electric, Tractor, Diesel, Gasoline, Butane, Other (Describe) <u>H/P</u>		
Pump Capacity (GPM)	No. of Stages	Setting Depth
20	9'	105 FT.
PUMP TEST		
Well yielded _____ GPM with a drawdown of _____ ft. after _____ hours of pumping		

WELL DATA		
Well Depth	Casing Diameter (In.)	Casing Length (Ft.)
540	4x2	520
Type of Casing	Hole Depth	Depth to Static Water Level
PVC	540	38
TYPE OF COMPLETION: (Circle One or More): Gravel Packed, Underreamed, Telescoped, Natural Development, Open Hole, Other (Describe)		
WELL GROUTED TO A DEPTH OF _____ FEET Type Grout (circle one): Cement, Bentonite, or Mix		

LOG DATA	
TYPE OF LOG RUN (Circle One): No Log Run, Electric, Gamma Ray, Density, Sonic, Neutron, Other (Describe)	
Name of Organization Running Log	

GEOLOGIC DATA (Office Use Only)			
Surface Elev.	Geologic Unit	Unit Thickness	Depth to Top
Subs. SWL	Date	Analysis	Aquifer Test
Driller's Remarks			

SCREEN DATA		
Diameter - Inches	Length - Feet	Slot Size - Inches
2"	20	.010
Screen Type	Depth to Bottom - Feet	
PVC rapped	540-520	

DESCRIPTION OF FORMATIONS ENCOUNTERED	FROM	TO	FORMATIONS (Continued)	
			FROM	TO
Clay	0	30		
Sand	30	90		
pea gravel	90	135		
Clay	135	250		
Clay & Sand st	250	320		
Sand & P	320	400		
Sand, m.	400	540		

RECEIVED

AUG 30 1993

Dept. of Environmental Quality
Office of Land & Water Resources

IF MORE SPACE IS NEEDED, USE BACK