MISSISSIPPI DEPARTMENT OF ENVIRONMENTAL QUALITY
Office of Land and Water Resources

P. O. Box 10631
Jackson, MS 39289-0631
WATER WELL DRILLERS LOG

COUNTY WELL LOCATED: Clark	
WELL NUMBER: V-2102	CODED
DATE WELL COMPLETED: 6/22/98	
PERMIT NUMBER	
NAME OF DRILLING FIRM: McDonald & Hill, Meridian, Miss.	

NAME & MAILING ADDRESS OF LANDOWNER: Cindy Kersh, P.O. Box 115, Enterprise, Ms.

WELL LOCATION	SEC	TOWNSHIP	RANGE
	10	4 (S)	14 (E) W

DISTANCE	DIRECTION	NEAREST TOWN
2 Miles	NW	of Enterprise

OTHER LANDMARK: Sawmill

WELL PURPOSE: Home, Irrigation, Municipal, Industrial, Fish Pond, etc.

PUMP DATA

PUMP TYPE (Circle One): Submersible, Turbine, Jet, Flowing Well, Other (Describe)

POWER TYPE (Circle One): Electric, Tractor, Diesel, Gasoline, Butane, Other (Describe) H/P 2

Pump Capacity (GPM)	No. of Stages	Setting Depth
35	9	84 FT.

PUMP TEST

Well yielded 45 GPM with a drawdown of 30 ft. after 3 hours of pumping

WELL DATA

Well Depth	Casing Diameter (In.)	Casing Length (Ft.)
250	4"	240'
Type of Casing	**Hole Depth**	**Depth to Static Water Level**
PVC	250	31'

TYPE OF COMPLETION: (Circle One or More): Gravel Packed, Underreamed, Telescoped, Natural Development, Open Hole, Other (Describe)

WELL GROUTED TO A DEPTH OF _____ FEET
Type Grout (circle one): Cement, Bentonite, or Mix

LOG DATA

TYPE OF LOG RUN (Circle One): No Log Run, Electric, Gamma Ray, Density, Sonic, Neutron, Other (Describe)

Name of Organization Running Log

GEOLOGIC DATA (Office Use Only)

Surface Elev.	Geologic Unit	Unit Thickness	Depth to Top
Subs. SWL	Date	Analysis	Aquifer Test

Driller's Remarks

Top of Lap Pipe or Reduction in Casing: FEET — IF TELESCOPED OR MORE THAN ONE SCREEN, USE BACK PAGE

SCREEN DATA

Diameter - Inches	Length - Feet	Slot Size - Inches
4"	10	.016
Screen Type		**Depth to Bottom - Feet**
PVC		250

DESCRIPTION OF FORMATIONS ENCOUNTERED	FROM	TO	FORMATIONS (Continued)	FROM	TO
Clay	0	10			
Sand	10	35			
Shale & Rock st	35	220			
Sand - Med	220	230			
Coarse Sand	230	250			
			07-15-98 2:50 RCVD		
			IF MORE SPACE IS NEEDED, USE BACK		