

COAHOMA  
E 50

MISSISSIPPI DEPARTMENT OF NATURAL RESOURCES  
Bureau of Land and Water

RECEIVED

CODED  
67c

Southport Mall  
P.O. Box 10631 NOV 04 1991

Jackson, Mississippi 39209

WATER WELL DRILLERS LOG

Bureau of Environmental Quality  
Bureau of Land and Water Resources

0-10-91  
date well completed

19 Hope Well & Supply Co., Inc.  
firm name

county well located

LANDOWNER	description of formations encountered	from	to
Southern Fresh	Top Soil, soft clay, fine sand	0	20
John McKee POB 248	fine sand with soft clay mixed	20	40
Fruan Point MS 38631	fine sand	40	60
(mailing address)	fine sand	60	80
WELL LOCATION:	Sand w/ some small gravel	80	100
sec. 28 T28N R. 4 E	Mostly sand w/ little gravel	100	120
4 miles S of Fruan Pt.	sand at first to gravel	120	140
(distance) (direction) (nearest town)	Gravel	140	160
WELL PURPOSE:	Gravel	160	180
(home, irrigation, municipal, industrial)	Gravel w/ streak of sand		
WELL COMPLETION DATA:	w/ back to gravel	180	200
(1) diameter (inches) 4x3	Rock about 203ft		
(2) total depth (feet) 793.25	then into sand	200	220
(3) static water level (feet) _____ below top of ground.	sand w/ streaks of clay	220	240
(4) casing Steel 740 (material) (depth)	sand w/ few streaks of clay	240	260
4 (size) If telescope see back.	sand & clay mixed	260	280
(5) screen 30" 740 (length) (depth to top)	sand & clay mixed	280	300
3" (size) (material)	" "	300	320
(6) pump 5 (HP) (yield gph)	Clay w/ little sand mixed	320	340
elec (type power)	Clay w/ very few streaks of sand	340	360
(7) electric log (yes or no)	Clay w/ few streaks of sand	360	380
(organization running log)	" "	380	400
(8) how well bottom plugged BWW	Clay w/ few streaks of sand, shell rock 4 1/2 ft		
DRILLERS REMARKS:	Clay	400	420
excellent well	Clay w/ little streak of sand at bottom	420	440
	Clay w/ streak of hard clay back to soft clay	440	460
	Clay w/ some sand at bottom	460	480
	Clay w/ small streak of sand at bottom	480	500
	Clay	500	520
	" "	520	540
	Clay w/ streak of sand	540	560
	Clay	560	580
	Clay	580	600
	Clay	600	620
	additional on PK		