

Coahoma
E 200
7-27-76

**MISSISSIPPI
 BOARD OF WATER COMMISSIONERS**
 416 North State Street
 Jackson, Mississippi 39201

WATER WELL DRILLERS LOG

7-27 1976 Lipe Well Co. Coahoma
 date well completed firm name county well located

LANDOWNER:	description of formations encountered	from	to
Byrd Screw Co. Clarksdale MS. (mailing address)			
WELL LOCATION:	Top Soil	0	20
sec. <u>26</u> T. <u>28</u> N. R. <u>4</u> E. W. <u>W</u>	Sand	20	100
<u>5</u> miles <u>North</u> of <u>Clarksdale</u> (distance) (direction) (nearest town)	Gravel	100	190
WELL PURPOSE: (home, irrigation, municipal, <u>Industrial</u>)	Clay and sand	190	240
WELL COMPLETION DATA:	Clay	240	280
(1) diameter (inches) <u>4 X 2</u>	Sand	280	460
(2) total depth (feet) <u>1164</u>	Clay	460	580
(3) static water level (feet) <u>10</u> below above top of ground.	Sand	580	760
(4) casing <u>Steel</u> <u>1134</u> (material) (depth) <u>168" 4</u> <u>966" 2"</u> (size) if telescope see back.	Clay	760	820
(5) screen <u>30</u> <u>1134</u> (length) (depth to top) <u>2"</u> <u>S, S,</u> (size) (material)	Sand	820	870
(6) pump <u>1/2</u> <u>8</u> (HP) (yield gpm) <u>elec.</u> (type power)	Sand and clay	870	880
(7) electric log <u>Non</u> (yes or no) <u>Non</u> (organization running log)	Sand	880	900
(8) how well bottom plugged	Clay and sand	900	980
	Sand	980	1030
	Clay and sand	1030	1040
	Sand	1040	1080
	Clay and sand	1080	1100
	Sand	1100	1120
		1120	1164

RECEIVED
 AUG 3 1976

DRILLERS REMARKS: Back
Pressure Valve on
Bottom

MISS. BD. OF WATER COMMISSIONERS