

MISSISSIPPI DEPARTMENT OF ENVIRONMENTAL QUALITY

Office of Land and Water Resources

P. O. Box 10631

JACKSON, MISSISSIPPI 39208-0631

WATER WELL DRILLERS LOG

RECEIVED
NOV 09 1999

COUNTY WELL LOCATED
George Co.

WELL NUMBER C-2130 CODED

PERMIT NUMBER

DATE WELL COMPLETED
10-29-99

NAME OF DRILLING FIRM
Pierce well

NAME & MAILING ADDRESS OF LANDOWNER
D+D Const.
Multi Mart
Lucedale, Ms

WELL LOCATION SEC 26 TOWNSHIP 1 RANGE 6
N S E W

DISTANCE 2 Miles DIRECTION E of NEAREST TOWN Lucedale

OTHER LANDMARK

WELL PURPOSE Home, Irrigation, Municipal, Industrial, Fish Pond, etc.

PUMP DATA

PUMP TYPE (Circle One): Jet Flowing Well
Submersible, Turbine, Other (Describe)

POWER TYPE (Circle One): Electric Butane
Other (Describe)

Pump Capacity (GPM) 10 No. of Stages 2 Setting Depth 60 FT.

PUMP TEST
Well yielded 10 GPM with
a drawdown of 10 ft.
after 1 hours of pumping

WELL DATA

Well Depth <u>75'</u>	Casing Diameter (In.) <u>2"</u>	Casing Length (Ft.) <u>65'</u>
Type of Casing <u>Plastic</u>	Hole Depth <u>75'</u>	Depth to Static Water Level <u>50'</u>

TYPE OF COMPLETION: (Circle One or More):
Gravel Packed, Underreamed, Telescoped,
Natural Development, Open Hole, Other

LOG DATA

TYPE OF LOG RUN (Circle One): No Log Run
Electric, Gamma Ray, Density, Sonic, Neutron,
Other (Describe)

Name of Organization Running Log

WELL GROUTED TO A DEPTH OF 15 FEET
Type Grout (circle one): Cement, Bentonite, or Mix

GEOLOGIC DATA (Office Use Only)

Surface Elev.	Geologic Unit	Unit Thickness	Depth to Top
Subs. SWL	Date	Analysis	Aquifer Test

Driller's Remarks

Top of Lap Pipe or Reduction in Casing

FEET IF TELESCOPED OR MORE THAN ONE SCREEN: USE BACK PAGE

SCREEN DATA

Diameter - inches <u>2"</u>	Length - Feet <u>10'</u>	Slot Size - inches <u>006</u>
Screen Type <u>Plastic</u>	Depth to Bottom - Feet <u>75</u>	

DESCRIPTION OF FORMATIONS ENCOUNTERED	FROM	TO	FORMATIONS (Continued)	FROM	TO
<u>Top soil</u>	<u>0</u>	<u>10</u>			
<u>Clay</u>	<u>10</u>	<u>25</u>			
<u>Sand</u>	<u>25</u>	<u>45</u>			
<u>Clay</u>	<u>45</u>	<u>55</u>			
<u>good sand</u>	<u>55</u>	<u>75</u>			

IF MORE SPACE IS NEEDED, USE BACK