		Vell Report	
County: George 039		Part 1	For Office Use Only:
	Mississippi Departme	ent of Environmental Quality	Aquifer:
Permit #:		and Water Resources	Well #: H- 81
Driller: Stephen Haverd		Box 10631	L. S. Elevation:
Date drilling completed: 63-24-65		Jackson, MS 39289-0631 (601)961-5210	
		54-6938 (fax)	E-log #:
rine Central (ma	any		
State Law requires that this r		e driller in detail and filed w	ith the Department with
30 days of completion of drill Well Owner Infor		Wal	Location
Owner Name Scott Woo	sd	Latitude: <u>30 ° 49 '299</u>	" Longitude: <u>88 ° 33</u> '
Mailing Address: 152 Gasin	hurchwell	Hethod of Lat/Long (circle of	ne): Conventional Survey,
			GPS Survey-grade GPS
Laudde		<u>NW 45W 4 Sec_35</u>	
City	State Zip Code	Distance Direction	
Telephone No. (601) 558 - 4	1144		~~ <u>Un-coal</u>
		Data	· · · · · · · · · · · · · · · · · · ·
	VV CE	Data	
Purpose of Well (circle one) Home	Industrial Public Supply	Irrigation Fish Culture	Other:
Date well drilling started: <u>03 - 2</u>	Date	well drilling completed: 0:	5-29-05
If flowing, method of flow regulation:	Valve Other	(describe)	
_			
Static Water Level: 75 feet	t above or below (circle one)) land surface Date measured:	03-24-05
	\frown		
Method of Measurement (circle one)	electric tap	e air line other:	
Method of Measurement (circle one) Hole depth: <u>36</u>			
		Well grouted to a depth of	
Hole depth: <u>\36</u> Well Type of grout (circle one): Cement	depth: 129 Bentonite Min	Well grouted to a depth of	18 feet
Hole depth: <u>\36</u> Well Type of grout (circle one): Cement Casing length: <u>\\9</u> feet Ca	depth: <u>}29</u> Bentonite <u>Min</u> asing diameter: <u>4</u>	Well grouted to a depth of 	18 feet
Hole depth: <u>\36</u> Well Type of grout (circle one): Cement Casing length: <u>\\9</u> feet Ca	depth: 129 Bentonite Min	Well grouted to a depth of	18 feet
Hole depth: <u>\36</u> Well Type of grout (circle one): Cement Casing length: <u>\\9</u> feet Ca	depth: <u>129</u> Bentonite Min asing diameter: <u>4</u> creen diameter: <u>668</u>	Well grouted to a depth of 	18 feet Duc 540 208 PUC
Hole depth: <u>\36</u> Well Type of grout (circle one): Cement Casing length: <u> 19</u> feet Ca Screen length: <u>10</u> feet So	depth: <u>129</u> Bentonite Min asing diameter: <u>4</u> creen diameter: <u>4</u> s Setting depth: From	Well grouted to a depth of 	18 feet PUC 540 SOP PUC 29 feet
Hole depth: <u>\36</u> Well Type of grout (circle one): Cement Casing length: <u>119</u> feet Ca Screen length: <u>10</u> feet So Screen slot size: <u>.008</u> inche	depth: 129 Bentonite Min asing diameter: 4 creen diameter: 4 s Setting depth: From e): crravel packed Under	Well grouted to a depth of inches Type of casing: inches Type of screen: inches Type of screen: feet to erreamed Telescoped Open	18 feet PUC 540 SOP PUC SOP PUC SOP Feet hole Natural Development
Hole depth: <u>\36</u> Well Type of grout (circle one): Cement Casing length: <u>119</u> feet Ca Screen length: <u>10</u> feet So Screen slot size: <u>.008</u> inche	depth: 129 Bentonite Min asing diameter: 4 creen diameter: 4 s Setting depth: From e): Gravel packed Under Other (describe):	Well grouted to a depth of 	18 feet DUC 540 SOP DUC SQ feet hole Natural Development
Hole depth: <u>\36</u> Well Type of grout (circle one): Cement Casing length: <u>\49</u> feet Ca Screen length: <u>\0</u> feet So Screen slot size: <u>.008</u> inche Type of completion (circle all applicable	depth: 129 Bentonite Min asing diameter: 4 creen diameter: 4 s Setting depth: From e): Gravel packed Unde Other (describe):feet. If t	Well grouted to a depth of 	18 feet PUC 540 SOP PUC SOP PUC Solution of page sen, describe on back of page
Hole depth: <u>136</u> Well Type of grout (circle one): Cement Casing length: <u>119</u> feet Ca Screen length: <u>10</u> feet So Screen slot size: <u>. 008</u> inche Type of completion (circle all applicable Top of lap pipe or reduction in casing: _ Logs run (circle all applicable): <u>Volog</u> Name of organization running log(s):	depth: 129 Bentonite Min asing diameter: 4 creen diameter: 4 s Setting depth: From e): Travel packed Unde Other (describe): 4 feet. If t run Electric Gamma Ray	Well grouted to a depth of	18 feet
Hole depth: <u>136</u> Well Type of grout (circle one): Cement Casing length: <u>119</u> feet Ca Screen length: <u>10</u> feet So Screen slot size: <u>, 008</u> inche Type of completion (circle all applicable Top of lap pipe or reduction in casing: _ Logs run (circle all applicable): <u>No log</u>	depth: 129 Bentonite Min asing diameter: 4 creen diameter: 4 s Setting depth: From e): Travel packed Unde Other (describe): 4 feet. If t run Electric Gamma Ray	Well grouted to a depth of	18 feet
Hole depth: <u>136</u> Well Type of grout (circle one): Cement Casing length: <u>119</u> feet Ca Screen length: <u>10</u> feet So Screen slot size: <u>. 008</u> inche Type of completion (circle all applicable Top of lap pipe or reduction in casing: _ Logs run (circle all applicable): <u>Volog</u> Name of organization running log(s):	depth: 129 Bentonite Min asing diameter: 4 creen diameter: 4 s Setting depth: From e): 6 oravel packed Unde Other (describe): 6 feet. If t run Electric Gamma Ray	Well grouted to a depth of	18 feet
Hole depth: <u>136</u> Well Type of grout (circle one): Cement Casing length: <u>119</u> feet Ca Screen length: <u>10</u> feet So Screen slot size: <u>, 008</u> inche Type of completion (circle all applicable Top of lap pipe or reduction in casing: <u>1000</u> Logs run (circle all applicable): <u>1000</u> <u>Name of organization running log(s):</u> I certify that the well was drilled, const	depth: 129 Bentonite Min asing diameter: 4 creen diameter: 4 s Setting depth: From e): 6 oravel packed Unde Other (describe): 6 feet. If t run Electric Gamma Ray	Well grouted to a depth of	18 feet
Hole depth: <u>136</u> Well Type of grout (circle one): Cement Casing length: <u>119</u> feet Ca Screen length: <u>10</u> feet So Screen slot size: <u>, 008</u> inche Type of completion (circle all applicable Top of lap pipe or reduction in casing: <u>1000</u> Logs run (circle all applicable): <u>1000</u> <u>Name of organization running log(s):</u> I certify that the well was drilled, const	depth: 129 Bentonite Min asing diameter: 4 creen diameter: 4 s Setting depth: From e): 6 oravel packed Unde Other (describe): 6 feet. If t run Electric Gamma Ray	Well grouted to a depth of	18 feet

APR 11 2005 BY. CLWF If well telescopes please sketch below and show depths.

Ground Level

, •-

Description of Formations Encour		From	То
Topsand	Wix	0	5
Sand(med)	Drawnd	5	35
Clay	Piak	35	42
Solf.	brash	42	48
Clay	yellow	48	55
Clav	blue	55	82
silt.	blue	82	91
Sand (fine Formed)	blue	91	98
Sond Cried	blue	18	130
		_	
		· · · · · · · · · · · · · · · · · · ·	

If more than one screen, show location of each on sketch

Sketch the property layout and include the following: 1) the well location; 2) any permanent structures on the property that may aid in locating the well; 3) any roads, power lines, or other items that may aid in locating the property and the well; 4) indicate direction.

Scott Wood Landowner Name:

ignature of Water Well Contractor

APPLIS 2005 BY, OLWR

4-81

à Guin Church Drine Way

STATE WELL REPORT				
County: George Pump Installe Permit #: Mississippi Departm Driller: Stephen Hassed PC Date completed: 03-24-85 (60)	Part 2 pr's Completion Report hent of Environmental Quality d and Water Resources D. Box 10631 MS 39289-0631 D1)961-5210 354-6938 (fax)			
installation of pump. Well Owner Information	_			
	Well Location			
Owner Name: Scott Wood Mailing Address: 152 Gavin Churchuell Lucedele MS 39452 City State Zip Code	Latitude: 30° 49,775 Longitude: 88° 33,616 Method of Lat/Long (circle one): Conventional Survey, USGS quad, Hand-held GPS Survey-grade GPS 44 Sec 35 Twn T25 Rng R54			
Telephone No. (Со) 508 - 4144	Distance Direction Nearest Town <u>Miles</u> of <u>Lucedale</u>			
Pump Type Circle one	Power Type Circle one			
Air Lift Jet Submersible	Diesel Engine Gasoline Engine Natural Gas			
Bucket Piston Turbine	Effectric Motor Hand Tractor PTO			
Centrifugal Rotary Flowing Well	Windmill Other (specify):			
Other (specify):	Horse Power Rating of Motor: 1,5 HP			
Date Pump Installed: 3 · 24 - 6 5	Setting Depth: 120 feet			
Rated Pump Capacity: 27 Gallons Per Minute	Number of Stages:			
Pump Test Data Date Well Tested: <u>3~24.05</u> Static Water Level (A): <u>75</u> Feet Below Land Surface	Method of Measuring Water Level Circle one Air Line Electric Measuring Line			
Pumping Water Level (B): <u>93</u> Feet Below Land Surface	Other (specify):			
Drawdown [(B) – (A)]: \8 Feet Below Land Surface	For flowing well, measured shut in head:feet			
Test Pumping Rate: <u>43</u> Gallons Per Minute	Well yielded <u>43</u> GPM with a drawdown of			
Duration of Pump Test (minimum 4 hours): <u>4.5</u> hours	<u> </u>			
I HEREBY CERTIFY that the above statements are true to the best of my knowledge Michael Stephen Haserd 673 Print Name of Pump Installer and License No. (if applicable) Signature of Pump Installer				

د. ۱۹۹۹ - ۱۹۹۹ - ۱۹۹۹ - ۱۹۹۹ - ۱۹۹۹ - ۱۹۹۹ - ۱۹۹۹ - ۱۹۹۹ - ۱۹۹۹ - ۱۹۹۹ - ۱۹۹۹ - ۱۹۹۹ - ۱۹۹۹ - ۱۹۹۹ - ۱۹۹۹ - ۱۹۹۹

> RECCOSO AFAILOS BYLOLVAR