

MISSISSIPPI DEPARTMENT OF ENVIRONMENTAL QUALITY

Office of Land and Water Resources

P. O. Box 10631
Jackson, MS 39289-0631
WATER WELL DRILLERS LOG

COUNTY WELL LOCATED Harrison	
WELL NUMBER E 2094	CODED
DATE WELL COMPLETED 9-19-94	

PERMIT NUMBER 0-239
NAME OF DRILLING FIRM Mc Bee Pump
E Well

NAME & MAILING ADDRESS OF LANDOWNER Penny Fairly Cemetery Pass Cr. Ms. 39571			
WELL LOCATION	SEC	TOWNSHIP	RANGE
	9	6 N	13 E
DISTANCE	DIRECTION	NEAREST TOWN	
5 Miles	East	Dadeau	
OTHER LANDMARK			
WELL PURPOSE <input checked="" type="radio"/> Home Irrigation, Municipal, Industrial, Fish Pond, etc.			

PUMP DATA		
PUMP TYPE (Circle One): Submersible, Turbine, <input checked="" type="radio"/> Jet Flowing Well, Other (Describe) _____		
POWER TYPE (Circle One): <input checked="" type="radio"/> Electric , Tractor, Diesel, Gasoline, Butane, Other (Describe) _____ H/P _____		
Pump Capacity (GPM) 10	No of Stages 2	Setting Depth 180 FT.
PUMP TEST		
Well yielded 7 GPM with a drawdown of _____ ft. after 72 hours of pumping		

WELL DATA		
Well Depth 320'	Casing Diameter (In.) 2"	Casing Length (Ft.) 20'
Type of Casing PUC	Hole Depth 320	Depth to Static Water Level 80'
TYPE OF COMPLETION: (Circle One or More): <input checked="" type="checkbox"/> Gravel Packed, <input type="checkbox"/> Underreamed, <input type="checkbox"/> Telescoped, <input checked="" type="checkbox"/> Natural Development , <input type="checkbox"/> Open Hole, <input type="checkbox"/> Other (Describe) _____		
WELL GROUTED TO A DEPTH OF 10 FEET Type Grout (circle one): Cement, Bentonite, or Mix		

LOG DATA	
TYPE OF LOG RUN (Circle One): Electric, Gamma Ray, Density, Sonic, Neutron, Other (Describe) _____ <input checked="" type="radio"/> No Log Run	
Name of Organization Running Log	

SCREEN DATA		
Diameter - Inches 2	Length - Feet 10	Slot Size - Inches 000
Screen Type PUC	Depth to Bottom - Feet 310'	

GEOLOGIC DATA (Office Use Only)			
Surface Elev.	Geologic Unit	Unit Thickness	Depth to Top
Subs. SWL	Date	Analysis	Aquifer Test
Driller's Remarks			
Top of Lap Pipe or Reduction in Casing			
FEET		IF TELESCOPED OR MORE THAN ONE SCREEN: USE BACK PAGE	

DESCRIPTION OF FORMATIONS ENCOUNTERED	FROM	TO	FOR TESTS (continued)	TO
Sand	0	20		
Sand - gravel	20	60		
mud	60	120		
mud - sand	120	140		
mud	140	180		
Sand	180	200		
Sand, mud	200	220		
mud, sand, mud	220	240		
mud	240	280		
Sand	280	320		

RECEIVED
MAR 30 1995

Dept. of Environmental Quality
Office of Land & Water Resources

IF MORE SPACE IS NEEDED, USE BACK

