

E13

MISSISSIPPI BOARD OF WATER COMMISSIONERS CODED

416 North State Street
Jackson, Mississippi 39201

WATER WELL DRILLERS LOG

Well #5

13
9/9/80

9-9-80
date well completed

Dreiling & Associates
firm name

Issaquena
county well located

LANDOWNER: Goose Lake Farms

Rodney Woodruff

Rt. 2

Rolling Fork, Ms. 39159
(mailing address)

description of formations encountered

from

to

Top Soil

0,

5

Brown Clay

5

10

Gray Clay-Fine Sand

10

15

Gray Clay-Gravel-Med Sand

15

20

Coarse Sand-Gravel-Gray

20

25

Clay

20

25

Lignite-Coal/Coarse Sand-

25

30

Gray Clay

25

30

Coarse Sand/Gravel/Lignite

30

35

Coal

35

40

Coarse Sand/Gravel

40

45

Coarse Sand-Gravel

45

50

Coarse Sand-Gravel

50

55

Fine Sand-Gray Clay

55

60

Blue Clay

60

65

Pea Gravel/Fine Sand

65

70

Gray Clay-Med. Sand

70

75

Gray Clay/Coarse Sand

75

80

Fine Sand-Lignite/Wood

80

85

Gray Clay-Fine Sand

85

90

Coarse Sand & Fine Sand

90

95

Gray Clay

95

100

Fine Sand/Gray Clay

100

105

Blue Clay/Coarse Sand-

105

110

Gravel

110

115

Coarse Sand/Gravel

115

120

Coarse Sand/Gravel

120

125

Lignite-Coal/Coarse Sand

125

130

and Gravel

130

135

Coarse sand and Gravel

135

140

Bottom of Hole 124'

DEPT. OF NATURAL RESOURCES
BUREAU OF LAND & WATER RESOURCES

SEP 30 1980

RECEIVED

WELL LOCATION:

sec. 1 T 9 N R 8 E
S W
5 miles West of Valley Park
(distance) (direction) (nearest town)

WELL PURPOSE: irrigation
(home, irrigation, municipal, industrial)

WELL COMPLETION DATA:

- (1) diameter (inches) 2 1/2"
- (2) total depth (feet) 124'
- (3) static water level (feet) 15' ^{below} above top of ground.
- (4) casing Steel, 124'
(material) (depth)
(size) If telescope see back.
- (5) screen 20', 104'
(length) (depth to top)
16", Steel
(size) (material)
- (6) pump 80, 1200
(HP) (yield gpm)
Diesel
(type power)
- (7) electric log no
(yes or no)

(organization running log)

(8) how well bottom plugged Steel Plug

DRILLERS REMARKS: