

COUNTY WELL LOCATED

MISSISSIPPI DEPARTMENT OF NATURAL RESOURCES

Bureau of Land and Water Resources

LaFayette

WELL NUMBER

CODED

PERMIT NUMBER

3-2019

NAME OF DRILLING FIRM

HICKS WELL COMPANY

DATE WELL COMPLETED

3-1-88

RT. 1 - BOX 157

P.O. Box 10631

Jackson, Mississippi 39209

WATER WELL DRILLERS LOG

NAME & MAILING ADDRESS OF LAND OWNER

SENATOBIA, MISS.

O.C. Burnes

ht + 1

Senatobia, MS 38668

WELL LOCATION:

SEC

TOWNSHIP

RANGE

26 6 N 3 E

DISTANCE

DIRECTION

NEAREST TOWN

8 Miles S of Waterford

OTHER LANDMARK

WELL PURPOSE: Home, Irrigation, Municipal, Industrial, Fish Pond, etc.

PUMP DATA

PUMP TYPE (Circle One):

Submersible Turbine, Jet Flowing Well,
Other (Describe)

POWER TYPE (Circle One):

Electric Tractor, Diesel, Gasoline, Butane,
Other (Describe)

Pump Capacity (GPM)

No. of Stages

Setting Depth

10

7

60

FT.

PUMP TEST

Well yielded _____ GPM with

a drawdown of _____ ft.

after _____ hours of pumping

WELL DATA

Well Depth

95

Casing Diameter (in.)

4"

Casing Length (Ft.)

85'

Type of Casing

PVC

Hole Depth

95'

Depth to Static Water Level

40'

TYPE OF COMPLETION: (Circle One or More):

Gravel Packed, Underreamed, Telescoped,
Natural Development, Open Hole, Other

(Describe) PVC Cap

Top of Lap Pipe or Reduction in Casing

FEET

IF TELESCOPED OR MORE THAN
ONE SCREEN: USE BACK PAGE

SCREEN DATA

Diameter - Inches

4"

Length - Feet

10'

Slot Size - Inches

0/3

Screen Type

PVC

Depth to Bottom - Feet

95

LOG DATA

TYPE OF LOG RUN (Circle One):

No Log Run,
Electric, Gamma Ray, Density, Sonic, Neutron,
Other (Describe)

Name of Organization Running Log

GEOLOGIC DATA (Office Use Only)

Surface Elev.	Geologic Unit	Unit Thickness	Depth to Top
Subs. SWL	Date	Analysis	Aquifer Test

Driller's Remarks

DESCRIPTION OF FORMATIONS ENCOUNTERED

FROM

TO

FORMATIONS (Continued)

FROM

TO

Red clay

0

10

Red sand

10

30

white sand

30

60

Black clay

60

95

(35' of deadman)

RECEIVED

APR 27 1988

Department of Natural Resources
Bureau of Land & Water Resources

IF MORE SPACE IS NEEDED, USE BACK