

MISSISSIPPI DEPARTMENT OF ENVIRONMENTAL QUALITY

Office of Land and Water Resources

P. O. Box 10631
Jackson, MS 39289-0631
WATER WELL DRILLERS LOG

COUNTY WELL LOCATED LINCOLN	
WELL NUMBER G-2164	CODED
DATE WELL COMPLETED 3-13-00	

PERMIT NUMBER 0-287
NAME OF DRILLING FIRM REEVES WELL SER.

NAME & MAILING ADDRESS OF LANDOWNER RICHARD LABETH			
398 WATTS LN NW			
BROOKHAVEN MS			
WELL LOCATION: SEC	TOWNSHIP	RANGE	
31	7 S	7 W	
DISTANCE	DIRECTION	NEAREST TOWN	
3 Miles	SW	of BROOKHAVEN	
OTHER LANDMARK			
WELL PURPOSE: <u>Home</u> , Irrigation, Municipal, Industrial, Fish Pond, etc.			

PUMP DATA			
PUMP TYPE (Circle One): Submersible, Turbine, Jet, Flowing Well, Other (Describe) _____			
POWER TYPE (Circle One): Electric, Tractor, Diesel, Gasoline, Butane, Other (Describe) _____ H/P			
Pump Capacity (GPM)	No. of Stages	Setting Depth	
		_____ FT.	
PUMP TEST			
Well yielded 50 GPM with			
a drawdown of 0 ft.			
after 1 hours of pumping			

WELL DATA		
Well Depth 88'	Casing Diameter (In.) 4"	Casing Length (Ft.) 20'
Type of Casing PVC	Hole Depth 88'	Depth to Static Water Level 50'
TYPE OF COMPLETION: (Circle One or More): Gravel Packed, Underreamed, Telescoped, Natural Development, Open Hole, Other (Describe) 10 GAL. SAND		
WELL GROUTED TO A DEPTH OF 10 FEET Type Grout (circle one): <u>Cement</u> , Bentonite, or Mix		

LOG DATA	
TYPE OF LOG RUN (Circle One): Electric, Gamma Ray, Density, Sonic, Neutron, Other (Describe) _____	
Name of Organization Running Log	

SCREEN DATA		
Diameter - Inches 4"	Length - Feet 10'	Slot Size - Inches 10 THS.
Screen Type PVC	Depth to Bottom - Feet 88'	

GEOLOGIC DATA (Office Use Only)			
Surface Elev.	Geologic Unit	Unit Thickness	Depth to Top
Subs. SWL	Date	Analysis	Aquifer Test
Driller's Remarks			
Top of Lap Pipe or Reduction in Casing			
FEET	IF TELESCOPED OR MORE THAN ONE SCREEN: USE BACK PAGE		

DESCRIPTION OF FORMATIONS ENCOUNTERED	FROM	TO	FORMATIONS (Continued)	
			FROM	TO
Clay	0	15		
red hard	15	30		
coarse sand +				
red gravel	30	88		

RECEIVED
FEB 27 2002
BY: OLWR

IF MORE SPACE IS NEEDED, USE BACK

