County: Marion
Permit #:
Driller: James M. Wells
Date drilling completed: 6-17-14

### STATE WELL REPORT

#### Part 1 Driller's Log

Mississippi Department of Environmental Quality
Office of Land and Water Resources P.O. Box 2309

Jackson, MS 39225-2309 (601)961-5210 (601)360-0535 (fax)

For Office Use Only:	_
Well #:	
Aquifer:	
E-Log #:	

State Law requires that this report be prepared by the license holder responsible for the work and filed with the Department at the above address within 30 days of completion of drilling of the well or borehole.

Well Owner Information	Well or Borehole Location
(Landowner if borehole is not for a water well)  Owner Name: Charles Circle	Latitude: 31 31.66 Longitude: 089 52.348
Mailing Address:	Method of Lat/Long (check one): Conventional Survey,
420 Goss Bunkerhill Rd.	USGS quad, Hand-held GPS, Survey-grade GPS
01111 000 301170	NW 14 NW 14, Sec 30 36 T 5N R 18W
City State Zip Code	1 C1 1 19W
Telephone No. (601) 441-1304	(Distance) (Direction) (Nearest Town)
Telephone No. (Wt)	(Distance) (Direction) (Nearest 100m)
	orehole Data
Date drilling started: 4-17-14 Date drilling completed:	6-17-14 Hole depth: 160 Hole diameter: 7/3"
Location of the source of any surface water used for drilling	ng: <u>running</u> creek
Method of dosing and volume of Chlorine used in drilling a	J \ A1
Logs run (circle all applicable): No log un Electric Gamr	•
Name of organization running log(s):	
Purpose of borehole (circle one): Water Well Geotechni	ical/Geological Investigation Ground Source Heat Pump
Seismic Survey Other	(describe)
If drilling is not related to water well c	onstruction, skip the remainder of this block
Purpose of Well (circle all applicable) Home Industrial	Public Supply Irrigation Fish Culture
Other (describe):	
If a flowing well, method of flow regulation: Valve	Other (describe)
Static Water Level: 40 feet [above or below (circle one)	igland surface Date measured: 6-17-14
Method of measurement (circle one) Steel tape Electric	tape Air line Other (describe):
Well depth: 160 Well grouted to a depth of: 10	
Casing length: 130 feet Casing diameter:	inches Type of casing:
Screen length: <u>30</u> feet Screen diameter: _	inches Type of screen:
Screen slot size: 1008 inches Setting depth	: From 130 feet to 160 feet
Type of completion (circle all applicable): Gravel packed	Underreamed Open hole Natural Development
Other (describe):	The state of the s
Top of lap pipe or reduction in casing:feet	2 - 1 - 2 - 2 - 2 - 2 - 2 - 2 - 2 - 2 -
If telescoped or more than	one screen, describe on next page

Form: OLWR-SWR-1A (4/13)

County:	We	For Office Use	e Only:
The sketch below only required for water wells	Description of formations encoun		
	and boreholes, unless specifically	exempted by regular	<u>tions</u>
f well telescopes, show depths on sketch.	Description of Formations Encounter	ed From (depth)	To (depth)
Fround Level	10,000	Ground level	
	Clay	1	20
	sand	20	30
	Clay	30	115
	gay	11.5	160
	Juna	<i>''\</i>	160
•			
more than one screen, show location of each on sketch			
2) any permanent structures on the property that may 3) any roads, power lines, or other items that may aid 4) north arrow	Bunkerhill 12d.	REC	JEWED
3		ٳڒڹۯ	1 7 2014
~]			
andowner Name: Charles Creel			OF WE
HEREBY CERTIFY that the well/borehole was drille quirements of the Mississippi Department of Envir applicable, and state laws.	d, constructed, and completed in acconnental Quality and the Mississippi	cordance with all ap Department of Heal	plicable
EREBY CERTIFY that the well/borehole was drille quirements of the Mississippi Department of Enviropplicable, and state laws.	onmental Quality and the Mississippi	Department of Heal	plicable
HEREBY CERTIFY that the well/borehole was drille quirements of the Mississippi Department of Envir	7-14-14 Zava	cordance with all ap Department of Heal ignature of Licensee	plicable th regulations

### STATE WELL REPORT

# County: Marian Permit #: Driller: James M. Wells Date completed: 6-17-14

## Part 2 Pump Installer's Completion Report

Mississippi Department of Environmental Quality
Office of Land and Water Resources
P.O. Box 2309
Jackson, MS 39225-2309
(601)961-5210
(601) 360-0535 (fax)

For Office Use Only:	
Well #: <u>1375</u>	
Aquifer:	

(601) 360-0535 (fax)
This part of the report must be completed by a licensed water well contractor or a licensed pump installer. A copy of Part 1 of the report must be attached and both parts filed with the Department at the above address within 30 days of well completion.
Well Owner Information Well Location
Owner Name: Charles Cree Latitude: 31°31.666 Longitude: 089.53.248
Mailing Address: Method of Lat/Long (check one): Conventional Survey,
400 Goss Bunkerhill Rd. USGS quad_, Hand-held GPS_, Survey-grade GPS_
Columbia MS 39429 NN 4 NW 4, Sec 36 T 5NV RJ860 City State Zip Code
Telephone No. (60) 441-1364
Pump Type (circle one)
Submersible Turbine Air Lift Centrifugal Flowing Well Jet Piston Rotary Other (describe):
Date Pump Installed: 6-17-19 Rated Pump Capacity: 27 Gallons Per Minute
ls This Pump (circle one): New Repaired Replacement
Power Type (circle one)
Electric Diesel Gasoline Natural Gas Tractor PTO Windmill Other (describe):
Horse Power Rating of Motor: Setting Depth: 160 feet Number of Stages:
, Pump Test Data for Non Flowing Well
/ 1 1 /
Date Well Tested: 6-17-14 Duration of Pump Test (minimum 4 hours): 4 hours
Date Well Tested: 6-11-1 Duration of Pump Test (minimum 4 hours): 4 hours  Static Water Level (A): 40 Feet Below Land Surface Pumping Water Level (B): 100 Feet Below Land Surface
Static Water Level (A): 40 Feet Below Land Surface Pumping Water Level (B): 100 Feet Below Land Surface
Static Water Level (A): 45 Feet Below Land Surface Pumping Water Level (B): 100 Feet Below Land Surface Drawdown [(B) - (A)]: 48 Feet Below Land Surface Test Pumping Rate: 35 Gallons Per Minute
Static Water Level (A): 40 Feet Below Land Surface Pumping Water Level (B): 100 Feet Below Land Surface Drawdown [(B) - (A)]: 48 Feet Below Land Surface Test Pumping Rate: 35 Gallons Per Minute Method of measurement (circle one) Steel tape Electric tape Air line Other (describe):
Static Water Level (A): 40 Feet Below Land Surface Pumping Water Level (B): 100 Feet Below Land Surface  Drawdown [(B) - (A)]: 48 Feet Below Land Surface Test Pumping Rate: 35 Gallons Per Minute  Method of measurement (circle one) Steel tape Electric tape Air line Other (describe):  Pump Test Data for Flowing Well
Static Water Level (A): 40 Feet Below Land Surface Pumping Water Level (B): 100 Feet Below Land Surface  Drawdown [(B) - (A)]: 48 Feet Below Land Surface Test Pumping Rate: 55 Gallons Per Minute  Method of measurement (circle one) Steel tape Electric tape Air line Other (describe):  Pump Test Data for Flowing Well  Measured shut in head:feet.
Static Water Level (A): 48 Feet Below Land Surface Pumping Water Level (B): 100 Feet Below Land Surface  Drawdown [(B) - (A)]: 48 Feet Below Land Surface Test Pumping Rate: 35 Gallons Per Minute  Method of measurement (circle one) Steel tape Electric tape Air line Other (describe):  Pump Test Data for Flowing Well  Measured shut in head:feet.  Well yielded GPM with a drawdown of feet after hours of pumping
Static Water Level (A): 40 Feet Below Land Surface Pumping Water Level (B): 50 Feet Below Land Surface Drawdown [(B) - (A)]: 48 Feet Below Land Surface Test Pumping Rate: 55 Gallons Per Minute Method of measurement (circle one) Steel tape Electric tape Air line Other (describe): Pump Test Data for Flowing Well  Measured shut in head:feet.  Well yieldedGPM with a drawdown offeet afterhours of pumping  Meter Installation
Static Water Level (A): 48 Feet Below Land Surface Pumping Water Level (B): 100 Feet Below Land Surface  Drawdown [(B) - (A)]: 48 Feet Below Land Surface Test Pumping Rate: 35 Gallons Per Minute  Method of measurement (circle one): Steel tape Electric tape Air line Other (describe):
Static Water Level (A): 48 Feet Below Land Surface Pumping Water Level (B): 100 Feet Below Land Surface  Drawdown [(B) - (A)]: 48 Feet Below Land Surface Test Pumping Rate: 35 Gallons Per Minute  Method of measurement (circle one) Steel tape Electric tape Air line Other (describe):  Pump Test Data for Flowing Well  Measured shut in head: feet.  Well yielded GPM with a drawdown of feet after hours of pumping  Meter Installation  Meter Manufacturer: Meter Serial Number: Type of Meter:
Static Water Level (A): 48 Feet Below Land Surface Pumping Water Level (B): 100 Feet Below Land Surface Drawdown [(B) - (A)]: 48 Feet Below Land Surface Test Pumping Rate: 35 Gallons Per Minute Method of measurement (circle one) Steel tape Electric tape Air line Other (describe):  Pump Test Data for Flowing Well  Measured shut in head:feet.  Well yieldedGPM with a drawdown offeet afterhours of pumping  Meter Installation  Meter Manufacturer: Meter Serial Number:  Totalizer Register Unit and Multiplier Factor (AF x .001, gal x 1000, etc):
Static Water Level (A): 48 Feet Below Land Surface Pumping Water Level (B): 55 Feet Below Land Surface Drawdown [(B) - (A)]: 48 Feet Below Land Surface Test Pumping Rate: 55 Gallons Per Minute Method of measurement (circle one) Steel tape Electric tape Air line Other (describe): Pump Test Data for Flowing Well  Measured shut in head:feet.  Well yielded GPM with a drawdown of feet after hours of pumping  Meter Installation  Meter Manufacturer: Meter Serial Number:  Meter Model Number/Name: Type of Meter:  Totalizer Register Unit and Multiplier Factor (AF x .001, gal x 1000, etc):  Installation Date: Meter installed by: Meter installed by:

Print Name of Pump Installer and License No. (if applicable)

7-14-14 Date

Signature of Pump Installer

Form: OLWR-SWR-1B (4/13)