

F

MISSISSIPPI DEPARTMENT OF NATURAL RESOURCES
Bureau of Land and Water Resources

P.O. Box 10631
Jackson, Mississippi 39209
WATER WELL DRILLERS LOG

COUNTY WELL LOCATED
Marion

WELL NUMBER CODED
No. 1 Buckley Newspaper

DATE WELL COMPLETED
7-29-89

PERMIT NUMBER

NAME OF DRILLING FIRM
Griner Drilling Service, Inc.

NAME & MAILING ADDRESS OF LANDOWNER
Exeter Drilling Co.
P.O. Box 1478
Houston, Tx. 77001

WELL LOCATION: SEC. TOWNSHIP RANGE
1842 N 4 **S** **E**
2588' W of **S** **W**

DISTANCE DIRECTION NEAREST TOWN
SECTOR **E** **Morganstown**

OTHER LANDMARK
Field

WELL PURPOSE: Home, Irrigation, Municipal, Industrial, Fish Pond, etc.
Oilfield Rig Supply

PUMP DATA

PUMP TYPE (Circle One):
 Submersible Turbine Jet Flowing Well,
Other (Describe) **72 H.P.**

POWER TYPE (Circle One):
 Electric Tractor Diesel Gasoline Butane,
Other (Describe) **230 volt**
3 phase

Pump Capacity (GPM) No. of Stages Setting Depth
80 **-** **105 FT.**

PUMP TEST

Well yielded **80** GPM with
a drawdown of **N/A** ft.
after **N/A** hours of pumping

WELL DATA

Well Depth 170'	Casing Diameter (In.) 4"	Casing Length (Ft.) 140'
Type of Casing PVC	Hole Depth 170'	Depth to Static Water Level 10'

TYPE OF COMPLETION: (Circle One or More):
 Gravel Packed Underreamed Telescoped,
 Natural Development Open Hole Other

Top of Lap Pipe or Reduction in Casing
FEET IF TELESCOPED OR MORE THAN ONE SCREEN: USE BACK PAGE

LOG DATA

TYPE OF LOG RUN (Circle One):
 No Log Run,
Electric, Gamma Ray, Density, Sonic, Neutron,
Other (Describe)

Name of Organization Running Log

SCREEN DATA

Diameter - Inches 4"	Length - Feet 20'	Slot Size - Inches .010
Screen Type PVC	Depth to Bottom - Feet 140'-160'	

GEOLOGIC DATA (Office Use Only)

Surface Elev.	Geologic Unit	Unit Thickness	Depth to Top
Subs. SWL	Date	Analysis	Aquifer Test

Driller's Remarks

DESCRIPTION OF FORMATIONS ENCOUNTERED	FROM	TO	FORMATIONS (Continued)	FROM	TO
Sand, pea gravel	0	170	DISGENT	510	

SEP 18 1989

Department of Natural Resources
Bureau of Land & Water Resources

IF MORE SPACE IS NEEDED, USE BACK

