

MISSISSIPPI DEPARTMENT OF ENVIRONMENTAL QUALITY

Office of Land and Water Resources

P. O. Box 10631
Jackson, MS 39289-0631
WATER WELL DRILLERS LOG

COUNTY WELL LOCATED MARSHAL	
WELL NUMBER R 2091	CODED
DATE WELL COMPLETED 4-14-99	

PERMIT NUMBER
NAME OF DRILLING FIRM N.W.B. Well Drilling BLANK Langford

NAME & MAILING ADDRESS OF LANDOWNER ROSE-ATTIA THOMPSON YORK BROUGH ROAD Red BANKS MISS			
WELL LOCATION:	SEC	TOWNSHIP	RANGE
	18	3	3
DISTANCE	DIRECTION	NEAREST TOWN	
3 Miles	E	of Red BANKS	
OTHER LANDMARK			
WELL PURPOSE: Home, Irrigation, Municipal, Industrial, Fish Pond, etc. Home			

PUMP DATA		
PUMP TYPE (Circle One): Submersible, Turbine, Jet, Flowing Well, Other (Describe) _____		
POWER TYPE (Circle One): Electric, Tractor, Diesel, Gasoline, Butane, Other (Describe) _____ H/P W		
Pump Capacity (GPM)	No. of Stages	Setting Depth
12		_____ FT.
PUMP TEST		
Well yielded _____ GPM with a drawdown of _____ ft. after _____ hours of pumping		

WELL DATA		
Well Depth 190	Casing Diameter (In.) 4	Casing Length (Ft.) 20-
Type of Casing PVC	Hole Depth 190	Depth to Static Water Level 160
TYPE OF COMPLETION: (Circle One or More): Gravel Packed, Underreamed, Telescoped, Natural Development, Open Hole, Other (Describe) _____		

LOG DATA	
TYPE OF LOG RUN (Circle One): Electric, Gamma Ray, Density, Sonic, Neutron, Other (Describe) _____	
Name of Organization Running Log	

WELL GROUTED TO A DEPTH OF _____ FEET
Type Grout (circle one): Cement, Bentonite, or Mix

GEOLOGIC DATA (Office Use Only)			
Surface Elev.	Geologic Unit	Unit Thickness	Depth to Top
Subs. SWL	Date	Analysis	Aquifer Test

SCREEN DATA		
Diameter - Inches 4	Length - Feet 10	Slot Size - Inches .013
Screen Type SPOTTED PVC	Depth to Bottom - Feet 190	

Driller's Remarks

DESCRIPTION OF FORMATIONS ENCOUNTERED	FROM	TO
DIRT	0	40
Red SAND	40	60
Red GRAVEL SAND	60	90
Mixed CLAY SAND	90	120
W. CLAY	120	140
White SAND	140	190

FORMATIONS (Continued)	FROM	TO
RECEIVED		
MAY 28 1999		
Dept. of Environmental Quality Office of Land & Water Resources		

IF MORE SPACE IS NEEDED, USE BACK

