

COUNTY WELL LOCATED
~~Clay~~ **OKTIBBEHA**

WELL NUMBER
1273

CODED

DATE WELL COMPLETED
03-11-92

PERMIT NUMBER
0-379

NAME OF DRILLING FIRM
Mid South Drilling Com.

Carrollton, AL 35447

MISSISSIPPI DEPARTMENT OF ENVIRONMENTAL QUALITY
 Bureau of Land and Water Resources

P. O. Box 10631
 Jackson, MS 39289-0631
 WATER WELL DRILLERS LOG

NAME & MAILING ADDRESS OF LANDOWNER
 A. B. Forte

1008 3rd Ave. North

Columbus, MS 39701

WELL LOCATION: SEC 21 TOWNSHIP 17 RANGE N19 E S25 W

DISTANCE 5 Miles DIRECTION SE of NEAREST TOWN West Point

OTHER LANDMARK

WELL PURPOSE: Home, Irrigation, Municipal, Industrial, Fish Pond, etc.
 hog farm

PUMP DATA

PUMP TYPE (Circle One):
 Submersible, Turbine, Jet, Flowing Well,
 Other (Describe) _____

POWER TYPE (Circle One):
 Electric, Tractor, Diesel, Gasoline, Butane,
 Other (Describe) _____ H/P _____

Pump Capacity (GPM) _____ No. of Stages _____ Setting Depth _____ FT.

PUMP TEST

Well yielded _____ GPM with
 a drawdown of _____ ft.
 after _____ hours of pumping

WELL DATA

Well Depth 440	Casing Diameter (In.) 4x2	Casing Length (Ft.) 340
Type of Casing PVC	Hole Depth 440	Depth to Static Water Level 149

TYPE OF COMPLETION: (Circle One or More):
 Gravel Packed, Underreamed, Telescoped,
 Natural Development, Open Hole, Other _____

Top of Lap Pipe or Reduction in Casing
 255 FEET IF TELESCOPED OR MORE THAN ONE SCREEN: USE BACK PAGE

LOG DATA

TYPE OF LOG RUN (Circle One):
 Electric, Gamma Ray, Density, Sonic, Neutron,
 Other (Describe) No Log Run

Name of Organization Running Log _____

SCREEN DATA

Diameter - Inches 2	Length - Feet 100	Slot Size - Inches .014
Screen Type PVC	Depth to Bottom - Feet	

GEOLOGIC DATA (Office Use Only)

Surface Elev.	Geologic Unit	Unit Thickness	Depth to Top
Subs. SWL	Date	Analysis	Aquifer Test

Driller's Remarks

DESCRIPTION OF FORMATIONS ENCOUNTERED	FROM	TO
clay	0	318
sand	318	367
rock	367	369
sand	369	440

INFORMATION CONTAINED HEREIN IS UNCLASSIFIED

MAR 19 1992

Dept. of Environmental Quality
 Bureau of Land & Water Resources

IF MORE SPACE IS NEEDED, USE BACK

