

MISSISSIPPI DEPARTMENT OF

QUALITY

Office of Land and Water Resources

P. O. Box 10631  
Jackson, MS 39289-0631  
WATER WELL DRILLERS LOG

LOCATED  
Washington

WELL NUMBER 2 CODED

DATE WELL COMPLETED  
2-2-94

PERMIT NUMBER

NAME OF DRILLING FIRM  
Schudco Ltd

NAME & MAILING ADDRESS OF LANDOWNER  
Tribbett Farms

Island rms 38756

WELL LOCATION: SEC 1 TOWNSHIP 17 RANGE 6  
N S E W

DISTANCE 1 Miles DIRECTION E of NEAREST TOWN Tribbett

OTHER LANDMARK

WELL PURPOSE: Home, Irrigation, Municipal, Industrial, Fish Pond, etc.  
Shop

PUMP DATA

PUMP TYPE (Circle One):  
Submersible, Turbine, Jet, Flowing Well,  
Other (Describe)

POWER TYPE (Circle One):  
Electric, Tractor, Diesel, Gasoline, Butane,  
Other (Describe) H/P 1

Pump Capacity (GPM) 18 No. of Stages Setting Depth 105 FT.

PUMP TEST

Well yielded \_\_\_\_\_ GPM with  
a drawdown of \_\_\_\_\_ ft.  
after \_\_\_\_\_ hours of pumping

WELL DATA

Well Depth <u>252</u>	Casing Diameter (In.) <u>4X2</u>	Casing Length (Ft.) <u>232</u>
Type of Casing <u>pvc</u>	Hole Depth <u>280</u>	Depth to Static Water Level <u>24 ft</u>

TYPE OF COMPLETION: (Circle One or More):  
Natural Development, Gravel Packed, Underreamed, Telescoped,  
Open Hole, Other (Describe)

LOG DATA

TYPE OF LOG RUN (Circle One):  
No Log Run, Electric, Gamma Ray, Density, Sonic, Neutron,  
Other (Describe)

Name of Organization Running Log

WELL GROUTED TO A DEPTH OF 10 FEET  
Type Grout (circle one): Cement, Bentonite, or Mix

GEOLOGIC DATA (Office Use Only)

Surface Elev.	Geologic Unit	Unit Thickness	Depth to Top
Subs. SWL	Date	Analysis	Aquifer Test

SCREEN DATA

Diameter - Inches <u>.2</u>	Length - Feet <u>20</u>	Slot Size - Inches <u>.010</u>
Screen Type <u>pvc</u>	Depth to Bottom - Feet <u>252</u>	

Driller's Remarks

DESCRIPTION OF FORMATIONS ENCOUNTERED	FROM	TO	FORMATIONS (Continued)	FROM	TO
<u>Top soil</u>	<u>0</u>	<u>14</u>			
<u>Sand &amp; gravel</u>	<u>14</u>	<u>155</u>			
<u>clay &amp; shell</u>	<u>155</u>	<u>225</u>			
<u>sand</u>	<u>225</u>	<u>254</u>			
<u>clay</u>	<u>254</u>	<u>280</u>			

IF MORE SPACE IS NEEDED, USE BACK

