

0305

MISSISSIPPI DEPARTMENT OF NATURAL RESOURCES

Bureau of Land and Water Resources

COUNTY WELL LOCATED
WILKINSON

WELL NUMBER CODED
No. 1

PERMIT NUMBER

NAME OF DRILLING FIRM
Crosby-Foster Griner Drilling Service, INC.

P.O. Box 10631
Jackson, Mississippi 39209
WATER WELL DRILLERS LOG

DATE WELL COMPLETED
2-9-89

NAME (MAILING ADDRESS) OF LANDOWNER
**Mobil Oil Exploration & Production, SE.
P.O. Box 51108 OCS
Lafayette, La. 70505**

WELL LOCATION: SEC TOWNSHIP RANGE
7 20 1

DISTANCE DIRECTION OF NEAREST TOWN
**5.71 N 1088 W
OF SE/CO.**

OTHER LANDMARK
**Oil Field Rig Supply
@ Centreville, Ms.**

PUMP DATA

PUMP TYPE (Circle One):
Submersible Turbine Jet Flowing Well,
Other (Describe) **S.H.P.**

POWER TYPE (Circle One):
Electric Tractor Diesel Gasoline Butane,
Other (Describe) **230 volt
3 phase**

Pump Capacity (GPM) No. of Stages Setting Depth
75 **—** **—** FT.

PUMP TEST
Well yielded **50** GPM with
a drawdown of **—** ft.
after **3** hours of pumping

WELL DATA

Well Depth Casing Diameter (In.) Casing Length (Ft.)
300' **4"** **280'**

Type of Casing Hole Depth Depth to Static Water Level
steel 300' **178'**

TYPE OF COMPLETION: (Circle One or More):
 Gravel Packed, Underreamed, Telescoped,
 Natural Development, Open Hole, Other
(Describe)

Top of Lap Pipe or Reduction in Casing
FEET IF TELESCOPED OR MORE THAN ONE SCREEN: USE BACK PAGE

LOG DATA

TYPE OF LOG RUN (Circle One): No Log Run,
Electric, Gamma Ray, Density, Sonic, Neutron,
Other (Describe)

Name of Organization Running Log

SCREEN DATA

Diameter - Inches Length - Feet Slot Size - Inches
4" **20'** **1.010**

Screen Type Depth to Bottom - Feet
Stainless Steel 280'-300'

GEOLOGIC DATA (Office Use Only)

Surface Elev.	Geologic Unit	Unit Thickness	Depth to Top
Subs. SWL	Date	Analysis	Aquifer Test

Driller's Remarks

DESCRIPTION OF FORMATIONS ENCOUNTERED	FROM	TO
SAND, p. gravel	0	80
CLAY, SAND	80	300

RECEIVED

FEB 28 1989

Department of Natural Resources
Bureau of Land & Water Resources

**No. 1 WATER
WELL ON
LOCATION**

IF MORE SPACE IS NEEDED, USE BACK

