

WELL SCHEDULE

U. S. DEPT. OF THE INTERIOR

GEOLOGICAL SURVEY

WATER RESOURCES DIVISION

PUNCHED

MASTER CARD

Record by B.D. Source of data Bowc Date 1-71 Map \_\_\_\_\_

State 28 County Amite (or town) 03

Latitude: 31° 05' 28" N Longitude: 090° 04' 21.5" W Sequential number: 1

Lat-long accuracy: 3 T 2 N 5 S, R 5 W, Sec 33, NW SE

Local well number: 0023BD3302NO5E Other number: \_\_\_\_\_ B & M

Local use: 305 Owner or name: FRED WHITE Address: Shady, Miss.

Ownership: County, Fed Gov't, City, Corp or Co, Private, State Agency, Water Dist P

Use of water: (A) Air cond, Bottling, Comm, Dewater, Power, Fire, Dom, Irr, Med, Ind, P S, Rec. (S) (T) (U) (V) (W) (X) (Y) (Z) H

Use of well: (A) Anode, Drain, Seismic, Heat Res, Obs, Oil-gas, Recharge, Test, Unused, Withdraw, Waste, Destroyed. (D) (G) (H) (I) (J) (K) (L) (M) (N) (O) (P) (Q) (R) (S) (T) (U) (V) (W) (X) (Y) (Z) W

DATA AVAILABLE: Well data  Freq. W/L meas.:  Field aquifer char.

Hyd. lab. data:

Qual. water data; type:

Freq. sampling:  Pumpage inventory:  yes no; period: \_\_\_\_\_ 76

Aperture cards:  yes 77

Log data: D 78 79

WELL-DESCRIPTION CARD

SAME AS ON MASTER CARD Depth well: 128 ft Meas. rept accuracy 3

Depth cased: (first perf.) 122 ft Casing type: PL; Diam. 4 in

Finish: (C) porous concrete, (F) gravel w. (perf.), (G) gravel w. (screen), (H) horz. gallery, (I) open end, (J) horz. open end, (K) horz. open end, (L) horz. open end, (M) horz. open end, (N) horz. open end, (O) horz. open end, (P) horz. open end, (Q) horz. open end, (R) horz. open end, (S) horz. open end, (T) horz. open end, (U) horz. open end, (V) horz. open end, (W) horz. open end, (X) horz. open end, (Y) horz. open end, (Z) horz. open end 5

Method: (A) air rot., (B) bored, (C) cable, (D) dug, (E) hyd rot., (F) jetted, (G) air rot., (H) air perc., (I) reverse perc., (J) reverse perc., (K) reverse perc., (L) reverse perc., (M) reverse perc., (N) reverse perc., (O) reverse perc., (P) reverse perc., (Q) reverse perc., (R) reverse perc., (S) reverse perc., (T) reverse perc., (U) reverse perc., (V) reverse perc., (W) reverse perc., (X) reverse perc., (Y) reverse perc., (Z) reverse perc. H

Date Drilled: 9-7-0 Pump intake setting: \_\_\_\_\_ ft

Driller: S+P name address

Lift (type): (A) air, (B) bucket, (C) cent., (D) jet, (E) multiple (cent.), (F) multiple (cent.), (G) multiple (cent.), (H) multiple (cent.), (I) multiple (cent.), (J) multiple (cent.), (K) multiple (cent.), (L) multiple (cent.), (M) multiple (cent.), (N) none, (O) piston, (P) rot., (Q) submerg., (R) submerg., (S) submerg., (T) submerg., (U) submerg., (V) submerg., (W) submerg., (X) submerg., (Y) submerg., (Z) submerg.  Deep  Shallow

Power (type): (A) diesel, (B) elec., (C) gas, (D) gasoline, (E) hand, (F) gas, (G) wind; H.P. 1/2 5 Trans. or meter no.

Descrip. MP \_\_\_\_\_ ft above \_\_\_\_\_ ft below LSD, Alt. MP \_\_\_\_\_

Alt. LSD: \_\_\_\_\_ Accuracy: (source) \_\_\_\_\_ 47

Water Level: 80 ft above MP; Ft below LSD 80 Accuracy: \_\_\_\_\_ 52 D

Date meas: D70 Yield: \_\_\_\_\_ gpm 10 Method determined \_\_\_\_\_ 61

Drawdown: \_\_\_\_\_ ft Accuracy: \_\_\_\_\_ Pumping period \_\_\_\_\_ hrs \_\_\_\_\_ 68

QUALITY OF WATER DATA: Iron \_\_\_\_\_ ppm Sulfate \_\_\_\_\_ ppm Chloride \_\_\_\_\_ ppm Hard. \_\_\_\_\_ ppm 72

Sp. Conduct \_\_\_\_\_ K x 10 6 Temp. \_\_\_\_\_ °F \_\_\_\_\_ ppm Date sampled \_\_\_\_\_ 77 79

Taste, color, etc. \_\_\_\_\_

Well No. 28

