

WELL SCHEDULE

U. S. DEPT. OF THE INTERIOR

GEOLOGICAL SURVEY

WATER RESOURCES DIVISION

MASTER CARD

Record by B.D. Source of data BOWC Date 11-70 Map \_\_\_\_\_

State 28 County (or town) Callahan 07

Latitude: 34 05 06 N Longitude: 08 92 35 1 Sequential number: 1

Lat-long accuracy: 3 T. 11 S. R. 2 Sec. 34 NE, SE, NW

Local well number: A012PB3411NO2W Other number: \_\_\_\_\_ B & M

Local use: 081 Owner or name: \_\_\_\_\_

Owner or name: B. CASTELBERY Address: Bowman, W.D.

Ownership: County, Fed Gov t, City, Corp or Co, Private, State Agency, Water Dist P

Use of water: (A) Air cond, (B) Bottling, (C) Comm, (D) Dewater, (E) Power, (F) Fire, (G) Dom, (H) Irr, (I) Med, (J) Ind, (K) P S, (L) Rec, (M) Stock, (N) Instit, (O) Unused, (P) Repressure, (Q) Recharge, (R) Desal-P S, (S) Desal-other, (T) Other H

Use of well: (A) Anode, (B) Drain, (C) Seismic, (D) Heat Res, (E) Obs, (F) Oil-gas, (G) Recharge, (H) Test, (I) Unused, (J) Withdraw, (K) Waste, (L) Destroyed W

DATA AVAILABLE: Well data  Freq. W/L meas.:  Field aquifer char.

Hyd. lab. data:

Qual. water data; type:

Freq. sampling:  Pumpage inventory: yes  no, period:

Aperture cards:  yes

Log data: D

WELL-DESCRIPTION CARD

SAME AS ON MASTER CARD Depth well: 260 ft Meas. rept accuracy 3

Depth cased: (first perf.) 220 ft Casing type: Pl. Diam. 4 in

Finish: porous concrete, gravel w. (perf.), gravel w. (screen), horiz. gallery, open end, other X

Method: (A) air bored, (B) cab-e, (C) dug, (D) hyd jetted, (E) rot., (F) percussion, (G) rotary, (H) air reverse, (I) trenching, (J) driven, (K) drive wash, (L) other H

Date Drilled: 970 Pump intake setting: \_\_\_\_\_ ft

Driller: Southern name address

Lift (type): (A) air, (B) bucket, (C) cent., (D) jet, (E) multiple, (F) multiple, (G) none, (H) piston, (I) rot, (J) submerg, (K) turb, (L) other  Deep  Shallow

Power (type): diesel, elec. nat gas, gasoline, hand, gas, wind, H.P. 1 Trans. or meter no. 5

Descrip. MP \_\_\_\_\_ ft above LSD, Alt. MP \_\_\_\_\_

Alt. LSD: \_\_\_\_\_ Accuracy: (source) \_\_\_\_\_

Water Level 50 ft above MP; Ft below LSD 50 Accuracy: \_\_\_\_\_

Date meas: 670 Yield: \_\_\_\_\_ gpm Method determined \_\_\_\_\_

Drawdown: \_\_\_\_\_ ft Accuracy: \_\_\_\_\_ Pumping period \_\_\_\_\_ hrs

QUALITY OF WATER DATA: Iron \_\_\_\_\_ ppm Sulfate \_\_\_\_\_ ppm Chloride \_\_\_\_\_ ppm Hard. \_\_\_\_\_ ppm

Sp. Conduct \_\_\_\_\_ K x 10 6 Temp. \_\_\_\_\_ °F Date sampled \_\_\_\_\_

Taste, color, etc. \_\_\_\_\_

PUNCHED and VERIFIED  
ROLLA COMPUTATION BRANCH

Well No. A12

Well No. A12

Latitude-longitude \_\_\_\_\_ N  
S  
d m s d m s

**HYDROGEOLOGIC CARD**

**SAME AS ON MASTER CARD** 03 Section: \_\_\_\_\_  
Province: \_\_\_\_\_

D Drainage Basin: 15G Subbasin: \_\_\_\_\_

(D) (C) (E) (F) (N) (K) (L)  
Topo of well site: depression, stream channel, dunes, flat, hilltop, sink, swamp,  
(Ø) (P) (S) (T) (U) (V)  
offshore, pediment, hillside, terrace, undulating, valley flat \_\_\_\_\_

**MAJOR AQUIFER:** \_\_\_\_\_ system \_\_\_\_\_ series TE \_\_\_\_\_ aquifer, formation, group LW

**Lithology:** \_\_\_\_\_ S **Origin:** \_\_\_\_\_ 2 **Aquifer Thickness:** 40 ft

**Length of well open to:** \_\_\_\_\_ ft 40 **Depth to top of:** \_\_\_\_\_ ft 220

**MINOR AQUIFER:** \_\_\_\_\_ system \_\_\_\_\_ series \_\_\_\_\_ aquifer, formation, group \_\_\_\_\_

**Lithology:** \_\_\_\_\_ S **Origin:** \_\_\_\_\_ \_\_\_\_\_ **Aquifer Thickness:** \_\_\_\_\_ ft

**Length of well open to:** \_\_\_\_\_ ft \_\_\_\_\_ **Depth to top of:** \_\_\_\_\_ ft \_\_\_\_\_

**Intervals Screened:** \_\_\_\_\_

**Depth to consolidated rock:** \_\_\_\_\_ ft \_\_\_\_\_ **Source of data:** \_\_\_\_\_


**Depth to basement:** \_\_\_\_\_ ft \_\_\_\_\_ **Source of data:** \_\_\_\_\_

**Surficial material:** \_\_\_\_\_ **Infiltration characteristics:** \_\_\_\_\_

**Coefficient Trans:** \_\_\_\_\_ gpd/ft \_\_\_\_\_ **Coefficient Storage:** \_\_\_\_\_

**Perm:** \_\_\_\_\_ gpd/ft<sup>2</sup>; Spec cap: \_\_\_\_\_ gpm/ft; Number of geologic cards: \_\_\_\_\_

Red sd 0-20 ft  
Blue clay 20-100  
Blue shell (shale?) 100-220  
Gray sd 220-260



Well No. A12