

WELL SCHEDULE

U. S. DEPT. OF THE INTERIOR

GEOLOGICAL SURVEY

WATER RESOURCES DIVISION

MASTER CARD BSM

1-75

Record by JIS Source of data BOWC Date 3/70 Map

State 28 County (or town) Carroll 08

Latitude: 33 27 55 N Longitude: 09 00 32 0 Sequential number: 1

Lat-long accuracy: 3 T. N. S. R. E. W. Sec 35

Local well number: D006BD3519NO2E Other number: B & M

Local use: 087 Owner or name: 508 Cypress

Owner or name: W L TAYLOR Address: Greenwood, Ms.

Ownership: County, Fed Gov't, City, Corp or Co, Private, State Agency, Water Dist P

Use of Air cond, Bottling, Comm, Dewater, Power, Fire, Dom, Irr, Med, Ind, P S, Rec, WATER:

(S) (T) (U) (V) (W) (X) (Y) (Z) Stock, Instit, Unused, Repressure, Recharge, Desal-P S, Desal-other, Other H

Use of (A) (D) (G) (H) (I) (J) (K) (L) (M) (N) (O) (P) (R) (T) (U) (W) (X) (Z) well: Anode, Drain, Seismic, Heat Res, Obs, Oil-gas, Recharge, Test, Unused, Withdraw, Waste, Destroyed. W

DATA AVAILABLE: Well data  Freq. W/L meas.:  Field aquifer char.

Hyd. lab. data:

Qual. water data; type:

Freq. sampling:  Pumpage inventory: yes  no, period:

Aperture cards:  yes

Log data:

WELL-DESCRIPTION CARD

SAME AS ON MASTER CARD Depth well: 304 ft Meas. rept accuracy 2

Depth cased: 294 ft Casing type: Steel; Diam. 4 in

Finish: porous concrete, gravel w. (perf.), gravel w. (screen), horz. gallery, open end, (P) perf., (S) screen, (T) sd. pt., (W) shored, (X) open hole, (Z) other S

Method (A) air rot, (B) bored, (C) cable, (D) dug, (H) rot., (J) air rot., (P) percussion, (R) rotary, (T) reverse, (U) trenching, (V) driven, (W) drive wash, (Z) other H

Date Drilled: 970 Pump intake setting:  ft

Driller:  name address

Lift (type): (A) air, (B) bucket, (C) cent, (J) jet, (L) multiple, (M) multiple, (N) none, (P) piston, (R) rot, (S) submerg, (T) turb, (Z) other S Deep  Shallow

Power (type): diesel, elec, gas, gasoline, hand, gas, wind; H.P. 3/4 S Trans. or meter no.

Descr. MP  ft above below LSD, Alt. MP

Alt. LSD: 340 Accuracy: (source) 5

Water Level 150 ft above below MP; Ft. below LSD 150 Accuracy: D

Date meas: 270 Yield: 8 gpm Method determined

Drawdown:  ft Accuracy:  Pumping period  hrs

QUALITY OF WATER DATA: Iron  ppm Sulfate  ppm Chloride  ppm Hard.

Sp. Conduct  K x 10<sup>6</sup> Temp.  °F Date sampled

Taste, color, etc.

Well No. D6

Latitude-longitude

N

S

d m s d m s

HYDROGEOLOGIC CARD

SAME AS ON MASTER CARD

Physiographic

Province: \_\_\_\_\_

03 Section: \_\_\_\_\_

D Drainage Basin: \_\_\_\_\_

115J Subbasin: \_\_\_\_\_

Topo of well site: (D) depression, stream channel, dunes, flat, hilltop, sink, swamp, (E) (F) (H) (K) (L) (M) (P) (S) (T) (U) (V) offshore, pediment, hillside, terrace, undulating, valley flat

MAJOR

AQUIFER: \_\_\_\_\_

system

series

TE

28. 29

aquifer, formation, group

WN

30 31

Lithology: \_\_\_\_\_

S Origin: \_\_\_\_\_

3 Aquifer Thickness: \_\_\_\_\_

21 ft

Length of well open to: \_\_\_\_\_ ft

35 37

10 Depth to top of: \_\_\_\_\_ ft

38 40

ft

283

41 43

MINOR

AQUIFER: \_\_\_\_\_

system

series

\_\_\_\_\_

44 45

aquifer, formation, group

\_\_\_\_\_

46 47

Lithology: \_\_\_\_\_

\_\_\_\_\_ Origin: \_\_\_\_\_

\_\_\_\_\_ Aquifer Thickness: \_\_\_\_\_

ft

Length of well open to: \_\_\_\_\_ ft

51 53

\_\_\_\_\_ Depth to top of: \_\_\_\_\_ ft

54 56

ft

\_\_\_\_\_

57 59

Intervals Screened: \_\_\_\_\_

2" SS

Depth to consolidated rock: \_\_\_\_\_ ft

\_\_\_\_\_

60 62

Source of data: \_\_\_\_\_

64

Depth to basement: \_\_\_\_\_ ft

\_\_\_\_\_

65 67

Source of data: \_\_\_\_\_

69

Surficial material: \_\_\_\_\_

\_\_\_\_\_ Infiltration characteristics: \_\_\_\_\_

70 71

72

Coefficient Trans: \_\_\_\_\_ gpd/ft

\_\_\_\_\_

73 75

Coefficient Storage: \_\_\_\_\_

\_\_\_\_\_


76 78

Coefficient Perm: \_\_\_\_\_ gpd/ft<sup>2</sup>; Spec cap: \_\_\_\_\_ gpm/ft; Number of geologic cards: \_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

79



Well No. D6