

WELL SCHEDULE

Elog #166

U. S. DEPT. OF THE INTERIOR

GEOLOGICAL SURVEY

WATER RESOURCES DIVISION

MASTER CARD

Record by WTR Source of data msgs Date 10/70 Map \_\_\_\_\_

State 28 County (or town) Clarke 12

Latitude: 315059N Longitude: 0885348 Sequential number: 1

Lat-long accuracy: 2 T 10 N 9 S, R 9 W Sec 9 SE SE NE

Local well number: P026DA0910N09W Other number: \_\_\_\_\_

Local use: 184166 Owner or name: \_\_\_\_\_

Owner or name: BEAVER DAM WA Address: \_\_\_\_\_

Ownership: County, Fed Gov't, City, Corp or Co, Private, State Agency, Water Dist N

Use of water: (A) Air cond, Bottling, Comm, Dewater, Power, Fire, Dom, Irr, Med, Ind, P S, Rec. (S) Stock, Instit, Unused, Repressure, Recharge, Desal-P S, Desal-other, Other P

Use of well: (A) Anode, Drain, Seismic, Heat Res, Obs, Oil-gas, Recharge, Test, Unused, Withdraw, Waste, Destroyed. (D) (G) (H) (I) (M) (N) (P) (R) (T) (U) (W) (X) (Y) (Z) W

DATA AVAILABLE: Well data  Freq. W/L meas.:  Field aquifer char.

Hyd. lab. data:

Qual. water data; type:

Freq. sampling:  Pumpage inventory:  period: \_\_\_\_\_

Aperture cards:

Log data: Elog 10'-718'

WELL-DESCRIPTION CARD

SAME AS ON MASTER CARD Depth well: 624 ft Meas. 3

Depth cased; (first perf.) 594 ft Casing type: \_\_\_\_\_; Diam. \_\_\_\_\_ in

Finish: porous concrete, gravel w. (perf.), gravel w. (screen), horiz. gallery, open end, perf., screen, sd. pt., shored, open hole, other S

Method Drilled: (A) air rot, (B) bored, (C) cable, (D) dug, (H) hyd rot., (J) jetted, (P) air percussion, (R) reverse, (T) trenching, (V) driven, (W) drive wash, other H

Date Drilled: 970 Pump intake setting: \_\_\_\_\_ ft 290

Driller: Shiner Dalg Sew

Lift (type): (A) air, (B) bucket, (C) cent. jet, (L) multiple, (M) multiple, (N) none, (P) piston, (R) rot, (S) submerg, (T) turb, other S Deep  Shallow

Power (type): nat diesel, elec, gas, gasoline, hand, gas, wind; H.P. 5 Trans. or meter no. T

Descrip. MP \_\_\_\_\_ ft above LSD, Alt. MP \_\_\_\_\_

Alt. LSD: 465 Accuracy: (source) T 4

Water Level: \_\_\_\_\_ ft above MP; \_\_\_\_\_ ft below LSD 208 Accuracy: \_\_\_\_\_ D

Date meas: 070 Yield: \_\_\_\_\_ gpm 30 Method determined

Drawdown: \_\_\_\_\_ ft Accuracy: \_\_\_\_\_ Pumping period: \_\_\_\_\_ hrs \_\_\_\_\_

QUALITY OF WATER DATA: Iron \_\_\_\_\_ ppm Sulfate \_\_\_\_\_ ppm Chloride \_\_\_\_\_ ppm Hard. \_\_\_\_\_ ppm

Sp. Conduct \_\_\_\_\_ K x 10 6 Temp. \_\_\_\_\_ °F \_\_\_\_\_ Date sampled \_\_\_\_\_

Taste, color, etc. \_\_\_\_\_

PUNCHED and VERIFIED  
ROLLA COMPUTATION BRANCH

Well No.

P26

Latitude-longitude \_\_\_\_\_ N S  
d m s d m s

HYDROGEOLOGIC CARD

SAME AS ON MASTER CARD Physiographic Province: \_\_\_\_\_ Section: 03

D Drainage Basin: 1131P Subbasin: \_\_\_\_\_

Topo of well site: (D) depression, stream channel, dunes, flat, hilltop, sink, swamp, (E) (F) (R) (K) (L) (U) (V) offshore, pediment, hillside, terrace, undulating, valley flat \_\_\_\_\_

MAJOR AQUIFER: \_\_\_\_\_ system \_\_\_\_\_ series TE aquifer, formation, group Cockfield \_\_\_\_\_

Lithology: \_\_\_\_\_ Origin: U.S. \_\_\_\_\_ Aquifer Thickness: 3 \_\_\_\_\_ ft

Length of well open to: \_\_\_\_\_ ft 30 Depth to top of: \_\_\_\_\_ ft 520

MINOR AQUIFER: \_\_\_\_\_ system \_\_\_\_\_ series \_\_\_\_\_ aquifer, formation, group \_\_\_\_\_

Lithology: \_\_\_\_\_ Origin: \_\_\_\_\_ Aquifer Thickness: \_\_\_\_\_ ft

Length of well open to: \_\_\_\_\_ ft \_\_\_\_\_ Depth to top of: \_\_\_\_\_ ft \_\_\_\_\_

Intervals Screened: \_\_\_\_\_

Depth to consolidated rock: \_\_\_\_\_ ft \_\_\_\_\_ Source of data: \_\_\_\_\_

Depth to basement: \_\_\_\_\_ ft \_\_\_\_\_ Source of data: \_\_\_\_\_


Surficial material: \_\_\_\_\_ Infiltration characteristics: \_\_\_\_\_

Coefficient Trans: \_\_\_\_\_ gpd/ft \_\_\_\_\_ Coefficient Storage: \_\_\_\_\_

Coefficient Perm: \_\_\_\_\_ gpd/ft<sup>2</sup>; Spec cap: \_\_\_\_\_ gpm/ft; Number of geologic cards: \_\_\_\_\_

broken down with look good on log

586' 4"  
30' 4"



Well No. \_\_\_\_\_

P26