

WELL SCHEDULE 2751

U. S. DEPT. OF THE INTERIOR GEOLOGICAL SURVEY WATER RESOURCES DIVISION

*Same well as R11 & Q20*

PUNCHED and VERIFIED  
ROLLA COMPUTATION BRANCH

MASTER CARD

Record by B.D. Source of data BOWC-? Date 12-70 Map \_\_\_\_\_

State 28 County (or town) Clarke 1 2

Latitude: 31 54 06 N Longitude: 08 07 24 W Sequential number: 4

Lat-long accuracy: 3 T. 1 S. R. 15 Sec 25, SW 1/4, SW 1/4, NE 1/4 B & M

Local well number: Q020CAH2501N15E Other number: \_\_\_\_\_

Local use: 017 Owner or name: \_\_\_\_\_

Owner or name: SOUTH HOUSEHOLD Address: Sardis, MS

Owning: HANSON SEALES

Ownership: (C) County, Fed Gov't, City, Corp or Co, Private, State Agency, Water Dist \_\_\_\_\_ (N) \_\_\_\_\_

Use of water: (A) Air cond, (B) Bottling, (C) Comm, (D) Dewater, (E) Power, (F) Fire, (G) Dom, (H) Irr, (I) Med, (J) P, S, Rec, (K) Stock, (L) Instit, (M) Unused, (N) Repressure, (O) Recharge, (P) Desal-P S, (Q) Desal-other, (R) Other \_\_\_\_\_ (W) \_\_\_\_\_

Use of well: (A) Anode, (B) Drain, (C) Seismic, (D) Heat Res, (E) Obs, (F) Oil-gas, (G) Recharge, (H) Test, (I) Unused, (J) Withdraw, (K) Waste, (L) Destroyed \_\_\_\_\_ (W) \_\_\_\_\_

DATA AVAILABLE: Well data  Freq. W/L meas.:  Field aquifer char.

Hyd. lab. data: \_\_\_\_\_

Qual. water data; type: \_\_\_\_\_ yes \_\_\_\_\_

Freq. sampling: \_\_\_\_\_ Pumpage inventory: no. period: \_\_\_\_\_ yes \_\_\_\_\_

Aperture cards: \_\_\_\_\_

Log data: \_\_\_\_\_

WL 11/29/88  
-23.9'

10/25/89  
-6.00

WELL-DESCRIPTION CARD

SAME AS ON MASTER CARD Depth well: 918 Meas. rept accuracy 3

Depth cased: (first perf.) 510 Casing type: Iron; Diam. 6x4x2 1/2 in 6

Finish: (C) porous concrete, (E) gravel w. (perf.), (G) gravel w. (screen), (H) horiz. gallery, (I) open end, (J) open perf., (K) screen, (L) sd. pt., (M) shored, (N) open hole, (O) other \_\_\_\_\_ (S) \_\_\_\_\_

Method: (A) air bored, (B) cable, (C) dug, (D) hyd rot., (E) jetted, (F) air percussion, (G) reverse, (H) rotary, (I) trenching, (J) driven, (K) drive wash, (L) other \_\_\_\_\_ (W) \_\_\_\_\_

Date Drilled: 969 Pump intake setting: 168 ft \_\_\_\_\_

Driller: Pringles name (L) \_\_\_\_\_ address \_\_\_\_\_

Lift (type): (A) air, (B) bucket, (C) cent, (D) jet, (E) multiple, (F) multiple, (G) none, (H) piston, (I) rot, (J) submerg, (K) turb, (L) other \_\_\_\_\_ (S) \_\_\_\_\_ Deep \_\_\_\_\_ Shallow \_\_\_\_\_

Power (type): (A) diesel, (B) elec, (C) gas, (D) gasoline, (E) hand, (F) gas, (G) wind, (H) H.P. \_\_\_\_\_ (I) \_\_\_\_\_ Trans. or meter no. \_\_\_\_\_

Descrip. MP \_\_\_\_\_ ft above \_\_\_\_\_ below LSD, Alt. MP \_\_\_\_\_

Alt. LSD: 205 Accuracy: (source) \_\_\_\_\_

Water Level: 15 ft above below MP; Ft below LSD 715 Accuracy: \_\_\_\_\_

Date meas: 369 Yield: 180 gpm Method determined \_\_\_\_\_

Drawdown: \_\_\_\_\_ ft Accuracy: \_\_\_\_\_ Pumping period \_\_\_\_\_ hrs \_\_\_\_\_

QUALITY OF WATER DATA: Iron \_\_\_\_\_ ppm Sulfate \_\_\_\_\_ ppm Chloride \_\_\_\_\_ ppm Hard. \_\_\_\_\_ ppm

Sp. Conduct \_\_\_\_\_ K x 10<sup>6</sup> Temp. \_\_\_\_\_ °F Date sampled \_\_\_\_\_

Taste, color, etc. \_\_\_\_\_

BEED CLR  
10/27/80.  
WL = +6.25'  
205'  
+ 6'  
211'

Well No. Q20