

9-185  
(October 1950)

**COPIED**  
UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY  
WATER RESOURCES DIVISION

WELL SCHEDULE

Date 11/15/60, 19\_\_ Field No. \_\_\_\_\_  
Record by B E Warron Office No. F-13  
Source of data MS Namora, LC, 6-F-71 S&B

1: Location: State \_\_\_\_\_ County Coahoma

Map \_\_\_\_\_  
NE 1/4 NW 1/4 sec. 21 T 28 N R 3 E W

2: Owner: City of Clarkdale Address \_\_\_\_\_

Tenant Fletcher Field Address \_\_\_\_\_

Driller Layne-Central Address Memphis

3: Topography \_\_\_\_\_

4: Elevation 168 ft. above \_\_\_\_\_  
below \_\_\_\_\_

5: Type: Dug, drilled, driven, bored, jetted \_\_\_\_\_ 1943

324' 6: Depth: Rept. 150-300' ft. Meas. \_\_\_\_\_ ft.

7: Casing: Diam. 12 1/2 in., to 6 in., Type Brny

Depth \_\_\_\_\_ ft., Finish 30' x 6"

8: Chief Aquifer Sparta Sm 1 From 282 ft. to 321 ft.

Others 232-272; 403-491

9: Water level 24' ft. (rept. \_\_\_\_\_) 1943 above \_\_\_\_\_  
below 154

which is \_\_\_\_\_ ft. above \_\_\_\_\_  
below surface

10: Pump: Type Layne turbine Capacity \_\_\_\_\_ G. M.

Power: Kind \_\_\_\_\_ Horsepower 20?

11: Yield: Flow \_\_\_\_\_ G. M., Pump 330 G. M., Meas., Rept. Est.

Drawdown \_\_\_\_\_ ft. after \_\_\_\_\_ hours pumping \_\_\_\_\_ G. M.

12: Use: Dom., Stock, PS., RR., Ind., Irr., Obs. \_\_\_\_\_

Adequacy, permanence \_\_\_\_\_

13: Quality hard water Temp \_\_\_\_\_ °F.

Taste, odor, color \_\_\_\_\_ Sample Yes \_\_\_\_\_  
No \_\_\_\_\_

Unfit for \_\_\_\_\_

14: Remarks: (Log, Analyses, etc.) Test hole to 1120'

Broken fine sand @ 1089-1113

Layne Memphis has data  
U. S. GOVERNMENT PRINTING OFFICE 16-62891-1

