

WELL SCHEDULE

U. S. DEPT. OF THE INTERIOR

GEOLOGICAL SURVEY

WATER RESOURCES DIVISION

MASTER CARD

Record by WTR Source of data Bowc Date 1/69 Map \_\_\_\_\_

State 35 28 County (or town) Hannegan 24

Latitude: 30<sup>deg</sup> 24<sup>min</sup> 44<sup>sec</sup> N Longitude: 089<sup>degrees</sup> 19<sup>min</sup> 53<sup>sec</sup> W Sequential number: 2

Lat-long accuracy: 1<sup>sec</sup> 13<sup>min</sup> 29<sup>sec</sup> 30 NE W NW

Local well number: J095A03007513W Other number: \_\_\_\_\_ B & M

Local use: 139 Owner or name: \_\_\_\_\_

Owner or name: DALE MORAN Address: Box 216 Rt #2 Pass Christian

Ownership: County, Fed Gov't, City, Corp or Co, Private, State Agency, Water Dist \_\_\_\_\_ P

Use of water: (A) Air cond, (B) Bottling, (C) Comm, (D) Dewater, (E) Power, (F) Fire, (G) Dom, (H) Irr, (I) Med, (J) P S, (K) Rec, (L) Stock, (M) Instat, (N) Unused, (O) Recharge, (P) Desal-P S, (Q) Desal-other, \_\_\_\_\_ A

Use of well: (A) Anode, (B) Drain, (C) Seismic, (D) Heat Res, (E) Obs, (F) Oil-gas, (G) Recharge, (H) Test, (I) Unused, (J) Withdraw, (K) Waste, (L) Destroyed, \_\_\_\_\_ W

DATA AVAILABLE: Well data  Freq. W/L meas.:  Field aquifer char.

Hyd. lab. data: \_\_\_\_\_

Qual. water data; type: \_\_\_\_\_

Freq. sampling: \_\_\_\_\_ Pumpage inventory:  yes  no; period: \_\_\_\_\_

Aperture cards: \_\_\_\_\_ yes  no

Log data: \_\_\_\_\_ D

WELL-DESCRIPTION CARD

SAME AS ON MASTER CARD Depth well: \_\_\_\_\_ ft 216 Meas. rept \_\_\_\_\_ 3

Depth cased; (first perf.) \_\_\_\_\_ ft 211 Casing type: \_\_\_\_\_; Diam. \_\_\_\_\_ in \_\_\_\_\_ 2

Finish: (C) porous concrete, (F) gravel w. concrete, (G) gravel w. (perf.), (H) horz. (screen), (I) open end, (J) gallery, (K) other \_\_\_\_\_ 3

Method Drilled: (A) air bored, (B) cable, (C) dug, (D) hyd, (E) jetted, (F) air rot., (G) reverse, (H) percussion, (I) rotary, (J) trenching, (K) driven, (L) drive wash, (M) other \_\_\_\_\_ H

Date Drilled: 10/68 9:6:8 Pump intake setting: \_\_\_\_\_ ft \_\_\_\_\_ 38

Driller: Penton Well Sew.

Lift (type): (A) air, (B) bucket, (C) cent, (D) jet, (E) multiple, (F) multiple, (G) none, (H) piston, (I) rot, (J) submerg, (K) turb, (L) other \_\_\_\_\_ Deep \_\_\_\_\_ Shallow \_\_\_\_\_ 40

Power (type): diesel, elec, gas, gasoline, hand, gas, wind; H.P. \_\_\_\_\_ Trans. or meter no. \_\_\_\_\_

Descrip. MP \_\_\_\_\_ ft above \_\_\_\_\_ below LSD, Alt. MP \_\_\_\_\_

Alt. LSD: \_\_\_\_\_ Accuracy: (source) \_\_\_\_\_ 47

Water Level \_\_\_\_\_ ft above \_\_\_\_\_ below MP; Ft \_\_\_\_\_ below LSD \_\_\_\_\_ Accuracy: \_\_\_\_\_ 52 D

Date meas: \_\_\_\_\_ Yield: \_\_\_\_\_ gpm \_\_\_\_\_ Method determined \_\_\_\_\_ 51

Drawdown: \_\_\_\_\_ ft \_\_\_\_\_ Accuracy: \_\_\_\_\_ Pumping period \_\_\_\_\_ hrs \_\_\_\_\_ 58

QUALITY OF WATER DATA: Iron \_\_\_\_\_ ppm \_\_\_\_\_ Sulfate \_\_\_\_\_ ppm \_\_\_\_\_ Chloride \_\_\_\_\_ ppm \_\_\_\_\_ Hard. \_\_\_\_\_ ppm \_\_\_\_\_ 72

Sp. Conduct \_\_\_\_\_ K x 10 \_\_\_\_\_ Temp. \_\_\_\_\_ °F \_\_\_\_\_ Date sampled \_\_\_\_\_ 76

Taste, color, etc. \_\_\_\_\_

PUNCHED and VERIFIED  
ROLLA COMPUTATION BRANCH

Well No.

J 95

Well No. \_\_\_\_\_

J95

Latitude-longitude: \_\_\_\_\_  
d m s N S

HYDROGEOLOGIC CARD

SAME AS ON MASTER CARD Physiographic Province: \_\_\_\_\_ Section: 03

Drainage Basin: D 13S Subbasin: \_\_\_\_\_

Topo of well site: (D) depression, stream channel, dunes, flat, hilltop, sink, swamp, (C) offshore, pediment, hillside, terrace, undulating, valley flat (E) (F) (R) (K) (L) (P) (S) (T) (U) (V)

MAJOR AQUIFER: system \_\_\_\_\_ series TP aquifer, formation, group GF

Lithology: \_\_\_\_\_ Origin: 3 Aquifer Thickness: 759 ft

Length of well open to: \_\_\_\_\_ ft Depth to top of: \_\_\_\_\_ ft 157

MINOR AQUIFER: system \_\_\_\_\_ series \_\_\_\_\_ aquifer, formation, group \_\_\_\_\_

Lithology: \_\_\_\_\_ Origin: \_\_\_\_\_ Aquifer Thickness: \_\_\_\_\_ ft

Length of well open to: \_\_\_\_\_ ft Depth to top of: \_\_\_\_\_ ft

Intervals Screened: \_\_\_\_\_


Depth to consolidated rock: \_\_\_\_\_ ft Source of data: \_\_\_\_\_

Depth to basement: \_\_\_\_\_ ft Source of data: \_\_\_\_\_

Surficial material: \_\_\_\_\_ Infiltration characteristics: \_\_\_\_\_

Coefficient Trans: \_\_\_\_\_ gpd/ft Coefficient Storage: \_\_\_\_\_

Coefficient Perm: \_\_\_\_\_ gpd/ft<sup>2</sup>; Spec cap: \_\_\_\_\_ gpm/ft; Number of geologic cards: \_\_\_\_\_



5 1/2 miles  
E of Kilm

Surface Clay	0	24
Sand	24	42
Brown Clay	42	65
Blue Clay	65	157
Fine Sand	157	195
Grey Sand	195	216

Well No. \_\_\_\_\_

J95

