

WELL SCHEDULE

U. S. DEPT. OF THE INTERIOR

GEOLOGICAL SURVEY

WATER RESOURCES DIVISION

PUNCHED

MASTER CARD

Record by WR Source of data Bowc Date 1/69 Map \_\_\_\_\_

State 28 County Harrison (or town) 24

Latitude: 30° 26' 55" N Longitude: 08° 8' 53" W Sequential number: 1

Lat-long accuracy: 4 T 7 S R 9 Sec. 9 NW SE

Local well number: M287BD0907509W Other well number: \_\_\_\_\_

Local use: 088 Owner or name: THOMAS LAING Address: Bochman Rd Biloxi

Ownership: County (C), Fed Gov't (F), City (M), Corp or Co (N), Private (P), State Agency (S), Water Dist (W) P

Use of water: Air cond, Bottling, Comm, Dewater, Power, Fire, Dom, Irr, Med, Ind, P S, Rec, Stock, Instit, Unused, Repressure, Recharge, Desal-P S, Desal-other, Other W

Use of well: Anode, Drain, Seismic, Heat Res, Obs, Oil-gas, Recharge, Test, Unused, Withdraw, Waste, Destroyed. W

DATA AVAILABLE: Well data  Freq. W/L meas:  Field aquifer char:

Hyd. lab. data: \_\_\_\_\_

Qual. water data; type: \_\_\_\_\_

Freq. sampling: \_\_\_\_\_ Pumpage inventory:  no. period: \_\_\_\_\_

Aperture/cards: \_\_\_\_\_

Log data: \_\_\_\_\_

WELL-DESCRIPTION CARD

SAME AS ON MASTER CARD Depth well: 120 ft Meas. rept. accuracy 3

Depth cased: 1110 ft Casing type: \_\_\_\_\_; Diam. in 2

Finish: porous concrete, gravel w. (perf.), gravel w. (screen), horiz. gallery, open end, perf., screen, sd. pt., shored, open hole, other 5

Method: (A) air bored, (B) cable, (C) dug, (D) hyd jetted, (E) rot., (F) percussion, (G) rotary, (H) reverse, (I) trenching, (J) driven, (K) drive wash, (L) other 1

Date Drilled: 8/68 9/68 Pump intake setting: \_\_\_\_\_ ft

Driller: Switzer address \_\_\_\_\_

Lift (type): (A) air, (B) bucket, (C) cent, (D) jet, (E) multiple, (F) none, (G) piston, (H) rot, (I) submerg, (J) turb, (K) other J Deep  Shallow

Power (type): nat, LP, diesel, elec, gas, gasoline, hand, gas, wind; H.P. 1/2 Trans. or meter no. 5

Descrip. MP \_\_\_\_\_ ft above LSD, Alt. MP \_\_\_\_\_

Alt. LSD: 20 Accuracy: (source) 3

Water Level: \_\_\_\_\_ ft above MP; \_\_\_\_\_ ft below LSD Accuracy: 36

Date meas: 8/68 Yield: 9 gpm Method determined: 1

Drawdown: \_\_\_\_\_ ft Accuracy: \_\_\_\_\_ Pumping period: \_\_\_\_\_ hrs

QUALITY OF WATER DATA: Iron \_\_\_\_\_ ppm Sulfate \_\_\_\_\_ ppm Chloride \_\_\_\_\_ ppm Hard. \_\_\_\_\_ ppm

Sp. Conduct K x 10<sup>6</sup> \_\_\_\_\_ Temp. \_\_\_\_\_ °F Date sampled \_\_\_\_\_

Taste, color, etc. \_\_\_\_\_

Well No.

M 287


Well No. \_\_\_\_\_

M 287

Latitude-longitude \_\_\_\_\_

HYDROGEOLOGIC CARD

SAME AS ON MASTER CARD      Physiographic Province: 03 Section: \_\_\_\_\_  
 Drainage Basin: D      Subbasin: 135       \_\_\_\_\_  
 Top of well site: (D) depression, stream channel, dunes, flat, hilltop, sink, swamp, (E) offshore, pediment, hillside, terrace, undulating, valley flat: F  
 MAJOR AQUIFER: TP      GP      aquifer, formation, group  
 Lithology: US      Origin: 3      Aquifer Thickness: >18 ft  
 Length of well open to: \_\_\_\_\_ ft      Depth to top of: 103 ft  
 MINOR AQUIFER: \_\_\_\_\_      \_\_\_\_\_      aquifer, formation, group  
 Lithology: \_\_\_\_\_      Origin: \_\_\_\_\_      Aquifer Thickness: \_\_\_\_\_ ft  
 Length of well open to: \_\_\_\_\_ ft      Depth to top of: \_\_\_\_\_ ft  
 Intervals Screened: \_\_\_\_\_  
 Depth to consolidated rock: \_\_\_\_\_ ft      Source of data: \_\_\_\_\_  
 Depth to basement: \_\_\_\_\_ ft      Source of data: \_\_\_\_\_  
 Surficial material: \_\_\_\_\_      Infiltration characteristics: \_\_\_\_\_  
 Coefficient Trans: \_\_\_\_\_ gpd/ft      Coefficient Storage: \_\_\_\_\_  
 Coefficient Perm: \_\_\_\_\_ gpd/ft<sup>2</sup>; Spec cap: \_\_\_\_\_      gpm/ft; Number of geologic cards: \_\_\_\_\_



2 miles N  
of Belton

Well No. M 287