

SITE ID-302147089103701  
FORM 9-1642  
(1-68)

Well No. 057

393C

WELL SCHEDULE

U. S. DEPT. OF THE INTERIOR

GEOLOGICAL SURVEY

WATER RESOURCES DIVISION

MASTER CARD

Record by WTO Source of data Bowc Date 3/69 Map \_\_\_\_\_

State 28 County (or town) Hannover 24

Latitude: 30214.7N Longitude: 0891037 Sequential number: 1

Lat-long accuracy: 4 Sec 10 Other well number: 0578A1008S12W B & M number: \_\_\_\_\_

Local use: 024 Owner of name: RH BAUGH #17

Owner or name: RH BAUGH Address: RH Box 54A

Ownership: County, Fed Gov't, City, Corp or Co, Private, State Agency, Water Dist P

Use of Air cond, Bottling, Comm, Dewater, Power, Fire, Dom, Irr, Med, Ind, P S, Rec, water: W

Use of well: Anode, Drain, Seismic, Heat Res, Obs, Oil-gas, Recharge, Test, Unused, Withdraw, Waste, Destroyed. W

DATA AVAILABLE: Well data  Freq. W/L meas.:  Field aquifer char:

Hyd. lab. data:

Qual. water data; type:

Freq. sampling:  Pumpage inventory:  yes no; period: \_\_\_\_\_

Aperture cards:  yes

Log data: D

WELL-DESCRIPTION CARD

SAME AS ON MASTER CARD Depth well: 438 Meas. rept accuracy 3

Depth cased; (first perf.): 428 Casing type: \_\_\_\_\_; Diam. in 2

Finish: porous gravel w. gravel w. horiz. open perf., screen, sd. pt., shored, open hole, concrete, (perf.), (screen), gallery, end, other 5

Method Drilled: (A) bored, (B) cable, (C) dug, (D) hyd jetted, (H) rot., (J) air percussion, (P) reverse, (R) rotary, (T) trenching, (V) driven, (W) drive wash, other 4

Date Drilled: 8/63 9/63 Pump intake setting: \_\_\_\_\_ ft 38

Driller: Sutter

Lift (type): (A) air, (B) bucket, (C) cent., (J) jet, (L) multiple, (M) multiple, (N) none, (P) piston, (R) rot., (S) submerg, (T) turb., other  Deep  Shallow 40

Power (type): diesel, elec, gas, gasoline, hand, gas, wind; H.P.  Trans. or meter no. \_\_\_\_\_

Descrip. MP \_\_\_\_\_ ft above \_\_\_\_\_ ft below LSD, Alt. MP \_\_\_\_\_

Alt. LSD: 20 Accuracy: (source) 3

Water Level \_\_\_\_\_ ft above MP; \_\_\_\_\_ ft below LSD Accuracy: \_\_\_\_\_

Date meas: 8/63 Yield: \_\_\_\_\_ gpm Method determined \_\_\_\_\_

Drawdown: \_\_\_\_\_ ft Accuracy: \_\_\_\_\_ Pumping period \_\_\_\_\_ hrs

QUALITY OF WATER DATA: Iron \_\_\_\_\_ ppm Sulfate \_\_\_\_\_ ppm Chloride \_\_\_\_\_ ppm Hard. \_\_\_\_\_ ppm

Sp. Conduct \_\_\_\_\_ K x 10<sup>6</sup> Temp. \_\_\_\_\_ °F Date sampled \_\_\_\_\_

Taste, color, etc. \_\_\_\_\_

PUNCHED

Well No. 057

Well No. 057

Latitude-longitude N  
S  
 d m s d m s

**HYDROGEOLOGIC CARD**

**SAME AS ON MASTER CARD** Physiographic Province: 03 Section: \_\_\_\_\_

D Drainage Basin: 1135 Subbasin: \_\_\_\_\_

Topo of well site: (D) depression, stream channel, dunes, flat, hilltop, sink, swamp, (E) (F) (R) (L) (U) (V) offshore, pediment, hillside, terrace, undulating, valley flat F

**MAJOR AQUIFER:** system \_\_\_\_\_ series TP aquifer, formation, group GF

Lithology: \_\_\_\_\_ Origin: 3 Aquifer Thickness: >28 ft

Length of well open to: \_\_\_\_\_ ft Depth to top of: \_\_\_\_\_ ft

**MINOR AQUIFER:** system \_\_\_\_\_ series \_\_\_\_\_ aquifer, formation, group \_\_\_\_\_

Lithology: \_\_\_\_\_ Origin: \_\_\_\_\_ Aquifer Thickness: \_\_\_\_\_ ft

Length of well open to: \_\_\_\_\_ ft Depth to top of: \_\_\_\_\_ ft

**Intervals Screened:**

Depth to consolidated rock: \_\_\_\_\_ ft Source of data: \_\_\_\_\_


Depth to basement: \_\_\_\_\_ ft Source of data: \_\_\_\_\_

Surficial material: \_\_\_\_\_ Infiltration characteristics: \_\_\_\_\_

Coefficient Trans: \_\_\_\_\_ gpd/ft Coefficient Storage: \_\_\_\_\_

Coefficient Perm: \_\_\_\_\_ gpd/ft<sup>2</sup>; Spec cap: \_\_\_\_\_ gpm/ft; Number of geologic cards: \_\_\_\_\_

Randy Clay	35	35
Clay	10	45
sand	45	90
Clay	26	116
sand	13	129
Clay	81	210
Clay - sand streak	84	294
sand	26	320
Clay	90	410
sand	28	438



Well No. 057

