

WRD Exp. (GW)  
April 1966

Abandoned per Frank Jordan P114  
Well No. 8/17/92

WELL SCHEDULE

U. S. DEPT. OF THE INTERIOR

GEOLOGICAL SURVEY

WATER RESOURCES DIVISION

PUNCHED and VERIFIED  
ROLLA COMPUTATION BRANCH

MASTER CARD

Record by TNS Source of data SUPT Date 4/9/58 Map \_\_\_\_\_

State 28 County (or town) Jksn 30

Latitude: 30<sup>deg</sup> 21<sup>min</sup> 56<sup>sec</sup> N Longitude: 088<sup>degrees</sup> 33<sup>min</sup> 48<sup>sec</sup> W Sequential number: 1

Lat-long accuracy: 4 T. 8 S, R 6 W, Sec 5, \_\_\_\_\_, \_\_\_\_\_, \_\_\_\_\_, NW B & M

Local well number: P114 B0508 S06W Other number: \_\_\_\_\_

Local use: 088 859 Owner or name: \_\_\_\_\_

Owner or name: QUAKER OATS CO Address: \_\_\_\_\_

Ownership: County, Fed Gov't, City, Corp or Co, Private, State Agency, Water Dist \_\_\_\_\_ N

Use of water: (A) Air cond, (B) Bottling, (C) Comm, (D) Dewater, (E) Power, (F) Fire, (G) Dom, (H) Irr, (I) Med, (J) P S, (K) Rec, (L) Stock, (M) Instit, (N) Unused, (O) Repressure, (P) Recharge, (Q) Desal-P S, (R) Desal-other, (S) Other \_\_\_\_\_ N

Use of well: (A) Anode, (B) Drain, (C) Seismic, (D) Heat Res, (E) Obs, (F) Oil-gas, (G) Recharge, (H) Test, (I) Unused, (J) Withdraw, (K) Waste, (L) Destroyed \_\_\_\_\_ W

DATA AVAILABLE: Well data  Freq. W/L meas.: \_\_\_\_\_ Field aquifer char.

Hyd. lab. data: \_\_\_\_\_

Qual. water data; type: \_\_\_\_\_

Freq. sampling: \_\_\_\_\_ Pumpage inventory: \_\_\_\_\_ yes no, period: \_\_\_\_\_

Aperture cards: \_\_\_\_\_ yes \_\_\_\_\_

Log data: \_\_\_\_\_

WELL-DESCRIPTION CARD

SAME AS ON MASTER CARD Depth well: \_\_\_\_\_ ft 300 Meas. rept accuracy \_\_\_\_\_ 6

Depth cased: \_\_\_\_\_ ft \_\_\_\_\_ Casing type: \_\_\_\_\_; Diam. \_\_\_\_\_ in \_\_\_\_\_ 8

Finish: (A) porous concrete, (B) gravel w. (perf.), (C) gravel w. (screen), (D) horiz. gallery, (E) open end, (F) perf., (G) screen, (H) sd. pt., (I) shored, (J) open hole, (K) other \_\_\_\_\_ H

Method Drilled: (A) air rot, (B) bored, (C) cable, (D) dug, (E) hyd jetted, (F) air rot., (G) percussion, (H) rotary, (I) reverse, (J) trenching, (K) driven, (L) wash, (M) other \_\_\_\_\_ 4

Date Drilled: 952 Pump intake setting: \_\_\_\_\_ ft \_\_\_\_\_ 38

Driller: SWITZER address \_\_\_\_\_

Lift (type): (A) air, (B) bucket, (C) cent, (D) jet, (E) multiple, (F) multiple, (G) none, (H) piston, (I) rot, (J) submerg, (K) turb, (L) other \_\_\_\_\_ T Deep \_\_\_\_\_ Shallow \_\_\_\_\_

Power (type): (A) diesel, (B) elec, (C) gas, (D) gasoline, (E) hand, (F) gas, (G) wind; H.P. 40  Trans. or meter no. \_\_\_\_\_

Descrip. MP \_\_\_\_\_ ft above \_\_\_\_\_ below LSD. Alt. MP \_\_\_\_\_

Alt. LSD: \_\_\_\_\_ 5 Accuracy: (source) \_\_\_\_\_ 3

Water Level \_\_\_\_\_ ft above \_\_\_\_\_ below MP; \_\_\_\_\_ ft above \_\_\_\_\_ below LSD Accuracy: \_\_\_\_\_ 52

Date meas: \_\_\_\_\_ Yield: \_\_\_\_\_ gpm 372 Method determined \_\_\_\_\_ 4

Drawdown: \_\_\_\_\_ ft 52 Accuracy: \_\_\_\_\_ Pumping period \_\_\_\_\_ hrs \_\_\_\_\_ 9

QUALITY OF WATER DATA: Iron \_\_\_\_\_ ppm Sulfate \_\_\_\_\_ ppm Chloride \_\_\_\_\_ ppm Hard. \_\_\_\_\_ ppm

Sp. Conduct \_\_\_\_\_ K x 10<sup>6</sup> \_\_\_\_\_ Temp. \_\_\_\_\_ °F \_\_\_\_\_ Date sampled \_\_\_\_\_

Taste, color, etc. \_\_\_\_\_

Well No.

P114

