

WRD Exp. (GW)  
April 1966

Well No. 661

U. S. DEPT. OF THE INTERIOR

# WELL SCHEDULE REPLACEMENT

WATER RESOURCES DIVISION

PUMPED TO FILL

### MASTER CARD

Record by T.N. Sittows Source of data \_\_\_\_\_ Date \_\_\_\_\_ Map \_\_\_\_\_

State 28 County (or town) 34

Latitude: 31 deg 40 min 22 sec N Longitude: 08 degrees 90 min 73 sec W Sequential number: 1

Lat-long accuracy: 3 T. 8 S. R. 11 Sec 8 SW & NW & NW

Local well number: G061B808N11A Other number: #12 B & M

Local use: 064 Owner of name: \_\_\_\_\_

Owner or name: MASONITE CORP. Address: \_\_\_\_\_

Ownership: County, Fed Gov't, City, Corp or Co, Private, State Agency, Water Dist N

Use of water: (A) Air cond, Bottling, Comm, Dewater, Power, Fire, Dom, Irr, Med, Ind, P S, Rec, (S) Stock, Instit, Unused, Repressure, Recharge, Desal-P S, Desal-other, Other N

Use of well: (A) Anode, Drain, Seismic, Heat Res, Obs, Oil-gas, Recharge, Test, Unused, Withdraw, Waste, Destroyed W

DATA AVAILABLE: Well data  Freq. W/L meas.:  Field aquifer char.

Hyd. lab. data:

Qual. water data; type:

Freq. sampling:  Pumpage inventory: yes  no, period:

Aperture cards:  yes

Log data:

### WELL-DESCRIPTION CARD

SAME AS ON MASTER CARD Depth well: 220 ft Meas. rept accuracy 6

Depth cased: (first perf.) 166 ft Casing type: \_\_\_\_\_; Diam. 12 in

Finish: (C) porous concrete, (F) gravel w. (perf.), (G) gravel w. (screen), (H) horiz. open perf., (Ø) open perf., (P) screen, (S) sd. pt., (T) shored, (W) open hole, (X) other S

Method: (A) air bored, (B) cable, (C) dug, (D) hyd jetted, (H) rot., (J) percussion, (P) air reverse, (R) trenching, (T) driven, (V) wash, (W) other A

Date Drilled: 9.6.1 Pump intake setting: \_\_\_\_\_ ft

Driller: LAYNE CENTRAL name address

Lift (type): (A) air, (B) bucket, (C) cent, (J) jet, (L) multiple, (M) multiple, (N) none, (P) piston, (R) rot, (S) submerg, (T) turb, (Z) other 7 Deep  Shallow

Power (type): diesel, elec, gas, gasoline, hand, gas, wind, H.P.  Trans. or meter no. \_\_\_\_\_

Descrip. MP \_\_\_\_\_ ft above below LSD, Alt. MP \_\_\_\_\_

Alt. LSD: 230 Accuracy: (source) 4

Water Level: \_\_\_\_\_ ft above below MP; Ft below LSD 145 Accuracy: \_\_\_\_\_

Date meas: 9.6.1 Yield: \_\_\_\_\_ gpm 297 Method determined \_\_\_\_\_

Drawdown: \_\_\_\_\_ ft Accuracy: \_\_\_\_\_ Pumping period \_\_\_\_\_ hrs

QUALITY OF WATER DATA: Iron \_\_\_\_\_ ppm Sulfate \_\_\_\_\_ ppm Chloride \_\_\_\_\_ ppm Hard. \_\_\_\_\_ ppm

Sp. Conduct \_\_\_\_\_ K x 10 6 Temp. \_\_\_\_\_ °F Date sampled \_\_\_\_\_

Taste, color, etc. \_\_\_\_\_

Well No. 661

Well No. G61

REQUIREMENT

Latitude-longitude

N  
S  
d m s d m s

HYDROGEOLOGIC CARD

SAME AS ON MASTER CARD  Physiographic Province: 03 Section: \_\_\_\_\_

Drainage Basin: D 130 Subbasin: \_\_\_\_\_

Topo of well site: (D) depression, stream channel, dunes, flat, hilltop, sink, swamp, (E) (F) (H) (K) (L) (O) (P) (S) (T) (U) (V) offshore, pediment, hillside, terrace, undulating, valley flat 7

MAJOR AQUIFER: system \_\_\_\_\_ series TM aquifer, formation, group CA

Lithology: US Origin: 3 Aquifer Thickness: \_\_\_\_\_ ft  
Length of well open to: \_\_\_\_\_ ft 54 Depth to top of: \_\_\_\_\_ ft

MINOR AQUIFER: system \_\_\_\_\_ series \_\_\_\_\_ aquifer, formation, group \_\_\_\_\_

Lithology: \_\_\_\_\_ Origin: \_\_\_\_\_ Aquifer Thickness: \_\_\_\_\_ ft  
Length of well open to: \_\_\_\_\_ ft \_\_\_\_\_ Depth to top of: \_\_\_\_\_ ft

Intervals Screened: \_\_\_\_\_

Depth to consolidated rock: \_\_\_\_\_ ft \_\_\_\_\_ Source of data: \_\_\_\_\_


Depth to basement: \_\_\_\_\_ ft \_\_\_\_\_ Source of data: \_\_\_\_\_

Surficial material: \_\_\_\_\_ Infiltration characteristics: \_\_\_\_\_

Coefficient Trans: \_\_\_\_\_ gpd/ft \_\_\_\_\_ Coefficient Storage: \_\_\_\_\_

Coefficient Perm: \_\_\_\_\_ gpd/ft<sup>2</sup>; Spec cap: \_\_\_\_\_ gpm/ft; Number of geologic cards: \_\_\_\_\_

Formerly pumped @ 500 gpm 1970 pump



Well No. G61