

Latitude-longitude N  
S  
d m s d m s

HYDROGEOLOGIC CARD

SAME AS ON MASTER CARD

Physiographic Province: \_\_\_\_\_

03  
20 21

Section: \_\_\_\_\_

D  
22

Drainage Basin: \_\_\_\_\_

1151F  
23 25

Subbasin: \_\_\_\_\_

Topo of well site: (D) depression, stream channel, dunes, flat, hilltop, sink, swamp, (E) offshore, pediment, hillside, terrace, undulating, valley flat (F) (G) (H) (I) (J) (K) (L) (M) (N) (O) (P) (Q) (R) (S) (T) (U) (V) \_\_\_\_\_ 27

MAJOR AQUIFER: \_\_\_\_\_ system \_\_\_\_\_ series \_\_\_\_\_ 28 29 \_\_\_\_\_ aquifer, formation, group \_\_\_\_\_ 30 31

Lithology: \_\_\_\_\_ 32 33 Origin: \_\_\_\_\_ 34 Aquifer Thickness: 39 ft

Length of well open to: \_\_\_\_\_ 35 37 ft \_\_\_\_\_ 38 40 Depth to top of: \_\_\_\_\_ 41 43 ft 30

MINOR AQUIFER: \_\_\_\_\_ system \_\_\_\_\_ series \_\_\_\_\_ 44 45 \_\_\_\_\_ aquifer, formation, group \_\_\_\_\_ 46 47

Lithology: \_\_\_\_\_ 48 49 Origin: \_\_\_\_\_ 50 Aquifer Thickness: \_\_\_\_\_ ft

Length of well open to: \_\_\_\_\_ 51 53 ft \_\_\_\_\_ 54 56 Depth to top of: \_\_\_\_\_ 57 59 ft

Intervals Screened: 1-4'


Depth to consolidated rock: \_\_\_\_\_ ft \_\_\_\_\_ 60 63 Source of data: \_\_\_\_\_ 64

Depth to basement: \_\_\_\_\_ ft \_\_\_\_\_ 65 68 Source of data: \_\_\_\_\_ 69

Surficial material: \_\_\_\_\_ 70 71 Infiltration characteristics: \_\_\_\_\_ 72

Coefficient Trans: \_\_\_\_\_ gpd/ft \_\_\_\_\_ 73 75 Coefficient Storage: \_\_\_\_\_ 76 78

Coefficient Perm: \_\_\_\_\_ gpd/ft<sup>2</sup>; Spec cap: \_\_\_\_\_ gpm/ft; Number of geologic cards: \_\_\_\_\_ 79



Well No.

J  
14

WELL SCHEDULE  
GEOLOGICAL SURVEY

U. S. DEPT. OF THE INTERIOR

WATER RESOURCES DIVISION

**PUNCHED**  
**JAN 3 1974**

MASTER CARD

Record by P. D. Source of data P. D. C. Date 6-71 Map \_\_\_\_\_

State 38 County (or town) Salayette 36

Latitude: 34<sup>1</sup>19<sup>2</sup>53<sup>3</sup>11<sup>4</sup> N Longitude: 08<sup>12</sup>94<sup>15</sup>03<sup>18</sup> 0  
 Lat-long accuracy: 5<sup>10</sup> T 9<sup>20</sup> R 5<sup>30</sup> Sec 2<sup>40</sup>

Local well number: 052<sup>35</sup> 0204<sup>40</sup> 505W<sup>45</sup> Other number: \_\_\_\_\_ B & M

Local use: 052<sup>35</sup> Owner or name: JIM TATUM<sup>36</sup> Address: Saylor<sup>41</sup>

Ownership: (C) County, Fed Gov't, (F) City, Corp or Co, Private, State Agency, Water Dist \_\_\_\_\_ (P) \_\_\_\_\_ (S) \_\_\_\_\_ (W) \_\_\_\_\_

Use of water: (A) Air cond, Bottling, Comm, Dewater, Power, Fire, Dom, Irr, Med, Ind, P S, Rec, (B) \_\_\_\_\_ (C) \_\_\_\_\_ (D) \_\_\_\_\_ (E) \_\_\_\_\_ (F) \_\_\_\_\_ (H) \_\_\_\_\_ (I) \_\_\_\_\_ (M) \_\_\_\_\_ (N) \_\_\_\_\_ (P) \_\_\_\_\_ (R) \_\_\_\_\_ (S) \_\_\_\_\_ (T) \_\_\_\_\_ (U) \_\_\_\_\_ (V) \_\_\_\_\_ (W) \_\_\_\_\_ (X) \_\_\_\_\_ (Y) \_\_\_\_\_ (Z) \_\_\_\_\_

Use of well: (A) Anode, Drain, Seismic, Heat Res, Obs, Oil-gas, Recharge, Test, Unused, Withdraw, Waste, Destroyed, (D) \_\_\_\_\_ (G) \_\_\_\_\_ (H) \_\_\_\_\_ (I) \_\_\_\_\_ (J) \_\_\_\_\_ (K) \_\_\_\_\_ (L) \_\_\_\_\_ (M) \_\_\_\_\_ (N) \_\_\_\_\_ (O) \_\_\_\_\_ (P) \_\_\_\_\_ (Q) \_\_\_\_\_ (R) \_\_\_\_\_ (S) \_\_\_\_\_ (T) \_\_\_\_\_ (U) \_\_\_\_\_ (V) \_\_\_\_\_ (W) \_\_\_\_\_ (X) \_\_\_\_\_ (Y) \_\_\_\_\_ (Z) \_\_\_\_\_

DATA AVAILABLE: Well data  Freq. W/L meas.:  Field aquifer char.

Hyd. lab. data: \_\_\_\_\_

Qual. water data; type: \_\_\_\_\_

Freq. sampling: \_\_\_\_\_ Pumpage inventory:  yes  no; period: \_\_\_\_\_

Aperture cards: \_\_\_\_\_ yes  no

Log data: \_\_\_\_\_

WELL-DESCRIPTION CARD

SAME AS ON MASTER CARD Depth well: \_\_\_\_\_ ft 69 Meas. 3

Depth cased; (first perf.) \_\_\_\_\_ ft 63 Casing type: \_\_\_\_\_; Diam. \_\_\_\_\_ in 2

Finish: porous concrete, (perf.), (screen), gravel w. gravel w. (screen), horiz. open gallery, end, (H) \_\_\_\_\_ (I) \_\_\_\_\_ (J) \_\_\_\_\_ (K) \_\_\_\_\_ (L) \_\_\_\_\_ (M) \_\_\_\_\_ (N) \_\_\_\_\_ (O) \_\_\_\_\_ (P) \_\_\_\_\_ (Q) \_\_\_\_\_ (R) \_\_\_\_\_ (S) \_\_\_\_\_ (T) \_\_\_\_\_ (U) \_\_\_\_\_ (V) \_\_\_\_\_ (W) \_\_\_\_\_ (X) \_\_\_\_\_ (Y) \_\_\_\_\_ (Z) \_\_\_\_\_

Method Drilled: (A) air bored, (B) cable, (C) dug, (D) hyd jetted, (E) rot., (F) air percussion, (G) rotary, (H) \_\_\_\_\_ (I) \_\_\_\_\_ (J) \_\_\_\_\_ (K) \_\_\_\_\_ (L) \_\_\_\_\_ (M) \_\_\_\_\_ (N) \_\_\_\_\_ (O) \_\_\_\_\_ (P) \_\_\_\_\_ (Q) \_\_\_\_\_ (R) \_\_\_\_\_ (S) \_\_\_\_\_ (T) \_\_\_\_\_ (U) \_\_\_\_\_ (V) \_\_\_\_\_ (W) \_\_\_\_\_ (X) \_\_\_\_\_ (Y) \_\_\_\_\_ (Z) \_\_\_\_\_

Date Drilled: 9:6:72 Pump intake setting: \_\_\_\_\_ ft \_\_\_\_\_

Driller: H. J. H.

Lift (type): (A) air, (B) bucket, (C) cent., (D) jet, (E) multiple, (F) multiple, (G) none, (H) piston, (I) rot., (J) submerg, (K) turb, (L) other, (M) \_\_\_\_\_ (N) \_\_\_\_\_ (O) \_\_\_\_\_ (P) \_\_\_\_\_ (Q) \_\_\_\_\_ (R) \_\_\_\_\_ (S) \_\_\_\_\_ (T) \_\_\_\_\_ (U) \_\_\_\_\_ (V) \_\_\_\_\_ (W) \_\_\_\_\_ (X) \_\_\_\_\_ (Y) \_\_\_\_\_ (Z) \_\_\_\_\_ Deep  Shallow

Power (type): (A) diesel, (B) elec, (C) gas, (D) gasoline, (E) hand, (F) gas, (G) wind, (H) H.P., (I) \_\_\_\_\_ (J) \_\_\_\_\_ (K) \_\_\_\_\_ (L) \_\_\_\_\_ (M) \_\_\_\_\_ (N) \_\_\_\_\_ (O) \_\_\_\_\_ (P) \_\_\_\_\_ (Q) \_\_\_\_\_ (R) \_\_\_\_\_ (S) \_\_\_\_\_ (T) \_\_\_\_\_ (U) \_\_\_\_\_ (V) \_\_\_\_\_ (W) \_\_\_\_\_ (X) \_\_\_\_\_ (Y) \_\_\_\_\_ (Z) \_\_\_\_\_ Trans. or meter no. \_\_\_\_\_

Descrip. MP \_\_\_\_\_ ft above \_\_\_\_\_ below LSD, Alt. MP \_\_\_\_\_

Alt. LSD: \_\_\_\_\_ Accuracy: \_\_\_\_\_

Water Level: 21 ft above MP; 21 ft below LSD Accuracy: \_\_\_\_\_

Date meas: 8:6:72 Yield: \_\_\_\_\_ gpm 12 Method determined \_\_\_\_\_

Drawdown: \_\_\_\_\_ ft Accuracy: \_\_\_\_\_ Pumping period: \_\_\_\_\_ hrs \_\_\_\_\_

QUALITY OF WATER DATA: Iron \_\_\_\_\_ ppm Sulfate \_\_\_\_\_ ppm Chloride \_\_\_\_\_ ppm Hard. \_\_\_\_\_ ppm

Sp. Conduct \_\_\_\_\_ K x 10 6 Temp. \_\_\_\_\_ °F Date sampled \_\_\_\_\_

Taste, color, etc. \_\_\_\_\_

Well No.

J 14