

# FILE COPY

Well No. C99

JUL 02 1975

PUNCHED

U. S. DEPT. OF THE INTERIOR

GEOLOGICAL SURVEY

WATER RESOURCES DIVISION

NOV 21 1972

### MASTER CARD

Water Level  
Datg  
11/15/82  
WL = 6.85  
8-20-87  
8.78

Record by BE Wason Source of data hand Date 8-25-72 Map California

State Miss County Howard (or town) 44

Latitude: 33° 33' 54" N Longitude: 088° 27' 05" W Sequential number: 1

Lat-long accuracy: 20 Sec 19 SE SE SE

Local well number: C099DD-917518W Other number: 1000 B16-H

Local use: 051 Owner or name: USCE 115A

Owner or name: USCE NP 115A Address: \_\_\_\_\_

Ownership: County, Red Gov't, City, Corp or Co, Private, State Agency, Water Dist F

Use of Air cond, Bottling, Comm, Dewater, Power, Fire, Dom, Irr, Med, Ind, P S, Rec, water: U

Stock, Instit, Unused, Repressure, Recharge, Desal-P S, Desal-other, Other U

Use of well: Anode, Drain, Seismic, Heat Res, Obs, Oil-gas, Recharge, Test, Unused, Withdraw, Waste, Destroyed. U

DATA AVAILABLE: Well data  Freq. W/L meas:  Field-aquifer char:

Hyd. lab. data:

Qual. water data; type: USGS 6/75 C

Freq. sampling: U Pumpage inventory: no. period:

Aperture cards:  yes

Log data: E-log 2-156 D E

### WELL-DESCRIPTION CARD

SAME AS ON MASTER CARD Depth well: 84 Meas. 1

Depth cased: 74 Casing type: PVC ; Diam. 4

Finish: porous concrete, gravel w. (perf.), (screen), gallery, end, horiz. open perf., screen, sd. pt., shored, open hole, other S

Method Drilled: air bored, cable, dug, hyd jetted, air reverse trenching, driven, drive-rot, percussion, rotary, other U

Date Drilled: 8-25-72 Pump intake setting: 972 ft 36

Driller: USCE Parks

Lift (type): air, bucket, cent, jet, multiple, multiple, none, piston, rot, submerg, turb, other  Deep  Shallow 40

Power (type): diesel, elec, gas, gasoline, hand, gas, wind; H.P.  Trans. or meter no. 41

Descrip. MP 172 ft above below LSD, Alt. MP 172 Accuracy: 10' topo 4

Alt. LSD: 172 Accuracy: 10' topo 4

Water Level 6.57 ft above below MP, Ft below LSD 5 Accuracy: A

Date meas: 072 Yield: 0 gpm Method determined 61

Drawdown: 0 ft Accuracy: 0 Pumping period 0 hrs 68

QUALITY OF WATER DATA: Iron 0 ppm Sulfate 0 ppm Chloride 0 ppm Hard. 0 ppm

Sp. Conduct 95 K x 10<sup>6</sup> 1 Temp. 17.5 °F Date sampled 6-5-75 675

Taste, color, etc. pH = 6.5; partial 10-1972.

Well No.

Well No. \_\_\_\_\_

Latitude-longitude \_\_\_\_\_

N  
S

HYDROGEOLOGIC CARD

**FINISHED**  
MASTER CARD  
NOV 15 1954

Physiographic Province: \_\_\_\_\_

WELL SCHEDULE **303**

Section: \_\_\_\_\_

Drainage Basin: **D**

Subbasin: **13L**

\_\_\_\_\_

Top of depression, stream channel, dunes, flac, hilltop, sink, swamp, \_\_\_\_\_  
well site: (D) (C) (E) (F) (H) (K) (L) \_\_\_\_\_

offshore, pediment, hillside, terrace, undulating valley floor \_\_\_\_\_

MAJOR AQUIFER: **K3** \_\_\_\_\_ **E2** \_\_\_\_\_

Lithology: **6S** Origin: **6** Thickness: \_\_\_\_\_

Length of well open to: \_\_\_\_\_ ft Depth to top of: \_\_\_\_\_ ft

MINOR AQUIFER: \_\_\_\_\_

Lithology: \_\_\_\_\_ Origin: \_\_\_\_\_ Thickness: \_\_\_\_\_

Length of well open to: \_\_\_\_\_ ft Depth to top of: \_\_\_\_\_ ft

Intervals Screened: \_\_\_\_\_

Depth to consolidated rock: \_\_\_\_\_ ft Source of data: \_\_\_\_\_

Depth to basement: \_\_\_\_\_ ft Source of data: \_\_\_\_\_

Surficial material: \_\_\_\_\_ Infiltration characteristics: \_\_\_\_\_

Coefficient Trans: \_\_\_\_\_ gpd/ft Coefficient Storage: \_\_\_\_\_

Coefficient Perm: \_\_\_\_\_ gpd/ft<sup>2</sup>; Spec cap: \_\_\_\_\_ gpm/ft; Number of geologic cards: \_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

8-24 72  
0-14 clay  
14-34 sand & gravel  
34-60 clay  
60-89 clay & sand  
80-170 clay

