

WELL SCHEDULE

U. S. DEPT. OF THE INTERIOR

GEOLOGICAL SURVEY

WATER RESOURCES DIVISION

MASTER CARD

Record by J. Shell Source of data BOWC Date 11/68 Map \_\_\_\_\_

State 28 County (or town) Marion 46

Latitude: 311045N Longitude: 0895552 Sequential number: 1

Lat-long accuracy: 2 T. 30 S. R. 19 Sec 31, NE, SE, SW

Local well number: K0210C3103N19W Other number: \_\_\_\_\_

Local use: 196 Owner or name: W. THORNTON Address: Foxworth

Ownership: County, Fed Gov't, City, Corp or Co, Private, State Agency, Water Dist P

Use of water: (S) (T) (U) (V) (W) (X) (Y) (Z) H

Use of well: (A) (D) (G) (H) (I) (J) (K) (L) (M) (N) (O) (P) (R) (T) (U) (V) (W) (X) (Z) W

DATA AVAILABLE: Well data  Freq. W/L meas.:  Field aquifer char.

Hyd. lab. data: \_\_\_\_\_

Qual. water data; type: \_\_\_\_\_

Freq. sampling: \_\_\_\_\_ Pumpage inventory:  yes  no, period: \_\_\_\_\_

Aperture cards: \_\_\_\_\_ yes

Log data: \_\_\_\_\_ D

WELL-DESCRIPTION CARD

SAME AS ON MASTER CARD Depth well: \_\_\_\_\_ ft 86 Meas. 3

Depth cased: \_\_\_\_\_ ft 83 Casing type: \_\_\_\_\_; Diam. \_\_\_\_\_ in \_\_\_\_\_

Finish: porous concrete, gravel w. (perf.), (screen), gravel w. (screen), gallery, end, horiz. open perf., screen, sd. pt., shored, open hole, other S

Method: (A) (B) (C) (D) (H) (J) (P) (R) (T) (V) (W) (Z) H

Drilled: air bored, cable, dug, hyd jetted, rot., air reverse trenching, driven, drive wash, percussion, rotary, other H

Date Drilled: 967 Pump intake setting: \_\_\_\_\_ ft \_\_\_\_\_

Driller: \_\_\_\_\_ name \_\_\_\_\_ address \_\_\_\_\_

Lift (type): (A) (B) (C) (J) multiple, multiple, none, piston, rot, submerg, turb, other  Deep  Shallow 40

Power (type): diesel, elec nat gas, gasoline, hand, gas, wind; H.P. 1  Trans. or meter no. 5

Descrip. MP \_\_\_\_\_ ft above \_\_\_\_\_ below LSD. Alt. MP \_\_\_\_\_

Alt. LSD: \_\_\_\_\_ Accuracy: \_\_\_\_\_

Water Level: 15 ft above MP; Ft below LSD 15 Accuracy: \_\_\_\_\_

Date meas: 667 Yield: \_\_\_\_\_ gpm \_\_\_\_\_ Method determined \_\_\_\_\_

Drawdown: \_\_\_\_\_ ft \_\_\_\_\_ Accuracy: \_\_\_\_\_ Pumping period \_\_\_\_\_ hrs \_\_\_\_\_

QUALITY OF WATER DATA: Iron \_\_\_\_\_ ppm Sulfate \_\_\_\_\_ ppm Chloride \_\_\_\_\_ ppm Hard. \_\_\_\_\_ ppm

Sp. Conduct \_\_\_\_\_ K x 10 6 Temp. \_\_\_\_\_ °F \_\_\_\_\_ Date sampled \_\_\_\_\_

Taste, color, etc. \_\_\_\_\_

Well No. K 21

Well No. 521

Latitude-longitude \_\_\_\_\_ N  
S  
d m s d m s

HYDROGEOLOGIC CARD

SAME AS ON MASTER CARD 03 Physiographic Province: \_\_\_\_\_ Section: \_\_\_\_\_

0 Drainage Basin: 131V Subbasin: \_\_\_\_\_

Topo of well site: (D) depression, stream channel, dunes, flat, hilltop, sink, swamp, (E) (F) (H) (K) (L) (O) (P) (S) (T) (U) (V) offshore, pediment, hillside, terrace, undulating, valley flat \_\_\_\_\_

MAJOR AQUIFER: \_\_\_\_\_ system \_\_\_\_\_ series TP \_\_\_\_\_ aquifer, formation, group CI

Lithology: \_\_\_\_\_ 45 Origin: \_\_\_\_\_ 2 Aquifer Thickness: 36 ft

Length of well open to: \_\_\_\_\_ ft 3 Depth to top of: \_\_\_\_\_ ft 50

MINOR AQUIFER: \_\_\_\_\_ system \_\_\_\_\_ series \_\_\_\_\_ aquifer, formation, group \_\_\_\_\_

Lithology: \_\_\_\_\_ 48 Origin: \_\_\_\_\_ 50 Aquifer Thickness: \_\_\_\_\_ ft

Length of well open to: \_\_\_\_\_ ft \_\_\_\_\_ Depth to top of: \_\_\_\_\_ ft \_\_\_\_\_

Intervals Screened: .010 Stainless Steel 83-86'

Depth to consolidated rock: \_\_\_\_\_ ft \_\_\_\_\_ Source of data: \_\_\_\_\_


Depth to basement: \_\_\_\_\_ ft \_\_\_\_\_ Source of data: \_\_\_\_\_

Surficial material: \_\_\_\_\_ 70-71 Infiltration characteristics: \_\_\_\_\_

Coefficient Trans: \_\_\_\_\_ gpd/ft 73 Coefficient Storage: \_\_\_\_\_ 78

Coefficient Perm: \_\_\_\_\_ gpd/ft<sup>2</sup>; Spec cap: \_\_\_\_\_ gpm/ft; Number of geologic cards: \_\_\_\_\_

6 mi. S/E of Kokomu.



Well No. 521