

### WELL SCHEDULE

U. S. DEPT. OF THE INTERIOR

GEOLOGICAL SURVEY

WATER RESOURCES DIVISION

#### MASTER CARD

Record by WTO-PEG Source of data Driller Date 6-1967 Map \_\_\_\_\_

State Miss 28 County (or town) Marion 46

Latitude: 31 14 04 N 19 Longitude: 08 95 03 5 Sequential number: 1

Lat-long accuracy: 2 T, 3 S, R, 14 W, Sec 7, SE 1/4, NW 1/4, SE 1/4

Local well number: L0268D0703N14E Other well number: \_\_\_\_\_

Local use: \_\_\_\_\_ Owner or name: Sands Motel

Owner or name: SANDS MOTEL Address: Columbia

Ownership: County, Fed Gov't, City, Corp or Co, Private, State Agency, Water Dist \_\_\_\_\_ P

Use of water: (A) Air cond, Bottling, Comm, Dewater, Power, Fire, (H) Irr, Med, Ind, P S, Rec, (I) Dom, (M) Stock, (N) Instit, (P) Unused, (R) Recharge, (S) Desal-P S, (T) Desal-other, (U) Other \_\_\_\_\_ H

Use of well: (A) Anode, (D) Drain, (G) Seismic, (H) Heat Res, (I) Obs, (P) Oil-gas, (R) Recharge, (T) Test, (U) Unused, (W) Withdraw, (X) Waste, (Z) Destroyed \_\_\_\_\_ W

DATA AVAILABLE: Well data  Freq. W/L meas.: NONE N Field aquifer char. \_\_\_\_\_

Hyd. lab. data: \_\_\_\_\_

Qual. water data; type: \_\_\_\_\_

Freq. sampling: NONE  Pumpage inventory: yes  no, period: \_\_\_\_\_

Aperture cards: \_\_\_\_\_

Log data: \_\_\_\_\_

#### WELL-DESCRIPTION CARD

SAME AS ON MASTER CARD Depth well: 738 ft Meas. 738 Meas. accuracy \_\_\_\_\_

Depth cased: 723 ft Casing type: Steel; Diam. 6 in \_\_\_\_\_

Finish: (C) porous concrete, (F) gravel w. (perf.), (G) gravel w. (screen), (H) horiz. gallery, (I) open end, (J) horz. gallery, (K) open end, (L) screen, (M) perf., (N) sd. pt., (O) shored, (P) open hole, (Q) other \_\_\_\_\_ S

Method Drilled: (A) air rot, (B) bored, (C) cable, (D) dug, (E) hyd rot, (F) jetted, (G) air percussion, (H) reverse, (I) rotary, (J) trenching, (K) driven, (L) drive wash, (M) other \_\_\_\_\_ H

Date Drilled: June 1967 9:67 Pump intake setting: \_\_\_\_\_ ft \_\_\_\_\_

Driller: Dean Griner, Columbia Miss

Lift (type): (A) air, (B) bucket, (C) cent, (D) jet, (E) multiple, (F) multiple, (G) none, (H) piston, (I) rot, (J) submerg, (K) turb, (L) other \_\_\_\_\_ S Deep \_\_\_\_\_ Shallow \_\_\_\_\_

Power (type): (A) diesel, (B) elec, (C) gas, (D) gasoline, (E) hand, (F) gas, (G) wind, (H) H.P., (I) \_\_\_\_\_ 3 Trans. or meter no. \_\_\_\_\_ T

Descrip. MP \_\_\_\_\_ ft above \_\_\_\_\_ below LSD, Alt. MP \_\_\_\_\_

Alt. LSD: 140 EST 140 Accuracy: \_\_\_\_\_

Water Level: + ft above \_\_\_\_\_ below MP; Ft below LSD \_\_\_\_\_ Accuracy: \_\_\_\_\_

Date meas: 667 Yield: \_\_\_\_\_ gpm \_\_\_\_\_ Method determined \_\_\_\_\_

Drawdown: \_\_\_\_\_ ft Accuracy: \_\_\_\_\_ Pumping period \_\_\_\_\_ hrs \_\_\_\_\_

QUALITY OF WATER DATA: Iron \_\_\_\_\_ ppm Sulfate \_\_\_\_\_ ppm Chloride \_\_\_\_\_ ppm Hard. \_\_\_\_\_ ppm

Sp. Conduct \_\_\_\_\_ K x 10<sup>6</sup> Temp. \_\_\_\_\_ °F Date sampled \_\_\_\_\_

Taste, color, etc. \_\_\_\_\_

PUNCHED and VERIFIED  
ROLLA COMPUTATION BRANCH

Well No. 1

L26

