

WELL SCHEDULE

U. S. DEPT. OF THE INTERIOR

GEOLOGICAL SURVEY

WATER RESOURCES DIVISION

PURCHASED AND VERIFIED  
FOLLOWING STATION BRANCH

MASTER CARD

Record by W.T. Oakley Source of data Tom Rankin Date 8-8-66 Map \_\_\_\_\_

State Miss County 28 (or town) Marion 46

Latitude: 31° 00' 42" N Longitude: 089° 47' 22" W Sequential number: 1

Lat-long accuracy: 3 T. 1 S. R. 14 Sec 33, SE t., NE t.

Local well number: 0006DA3301N14E Other number: \_\_\_\_\_ B & M

Local use: \_\_\_\_\_ Owner or name: Tom Rankin

Owner or name: TOM RANKIN Address: Sandy Hook

Ownership: County, Fed Gov't, City, Corp or Co, Private, State Agency, Water Dist \_\_\_\_\_ P

Use of water: (A) Air cond, Bottling, Comm, Dewater, Power, Fire, Irr, Med, Ind, P S, Rec, Stock, Instit, Unused, Repressure, Recharge, Desal-P S, Desal-other, Other \_\_\_\_\_ H

Use of well: (A) Anode, Drain, Seismic, Heat Res, Obs, Oil-gas, Recharge, Test, Unused, Withdraw, Waste, Destroyed. \_\_\_\_\_ W

DATA AVAILABLE: Well data \_\_\_\_\_ Freq. W/L meas.: \_\_\_\_\_ Field aquifer char. \_\_\_\_\_

Hyd. lab. data: \_\_\_\_\_

Qual. water data; type: \_\_\_\_\_

Freq. sampling: \_\_\_\_\_ Pumpage inventory: \_\_\_\_\_

Aperture cards: \_\_\_\_\_

Log data: \_\_\_\_\_

Flam stops & may be caused in 11/19/81

WELL-DESCRIPTION CARD

SAME AS ON MASTER CARD Depth well: 1,185 ft Meas. accuracy \_\_\_\_\_ 6

Depth cased: \_\_\_\_\_ Casing type: oil field tubing; Diam. 3 in \_\_\_\_\_ 3

Finish: (C) porous concrete, (F) gravel w. (screen), (G) gravel w. (gallery), (H) horiz. open end, (I) perf., (J) screen, sd. pt., (K) shored, (L) open hole, (M) other \_\_\_\_\_ P

Method: (A) air rot, (B) bored, (C) cable, (D) dug, (E) hyd. rot., (F) jetted, (G) air percussion, (H) reverse, (I) rotary, (J) trenching, (K) driven, (L) wash, (M) other \_\_\_\_\_ H

Date Drilled: 1962 9.6.2 Pump intake setting: \_\_\_\_\_ ft \_\_\_\_\_

Driller: Dean Griner Columbia

Lift (type): (A) air, (B) bucket, (C) cent, (D) jet, (E) multiple, (F) multiple, (G) (cent.), (H) (turb.), (I) (turb.), (J) (turb.), (K) (turb.), (L) (turb.), (M) (turb.), (N) (turb.), (O) (turb.), (P) (turb.), (Q) (turb.), (R) (turb.), (S) (turb.), (T) (turb.), (U) (turb.), (V) (turb.), (W) (turb.), (X) (turb.), (Y) (turb.), (Z) (turb.) \_\_\_\_\_ N Deep \_\_\_\_\_ Shallow \_\_\_\_\_

Power (type): (A) diesel, (B) elec, (C) gas, (D) gasoline, (E) hand, (F) gas, (G) wind; H.P. \_\_\_\_\_ Trans. or meter no. \_\_\_\_\_

Descrip. MP \_\_\_\_\_ ft above \_\_\_\_\_ ft below LSD, Alt. MP \_\_\_\_\_

Alt. LSD: \_\_\_\_\_ Accuracy: \_\_\_\_\_

Water Level: + ft above MP; \_\_\_\_\_ ft below LSD \_\_\_\_\_ Accuracy: \_\_\_\_\_

Date meas: 8-8-66 8.6.6 Yield: \_\_\_\_\_ gpm \_\_\_\_\_ Method determined \_\_\_\_\_

Drawdown: \_\_\_\_\_ ft \_\_\_\_\_ Accuracy: \_\_\_\_\_ Pumping period \_\_\_\_\_ hrs \_\_\_\_\_

QUALITY OF WATER DATA: Iron \_\_\_\_\_ ppm Sulfate \_\_\_\_\_ ppm Chloride \_\_\_\_\_ ppm Hard. \_\_\_\_\_ ppm

Sp. Conduct \_\_\_\_\_ K x 10<sup>6</sup> \_\_\_\_\_ Temp. 75 °F \_\_\_\_\_ Date sampled \_\_\_\_\_ 866

Taste, color, etc. Field Sp. Conduct = 20

Well No. Q6

