

WELL SCHEDULE

U. S. DEPT. OF THE INTERIOR

GEOLOGICAL SURVEY

WATER RESOURCES DIVISION

MASTER CARD

Record by J.S. Source of data BOWC Date 1/70 Map \_\_\_\_\_

State 28 County (or town) Marshall 47

Latitude: 34<sup>deg</sup> 53<sup>min</sup> 32<sup>sec</sup> N Longitude: 089<sup>degrees</sup> 22<sup>min</sup> 31<sup>sec</sup> W Sequential number: 1

Lat-long accuracy: 3<sup>sec</sup> T S, R \_\_\_\_\_ W, Sec: 23 \_\_\_\_\_

Local well number: 6006BD2302S02W Other number: \_\_\_\_\_ B & H

Local use: 125 \_\_\_\_\_

Owner or name: THOMAS BYRD Address: Rt #1, Lamar, Mo.

Ownership: County, Fed Gov't, City, Corp or Co, Private, State Agency, Water Dist \_\_\_\_\_ P

Use of water: (A) Air cond, Bottling, Comm, Dewater, Power, Fire, Dom, Irr, Med, Ind, P S, Rec, (S) \_\_\_\_\_ (T) \_\_\_\_\_ (U) \_\_\_\_\_ (V) \_\_\_\_\_ (W) \_\_\_\_\_ (X) \_\_\_\_\_ (Y) \_\_\_\_\_ (Z) \_\_\_\_\_ H

Use of well: (A) Anode, Drain, Seismic, Heat Res, Obs, Oil-gas, Recharge, Test, Unused, Withdraw, Waste, Destroyed. (D) \_\_\_\_\_ (G) \_\_\_\_\_ (H) \_\_\_\_\_ (I) \_\_\_\_\_ (J) \_\_\_\_\_ (K) \_\_\_\_\_ (L) \_\_\_\_\_ (M) \_\_\_\_\_ (N) \_\_\_\_\_ (O) \_\_\_\_\_ (P) \_\_\_\_\_ (R) \_\_\_\_\_ (T) \_\_\_\_\_ (U) \_\_\_\_\_ (W) \_\_\_\_\_ (X) \_\_\_\_\_ (Z) \_\_\_\_\_ W

DATA AVAILABLE: Well data  Freq. W/L meas:  Field aquifer char.

Hyd. lab. data: \_\_\_\_\_

Qual. water data; type: \_\_\_\_\_

Freq. sampling: \_\_\_\_\_ Pumpage inventory: \_\_\_\_\_ yes no; period: \_\_\_\_\_

Aperture cards: \_\_\_\_\_ yes D

Log data: \_\_\_\_\_ D

WELL-DESCRIPTION CARD

SAME AS ON MASTER CARD Depth well: \_\_\_\_\_ ft 180 Meas. rept accuracy \_\_\_\_\_ 3

Depth cased (first perf.): \_\_\_\_\_ ft 176 Casing type: Plastic; Diam. \_\_\_\_\_ in \_\_\_\_\_ 4

Finish: porous concrete, gravel w. concrete, (perf.), (screen), gravel w. (screen), horiz. gallery, end, (H) open perf., (S) screen, sd. pt., shored, open hole, other \_\_\_\_\_ S

Method: (A) air bored, (B) cable, (C) dug, (D) hyd jetted, (E) air reverse, (F) trenching, (G) driven, (H) drive rot., (I) percussive, (J) rotary, (K) wash, other \_\_\_\_\_ H

Date Drilled: 9.6.9 Pump intake setting: \_\_\_\_\_ ft \_\_\_\_\_ 38

Driller: \_\_\_\_\_ name \_\_\_\_\_ address \_\_\_\_\_

Lift (type): (A) air, (B) bucket, (C) cent, (D) jet, (E) multiple, (F) multiple, (G) none, (H) piston, (I) rot, (J) submerg, (K) turb, (L) other \_\_\_\_\_ Deep \_\_\_\_\_ Shallow \_\_\_\_\_ 40

Power (type): diesel, elec, gas, gasoline, hand, gas, wind; H.P. \_\_\_\_\_ 1/2 Trans. or meter no. \_\_\_\_\_ S

Descrip. MP \_\_\_\_\_ ft above \_\_\_\_\_ below LSD, Alt. MP \_\_\_\_\_

Alt. LSD: \_\_\_\_\_ Accuracy: (source) \_\_\_\_\_ 47

Water Level: 140 ft above below MP; Ft below LSD 140 Accuracy: \_\_\_\_\_ D

Date meas: D.6.9 Yield: \_\_\_\_\_ gpm \_\_\_\_\_ 10 Method determined \_\_\_\_\_ 61

Drawdown: \_\_\_\_\_ ft \_\_\_\_\_ Accuracy: \_\_\_\_\_ Pumping period \_\_\_\_\_ hrs \_\_\_\_\_ 68

QUALITY OF WATER DATA: Iron \_\_\_\_\_ ppm \_\_\_\_\_ Sulfate \_\_\_\_\_ ppm \_\_\_\_\_ Chloride \_\_\_\_\_ ppm \_\_\_\_\_ Hard. \_\_\_\_\_ ppm \_\_\_\_\_ 72

Sp. Conduct \_\_\_\_\_ K x 10<sup>6</sup> \_\_\_\_\_ Temp. \_\_\_\_\_ °F \_\_\_\_\_ Date sampled \_\_\_\_\_ 77 79

Taste, color, etc. \_\_\_\_\_

PUMPED

Well No.

G 6

Well No. G 6

Latitude-longitude N  
S  
d m s d m s

**HYDROGEOLOGIC CARD**

SAME AS ON MASTER CARD Physiographic Province: \_\_\_\_\_ 03 Section: \_\_\_\_\_

D Drainage Basin: 15E Subbasin:

Topo of well site: (D) depression, stream channel, dunes, flat, hilltop, sink, swamp, (C) (E) (P) (H) (K) (L) (φ) (P) (S) (T) (U) (V) offshore, pediment, hillside, terrace, undulating, valley flat 27

MAJOR AQUIFER: \_\_\_\_\_ system \_\_\_\_\_ series \_\_\_\_\_ aquifer, formation, group \_\_\_\_\_ 28 29 30 31

Lithology: \_\_\_\_\_ Origin: \_\_\_\_\_ Aquifer Thickness: 20 ft 32 33 34

Length of well open to: \_\_\_\_\_ ft 4 Depth to top of: \_\_\_\_\_ ft 160 35 37 38 40 41 43

MINOR AQUIFER: \_\_\_\_\_ system \_\_\_\_\_ series \_\_\_\_\_ aquifer, formation, group \_\_\_\_\_ 44 45 46 47

Lithology: \_\_\_\_\_ Origin: \_\_\_\_\_ Aquifer Thickness: \_\_\_\_\_ ft 48 49 50

Length of well open to: \_\_\_\_\_ ft \_\_\_\_\_ Depth to top of: \_\_\_\_\_ ft \_\_\_\_\_ 51 53 54 56 57 59

Intervals Screened: 4" Gravel Pack


Depth to consolidated rock: \_\_\_\_\_ ft \_\_\_\_\_ Source of data: \_\_\_\_\_ 60 63 64

Depth to basement: \_\_\_\_\_ ft \_\_\_\_\_ Source of data: \_\_\_\_\_ 65 68 69

Surficial material: \_\_\_\_\_ Infiltration characteristics: \_\_\_\_\_ 70 71 72

Coefficient Trans: \_\_\_\_\_ gpd/ft \_\_\_\_\_ Coefficient Storage: \_\_\_\_\_ 73 75 76 78

Coefficient Perm: \_\_\_\_\_ gpd/ft<sup>2</sup>; Spec cap: \_\_\_\_\_ gpm/ft; Number of geologic cards: \_\_\_\_\_ 79



Well No.

G 6