

**PUNCHED**

**WELL SCHEDULE**

U. S. DEPT. OF THE INTERIOR

GEOLOGICAL SURVEY

WATER RESOURCES DIVISION

**MASTER CARD**

**MAR 11 1973**

Record by Parsons Source of data Orls Date 1-24-57 Map \_\_\_\_\_

State 28 County (or town) 48

Latitude: 34° 02' 25" N Longitude: 088° 42' 58" W Sequential number: 7

Lat-long accuracy: 3 T 12 S R 6 Sec 18 SW NW

Local well number: A009CB1812506E Other number: \_\_\_\_\_

Local use: \_\_\_\_\_ Owner or name: CLAUD SMITH Address: \_\_\_\_\_

Ownership: County, Fed Gov't, City, Corp or Co, Private, State Agency, Water Dist P

Use of water: (A) Air cond, Bottling, Comm, Dewater, Power, Fire, Dom, Irr, Med, Ind, P S, Rec, (S) Stock, Instit, Unused, Reppure, Recharge, Desal-P S, Desal-other, Other H

Use of well: (A) Anode, Drain, Seismic, Heat Res, Obs, Oil-gas, Recharge, Test, Unused, Withdraw, Waste, Destroyed. W

DATA AVAILABLE: Well data  Freq. W/L meas.:  Field aquifer char.

Hyd. lab. data: \_\_\_\_\_

Qual. water data; type: \_\_\_\_\_

Freq. sampling: \_\_\_\_\_ Pumpage inventory:  yes  no period: \_\_\_\_\_

Aperture cards: \_\_\_\_\_

Log data: \_\_\_\_\_

**WELL-DESCRIPTION CARD**

SAME AS ON MASTER CARD

Depth well: 350 ft Meas. rept accuracy 6

Depth cased; (first perf.): 60 ft Casing type: \_\_\_\_\_; Diam. in 4

Finish: (C) porous concrete, (F) gravel w. (perf.), (G) gravel w. (screen), (H) horiz. (perf.), (I) open end, (J) gallery, (K) perf., (L) screen, (M) sd. pt., (N) shored, (O) open hole, (P) other X

Method Drilled: (A) air rot, (B) bored, (C) cable, (D) dug, (E) hyd rot., (F) jetted, (G) air rot., (H) percussion, (I) rotary, (J) reverse, (K) trenching, (L) driven, (M) drive wash, (N) other H

Date Drilled: 953 Pump intake setting: \_\_\_\_\_ ft

Driller: H P Herndon name address

Lift (type): (A) air, (B) bucket, (C) cent, (D) jet, (E) multiple (cent.), (F) multiple (turb.), (G) none, (H) piston, (I) rot, (J) submerg, (K) turb, (L) other  Deep  Shallow 40

Power (type): (A) diesel, (B) elec, (C) gas, (D) gasoline, (E) hand, (F) gas, (G) wind, (H) H.P.  Trans. or meter no. 41

Descr. MP \_\_\_\_\_ ft above \_\_\_\_\_ ft below LSD, Alt. MP \_\_\_\_\_

Alt. LSD: \_\_\_\_\_ Accuracy: (source) \_\_\_\_\_ 47

Water Level: \_\_\_\_\_ ft above \_\_\_\_\_ ft below MP; \_\_\_\_\_ ft above \_\_\_\_\_ ft below LSD 80 Accuracy: \_\_\_\_\_ 52

Date meas: 757 Yield: \_\_\_\_\_ gpm \_\_\_\_\_ Method determined \_\_\_\_\_ 61

Drawdown: \_\_\_\_\_ ft \_\_\_\_\_ Accuracy: \_\_\_\_\_ Pumping period \_\_\_\_\_ hrs \_\_\_\_\_ 66

QUALITY OF WATER DATA: Iron \_\_\_\_\_ ppm Sulfate \_\_\_\_\_ ppm Chloride \_\_\_\_\_ ppm Hard. \_\_\_\_\_ ppm

Sp. Conduct \_\_\_\_\_ K x 10 \_\_\_\_\_ Temp. \_\_\_\_\_ °F \_\_\_\_\_ Date sampled \_\_\_\_\_ 77

Taste, color, etc. \_\_\_\_\_

Well No.

Latitude-longitude \_\_\_\_\_  
d m s N  
d m s S

**GEOLOGIC CARD**  
WELL NO. \_\_\_\_\_  
ASTER CARD

Physiographic Province: \_\_\_\_\_ Section: 03

Drainage Basin: D Subbasin: 13C

Top of well: \_\_\_\_\_  
well site: (A) (B) (C) (E) (F) (H) (K) (L) \_\_\_\_\_  
(M) (N) (P) (S) (T) (U) (V) HILL

MAJOR AQUIFER: \_\_\_\_\_ system \_\_\_\_\_ series Eutan K3 aquifer, formation, group EZ

Lithology: \_\_\_\_\_ Origin: US Aquifer Thickness: \_\_\_\_\_ ft  
Length of well open to: \_\_\_\_\_ ft Depth to top of: \_\_\_\_\_ ft

MINOR AQUIFER: \_\_\_\_\_ system \_\_\_\_\_ series \_\_\_\_\_ aquifer, formation, group \_\_\_\_\_

Lithology: \_\_\_\_\_ Origin: \_\_\_\_\_ Aquifer Thickness: \_\_\_\_\_ ft  
Length of well open to: \_\_\_\_\_ ft Depth to top of: \_\_\_\_\_ ft

Intervals Screened:

Depth to consolidated rock: \_\_\_\_\_ ft \_\_\_\_\_ Source of data: \_\_\_\_\_


Depth to basement: \_\_\_\_\_ ft \_\_\_\_\_ Source of data: \_\_\_\_\_

Surficial material: \_\_\_\_\_ Infiltration characteristics: \_\_\_\_\_

Coefficient Trans: \_\_\_\_\_ gpd/ft \_\_\_\_\_ Coefficient Storage: \_\_\_\_\_

Coefficient Perm: \_\_\_\_\_ gpd/ft<sup>2</sup>; Spec cap: \_\_\_\_\_ gpm/ft; Number of geologic cards: \_\_\_\_\_

MAP ON ORIGINAL



Well No. \_\_\_\_\_