

**WELL SCHEDULE**

U. S. DEPT. OF THE INTERIOR

GEOLOGICAL SURVEY

WATER RESOURCES DIVISION

**MASTER CARD**

**MAR 11 1973**

Record by JCM Source of data BOWC Date 9-72 Map \_\_\_\_\_

State 28 County (or town) Monroe 48

Latitude: 34° 03' 50" N Longitude: 088° 43' 00" W Sequential number: 1

Lat-long accuracy: 30 T 120 R 60 W 6 NW SW

Local well number: A065BC0612S06E Other number: \_\_\_\_\_

Local use: 021 Owner or name: \_\_\_\_\_

Owner or name: ROY KING Address: Shannon

Overship: County (C), Fed Gov't (F), City, Corp or Co (M), Private (N), State Agency (P), Water Dist (S) P

Use of water: (A) Air cond, Bottling, Comm, Dewater, Power, Fire, Dom, Irr, Med, Ind, P S, Rec, (S) Stock, Inatit, Unused, Repressure, Recharge, Desal-P S, Desal-other, Other H

Use of well: (A) Anode, Drain, Seismic, Heat Res, Obs, Oil-gas, Recharge, Test, Unused, Withdraw, Waste, Destroyed. W

DATA AVAILABLE: Well data  Freq. W/L meas.:  Field aquifer char.

Hyd. lab. data: \_\_\_\_\_

Qual. water data; type: \_\_\_\_\_

Freq. sampling:  Pumpage inventory: no. period: \_\_\_\_\_

Temperature cards: \_\_\_\_\_

Log data: D

**WELL-DESCRIPTION CARD**

SAME AS ON MASTER CARD Depth well: 340 Meas. 3

Depth cased: (first perf.) \_\_\_\_\_ ft 19 Casing type: Steel Diam. in 5

Finish: porous concrete, gravel w. concrete, (perf.), (C) gravel w. (screen), (H) horiz. gallery, (O) open end, (P) perf., (S) screen, (T) ad. pt., (W) shored, (X) open hole, (Z) other X

Method: (A) air bored, (B) cable, (C) dug, (D) hyd jetted, (H) air rot., (J) percussion, (P) rotary, (R) reverse, (T) trenching, (V) driven, (W) drive wash, (Z) other H

Date Drilled: 9-7-2 Pump intake setting: \_\_\_\_\_ ft \_\_\_\_\_

Driller: Homan name \_\_\_\_\_ address \_\_\_\_\_

Lift (type): (A) air, (B) bucket, (C) cent., (J) jet, (L) multiple, (M) multiple, (N) none, (P) piston, (R) rot., (S) submerg, (T) turb., (Z) other  Deep  Shallow 40

Power (type): diesel, elc, gas, gasoline, hand, gas, wind, H.P. 3/4 5 Trans. or meter no. \_\_\_\_\_

Descrip. MP \_\_\_\_\_ ft above \_\_\_\_\_ ft below LSD, Alt. MP \_\_\_\_\_

Alt. LSD: \_\_\_\_\_ Accuracy: (source) \_\_\_\_\_

Water Level: \_\_\_\_\_ ft above \_\_\_\_\_ ft below MP; \_\_\_\_\_ ft below LSD 80 Accuracy: \_\_\_\_\_

Date meas: 9-7-2 Yield: \_\_\_\_\_ gpm 5 Method determined \_\_\_\_\_

Drawdown: \_\_\_\_\_ ft \_\_\_\_\_ Accuracy: \_\_\_\_\_ Pumping period \_\_\_\_\_ hrs \_\_\_\_\_

QUALITY OF WATER DATA: Iron \_\_\_\_\_ ppm Sulfate \_\_\_\_\_ ppm Chloride \_\_\_\_\_ ppm Hard. \_\_\_\_\_ ppm

Sp. Conduct \_\_\_\_\_ K x 10 6 Temp. \_\_\_\_\_ °F \_\_\_\_\_ Date sampled \_\_\_\_\_

Taste, color, etc. \_\_\_\_\_

Well No.

A65

PUNCHED

Well No. \_\_\_\_\_

Latitude-longitude \_\_\_\_\_  
d m s d m s

HYDROGEOLOGIC CARD

ETC: 11 2044

SAME AS ON MASTER CARD

Physiographic Province: \_\_\_\_\_

03 Section: \_\_\_\_\_

D Drainage Basin: \_\_\_\_\_

13C Subbasin: \_\_\_\_\_

Topo of well site: (D) depression, (C) stream channel, (B) dunes, (P) flat, (R) hilltop, (K) sink, (L) swamp, (S) offshore, (T) pediment, (U) hillside, (V) terrace, undulating, valley flat

MAJOR AQUIFER: \_\_\_\_\_

K3

EZ

Lithology: \_\_\_\_\_

S

Origin: \_\_\_\_\_

6

Thickness: 140 ft

Length of well open to: \_\_\_\_\_ ft

140

Depth to top of: \_\_\_\_\_ ft

200

MINOR AQUIFER: \_\_\_\_\_

Lithology: \_\_\_\_\_

\_\_\_\_\_

Origin: \_\_\_\_\_

\_\_\_\_\_

Thickness: \_\_\_\_\_ ft

Length of well open to: \_\_\_\_\_ ft

\_\_\_\_\_

Depth to top of: \_\_\_\_\_ ft

\_\_\_\_\_

Intervals Screened: None

Depth to consolidated rock: \_\_\_\_\_ ft

\_\_\_\_\_

Source of data: \_\_\_\_\_

Depth to basement: \_\_\_\_\_ ft

\_\_\_\_\_

Source of data: \_\_\_\_\_

Surficial material: \_\_\_\_\_

\_\_\_\_\_


Infiltration characteristics: \_\_\_\_\_

Coefficient Trans: \_\_\_\_\_ gpd/ft

\_\_\_\_\_

Coefficient Storage: \_\_\_\_\_

Coefficient Perm: \_\_\_\_\_ gpd/ft<sup>2</sup>; Spec cap: \_\_\_\_\_ gpm/ft; Number of geologic cards: \_\_\_\_\_



Well No.

A65