

WELL SCHEDULE  
GEOLOGICAL SURVEY

**PUNCHED**

U. S. DEPT. OF THE INTERIOR

WATER RESOURCES DIVISION

MASTER CARD

Record by JCM Source of data BOWC Date 7-72 Map MAR'11 1973

State 28 County (or town) Monroe 48

Latitude: 33<sup>deg</sup> 53<sup>min</sup> 00<sup>sec</sup> N Longitude: 08<sup>deg</sup> 83<sup>min</sup> 90<sup>sec</sup> 0 Sequential number: 1

Lat-long accuracy: 2<sup>deg</sup> 14<sup>min</sup> 6<sup>sec</sup> S 3<sup>deg</sup> SE SE SE

Local well number: K053D.D0314506E Other number: B & M

Local use: 021 Owner or name: MICLAISTEN Address: Aberdeen

Ownership: County, Fed Gov't, City, Corp or Co, Private, State Agency, Water Dist P

Use of water: (A) Air cond, Bottling, Comm, Dewater, Power, Fire, Dom, Irr, Med, Ind, P S, Rec, (S) Stock, Instit, Unused, Repressure, Recharge, Desal-P S, Desal-other, Other H

Use of well: (A) Anode, Drain, Seismic, Heat Res, Obs, Oil-gas, Recharge, Test, Unused, Withdraw, Waste, Destroyed, (W) W

DATA AVAILABLE: Well data  Freq. W/L meas:  Field aquifer char.

Hyd. lab. data:

Qual. water data; type:

Freq. sampling:  Pumpage inventory:  yes no, period:

Aperture cards:  yes

Log data: D

WELL-DESCRIPTION CARD

SAME AS ON MASTER CARD Depth well: 300 ft Meas. rept accuracy 3

Depth cased; (first perf.): 30 ft Casing type: steel; Diam. in 5

Finish: porous concrete, gravel w. (perf.), (screen), gravel w. horiz. open perf., screen, sd. pt., shored, open hole, other X

Method Drilled: (A) air bored, (C) cable, (D) dug, (H) hyd jetted, (J) air reverse, (P) percussion, (R) rotary, (T) trenching, (V) driven, (W) drive wash, other H

Date Drilled: 9-7-72 Pump intake setting: 5 ft

Driller: \_\_\_\_\_

Lift (type): (A) air, (B) bucket, (C) cent, (J) jet, (L) multiple, (M) multiple, (N) none, (P) piston, (R) rot, (S) submerg, (T) turb, other S Deep  Shallow

Power (type): diesel, X nat, gas, gasoline, hand, gas, wind; H.P. LP 1/2 Trans. or meter no. 5

Descrip. MP \_\_\_\_\_ ft above LSD, Alt. MP \_\_\_\_\_

Alt. LSD: \_\_\_\_\_ Accuracy: (source) \_\_\_\_\_

Water Level: \_\_\_\_\_ ft above MP; below LSD 97 Accuracy: \_\_\_\_\_

Date meas: 6-7-72 Yield: \_\_\_\_\_ gpm Method determined \_\_\_\_\_

Drawdown: \_\_\_\_\_ ft Accuracy: \_\_\_\_\_ Pumping period \_\_\_\_\_ hrs

QUALITY OF WATER DATA: Iron \_\_\_\_\_ ppm Sulfate \_\_\_\_\_ ppm Chloride \_\_\_\_\_ ppm Hard. \_\_\_\_\_ ppm

Sp. Conduct \_\_\_\_\_ K x 10<sup>6</sup> Temp. \_\_\_\_\_ °F Date sampled \_\_\_\_\_

Taste, color, etc. \_\_\_\_\_

Well No.

K53

Well No. \_\_\_\_\_

Latitude-longitude \_\_\_\_\_  
d m s d m s

HYDROGEOLOGIC CARD

SAME AS 0170019 Physiographic Province: \_\_\_\_\_ Section: 03

Drainage Basin: D Subbasin: 134

Top of well site: (D) CEB (C) L (E) (P) (H) (K) (L)  
(Q) (P) (S) (T) (U) (V)  
offshore, pediment, hillside, terrace, undulating, valley flat

MAJOR AQUIFER: system \_\_\_\_\_ series K3 aquifer, formation, group EZ

Lithology: \_\_\_\_\_ Origin: S Aquifer Thickness: 140 ft  
Length of well open to: \_\_\_\_\_ ft 140 Depth to top of: \_\_\_\_\_ ft 160

MINOR AQUIFER: system \_\_\_\_\_ series \_\_\_\_\_ aquifer, formation, group \_\_\_\_\_

Lithology: \_\_\_\_\_ Origin: \_\_\_\_\_ Aquifer Thickness: \_\_\_\_\_ ft  
Length of well open to: \_\_\_\_\_ ft \_\_\_\_\_ Depth to top of: \_\_\_\_\_ ft \_\_\_\_\_

Intervals Screened: NONE


Depth to consolidated rock: \_\_\_\_\_ ft \_\_\_\_\_ Source of data: \_\_\_\_\_

Depth to basement: \_\_\_\_\_ ft \_\_\_\_\_ Source of data: \_\_\_\_\_

Surficial material: \_\_\_\_\_ Infiltration characteristics: \_\_\_\_\_

Coefficient Trans: \_\_\_\_\_ gpd/ft \_\_\_\_\_ Coefficient Storage: \_\_\_\_\_

Coefficient Perm: \_\_\_\_\_ gpd/ft<sup>2</sup>; Spec cap: \_\_\_\_\_ gpm/ft; Number of geologic cards: \_\_\_\_\_



Well No.

K53