

9-185  
(October 1950)

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY  
WATER RESOURCES DIVISION

WELL SCHEDULE

Date 4-24, 1964 Field No. \_\_\_\_\_  
Record by P.E. Grantham + B.E. Wasson Office No. 428  
Source of data Dr. + Obser.

1. Location: State Miss County Monroe

Map NW 1/4 W W 1/4 sec. 35 T. 14 N. R. 7 E W

2. Owner: City of Aberdeen Address \_\_\_\_\_

Test Hole #2 Address \_\_\_\_\_

Driller Carlross Well Supply Address \_\_\_\_\_

3. Topography \_\_\_\_\_

4. Elevation \_\_\_\_\_ ft. above \_\_\_\_\_  
below \_\_\_\_\_

5. Type: Dug drilled, driven, bored, jetted 1964

6. Depth: Rept. \_\_\_\_\_ ft. Meas. \_\_\_\_\_ ft.

7. Casing: Diam. \_\_\_\_\_ in., to \_\_\_\_\_ in., Type \_\_\_\_\_

Depth \_\_\_\_\_ ft., Finish \_\_\_\_\_

8. Chief Aquifer \_\_\_\_\_ From \_\_\_\_\_ ft. to \_\_\_\_\_ ft.

Others \_\_\_\_\_

9. Water level \_\_\_\_\_ ft. rept. \_\_\_\_\_ 19 \_\_\_\_\_ above  
meas. \_\_\_\_\_ below

\_\_\_\_\_ which is \_\_\_\_\_ ft. above  
below surface

10. Pump: Type \_\_\_\_\_ Capacity \_\_\_\_\_ G. M.

Power: Kind \_\_\_\_\_ Horsepower \_\_\_\_\_

11. Yield: Flow \_\_\_\_\_ G. M., Pump \_\_\_\_\_ G. M., Meas., Rept. Est. \_\_\_\_\_

Drawdown \_\_\_\_\_ ft. after \_\_\_\_\_ hours pumping \_\_\_\_\_ G. M.

12. Use: Dom., Stock, PS., RR., Ind., Irr., Obs. \_\_\_\_\_


Adequacy, permanence \_\_\_\_\_

13. Quality \_\_\_\_\_ Temp \_\_\_\_\_ °F.

Taste, odor, color \_\_\_\_\_ Sample Yes  
No

Unfit for \_\_\_\_\_

14. Remarks: (Log, Analyses, etc.) Test hole drilled too



UNITED STATES  
 DEPARTMENT OF THE INTERIOR  
 GEOLOGICAL SURVEY  
 WATER RESOURCES DIVISION

(Revised 1962)

WELL LOG SHEET

Well No. \_\_\_\_\_  
 Section \_\_\_\_\_  
 Township \_\_\_\_\_  
 Range \_\_\_\_\_

- 0-10 white clay
- 10-13 yellow clay
- 18-30 Soap stone (hard)
- 30-40 Sand
- 40-46 Hard shale then rock
- 46-60 " " " "
- 60-68 Sand Loose
- 68-90 Sand sh Strk
- 90-112 Hard cement sand shale (No Good)
- 112-115 Clay Hard
- 115-134 Sand thin streaks Sh
- 134-139 Sand
- 139-157 Rock
- 157-180 Sdy Sh
- 180-195 " "
- 195-203 Sand
- 203-227 Sh Strk Sd

