

### WELL SCHEDULE

U. S. DEPT. OF THE INTERIOR

GEOLOGICAL SURVEY

WATER RESOURCES DIVISION

#### MASTER CARD

Record by B Source of data Auc Date 6.68 Map \_\_\_\_\_

State 28 County Seah (or town) 62

Latitude: 322700N Longitude: 0894300 Sequential number: 2

Lat-long accuracy: 6 T. 7 R. 6 Sec. 18

Local well number: E026 Other number: \_\_\_\_\_ B & M

Local use: 026 Owner or name: \_\_\_\_\_

Owner or name: L MINTON Address: \_\_\_\_\_

Ownership: County, Fed Gov't, City, Corp or Co, Private, State Agency, Water Dist P

Use of water: (A) Air cond, Bottling, Comm, Dewater, Power, Fire, Dom, Irr, Med, Ind, P S, Rec, (S) Stock, Inatit, Unused, Repressure, Recharge, Desal-P S, Desal-other, Other H

Use of well: (A) Anode; Drain, Seismic, Heat Res, Obs, Oil-gas, Recharge, Test, Unused, Withdraw, Waste, Destroyed (X) \_\_\_\_\_ W

DATA AVAILABLE: Well data  Freq. W/L meas.:  Field aquifer char.

Hyd. lab. data: \_\_\_\_\_

Qual. water data; type: \_\_\_\_\_

Freq. sampling: \_\_\_\_\_ Pumpage inventory: yes  no  period: \_\_\_\_\_

Aperture cards: \_\_\_\_\_ yes

Log data: D

#### WELL-DESCRIPTION CARD

SAME AS ON MASTER CARD Depth well: 330 ft Meas. accuracy 3

Depth cased; (first perf.) 315 ft Casing type: \_\_\_\_\_; Diám. in 2

Finish: porous concrete, gravel w. (perf.), (screen), gravel w. (screen), horiz. open end, gallery, open perf., screen, sd. pt., shored, hole, other S

Method: (A) air bored, cable, dug, hyd rot., (H) jetted, (J) air percussion, (P) reverse trenching, (R) driven, (T) drive wash, (V) other H

Date Drilled: 964 Pump intake setting: \_\_\_\_\_ ft

Driller: \_\_\_\_\_

Lift (type): (A) air, bucket, cent, jet, (B) multiple, (C) multiple, (cent.), (L) none, (M) piston, (N) rot, (P) submerg, (R) turb, (S) other, (T) Deep  Shallow

Power (type): nat diesel, elec, gas, gasoline, hand, gas, wind; LP  Trans. or meter no. \_\_\_\_\_

Descrip. MP \_\_\_\_\_ above ft below LSD. Alt. MP \_\_\_\_\_

Alt. LSD: \_\_\_\_\_ Accuracy: (source) \_\_\_\_\_

Water Level: \_\_\_\_\_ ft above MP; \_\_\_\_\_ ft below LSD 65 Accuracy: \_\_\_\_\_

Date meas: 964 Yield: \_\_\_\_\_ gpm Method determined \_\_\_\_\_

Drawdown: \_\_\_\_\_ ft Accuracy: \_\_\_\_\_ Pumping period \_\_\_\_\_ hrs

QUALITY OF WATER DATA: Iron \_\_\_\_\_ ppm Sulfate \_\_\_\_\_ ppm Chloride \_\_\_\_\_ ppm Hard. \_\_\_\_\_ ppm

Sp. Conduct \_\_\_\_\_ K x 10<sup>6</sup> Temp. \_\_\_\_\_ °F Date sampled \_\_\_\_\_

Taste, color, etc. \_\_\_\_\_

ROLLA COMPUTATION BRANCH

Well No.

E26

Latitude-longitude \_\_\_\_\_  
N  
S  
d m s d m s

HYDROGEOLOGIC CARD

SAME AS ON MASTER CARD 03 Section: \_\_\_\_\_  
19 20 21

D Drainage Basin: 137 Subbasin: \_\_\_\_\_  
22 23 25 26

(D) (C) (E) (F) (H) (K) (L)  
Top of well site: depression, stream channel, dunes, flat, hilltop, sink, swamp,  
(Ø) (P) (S) (T) (U) (V)  
offshore, pediment, hillside, terrace, undulating, valley flat \_\_\_\_\_ 27

MAJOR AQUIFER: \_\_\_\_\_ system, \_\_\_\_\_ series TE aquifer, formation, group CØ  
28 29 30 31

Lithology: \_\_\_\_\_ US Origin: \_\_\_\_\_ 2 Aquifer Thickness: \_\_\_\_\_ ft  
32 33 34

Length of well open to: \_\_\_\_\_ ft 15 Depth to top of: \_\_\_\_\_ ft 222  
35 37 38 40 41 43

MINOR AQUIFER: \_\_\_\_\_ system, \_\_\_\_\_ series \_\_\_\_\_ aquifer, formation, group \_\_\_\_\_  
44 45 46 47

Lithology: \_\_\_\_\_ Origin: \_\_\_\_\_ Aquifer Thickness: \_\_\_\_\_ ft  
48 49 50

Length of well open to: \_\_\_\_\_ ft \_\_\_\_\_ Depth to top of: \_\_\_\_\_ ft \_\_\_\_\_  
51 53 54 56 57 59

Intervals Screened: \_\_\_\_\_


Depth to consolidated rock: \_\_\_\_\_ ft \_\_\_\_\_ Source of data: \_\_\_\_\_ 64

Depth to basement: \_\_\_\_\_ ft \_\_\_\_\_ Source of data: \_\_\_\_\_ 69

Surficial material: \_\_\_\_\_ Infiltration characteristics: \_\_\_\_\_ 72

Coefficient Trans: \_\_\_\_\_ gpd/ft \_\_\_\_\_ Coefficient Storage: \_\_\_\_\_ 76 78

Coefficient Perm: \_\_\_\_\_ gpd/ft<sup>2</sup>; Spec cap: \_\_\_\_\_ gpm/ft; Number of geologic cards: \_\_\_\_\_ 79



Well No.

**E26**