

# WELL SCHEDULE

U. S. DEPT. OF THE INTERIOR

GEOLOGICAL SURVEY

WATER RESOURCES DIVISION

## MASTER CARD

Record by BEWASSON Source of data Plant Supt. Date 5-18-60 Map \_\_\_\_\_

State Mississippi 28 County Washington 76  
(or town)

Latitude: 33 22 15 N Longitude: 09 10 01 8 Sequential number: 2  
deg min sec N S 12 degrees 15 min sec 18

Lat-long accuracy: 2 T. 18 S. R. 8 E. Sec 28, 3 Sw 3 Sw 26 (SW, SW, 26)  
Local well number: D060CC2818008W Other number: #2 North  
Local use: 064 Owner or name: MICH. & WIS. CP Address: Greenville, miss.  
Ownership: County, Fed Gov't, City, Corp or Co, Private, State Agency, Water Dist N  
Use of water: (A) Air cond, Bottling, Comm, Dewater, Power, Fire, Dom, Irr, Med, Ind, P S, Rec, (N) (P) (R)  
(S) (T) (U) (V) (W) (X) (Y) (Z) Stock, Instit, Unused, Repressure, Recharge, Desal-P S, Desal-other, Other N  
Use of well: (A) (D) (G) (H) (I) (J) (K) (L) (M) (N) (O) (P) (R) (T) (U) (V) (W) (X) (Z) W  
Anode, Drain, Seismic, Heat Res, Obs, Oil-gas, Recharge, Test, Unused, Withdraw, Waste, Destroyed.

DATA AVAILABLE: Well data  Freq. W/L meas.: Irregular I Field aquifer char.

Hyd. lab. data: \_\_\_\_\_

Qual. water data; type: Layne Lab.

Freq. sampling: \_\_\_\_\_ Pumpage inventory:  yes, no, period: \_\_\_\_\_

Aperture cards: \_\_\_\_\_

Log data: Driller's log to 501 ft

## WELL-DESCRIPTION CARD

SAME AS ON MASTER CARD Depth well: 492 ft Meas. 492 accuracy 3  
Depth cased: 452 ft Casing Type: \_\_\_\_\_; Diam. 10, 6 in 10

Finish: (C) porous concrete, (F) gravel w. (perf.), (G) gravel w. (screen), (H) horiz. gallery, (I) open end, (P) perf., (S) screen, (W) sd. pt., (X) shored, (Z) open hole, other S

Method Drilled: (A) air rot, (B) bored, (C) cable, (D) dug, (H) hyd rot, (J) jetted, (P) air percussion, (R) reverse, (T) trenching, (V) driven, (W) drive wash, other H

Date Drilled: 1956 956 Pump intake setting: \_\_\_\_\_ ft \_\_\_\_\_

Driller: Layne Central MEMPHIS, TENN. address \_\_\_\_\_

Lift (type): (A) air, (B) bucket, (C) cent, (J) jet, (L) multiple, (M) multiple, (N) none, (P) piston, (R) rot, (S) submerg, (T) turb, (Z) other T Deep  Shallow

Power (type): diesel, elec, gas, gasoline, hand, gas, wind; H.P. 7 1/2 4 Trans. or meter no. \_\_\_\_\_

Descrip. MP Air vent, which is 2.0 ft above 100, Alt. MP \_\_\_\_\_

Alt. LSD: 117 Accuracy: topo 3

Water Level 47.55 ft above MP; Ft below LSD 4.6 Accuracy: meas. A

Date meas: 1-25-68 168 Yield: 100 gpm 1000 Method P determined 1

Drawdown: \_\_\_\_\_ ft Accuracy: \_\_\_\_\_ Pumping period \_\_\_\_\_ hrs \_\_\_\_\_

QUALITY OF WATER DATA: Iron \_\_\_\_\_ Sulfate \_\_\_\_\_ Chloride \_\_\_\_\_ Hard. \_\_\_\_\_

Sp. Conduct 540 K x 10<sup>6</sup> 4 Temp. 67 °F 67 Date sampled 168

Taste, color, etc. \_\_\_\_\_

Well No. D60

Latitude-longitude N  
S

**HYDROGEOLOGIC CARD**

NAME AS ON MASTER CARD Physiographic Province: Coastal Plain 03 Section: Miss River

all Plain E Drainage Basin: 115 I Subbasin:         

of site: (D) depression, stream channel, dunes, flat, hilltop, sink, swamp, (E) offshore, pediment, hillside, terrace, undulating, valley flat (V)          Y

OR Tertiary Eocene TE Cockfield C Φ

ology: Unconsolidated Sand US Origin: Deltaic          Aquifer Thickness:          ft

Length of well open to: 40 ft 40 Depth to top of:          ft         

OR                                                      

ology:                   Origin:                   Aquifer Thickness:          ft

Length of well open to:          ft          Depth to top of:          ft         

ervals 452' - 492' ; 40' ss

h to          ft          Source of data:         

h to          ft          Source of data:         


icial                   Infiltration characteristics:         

icient                   Coefficient Storage:         

icient                                                      

See location on sched. D59)

∅ 37.59' - 5-18-60 (GL)  
 see about 2300 gpd - 875,000 gpy 1958  
 - water softener



441 ft of 10-in  
 56 6

Well No. D60

*Handwritten notes at the bottom of the page, including 'D 11' and other illegible characters.*

