

PUNCHED and VERIFIED  
ROLLA COMPUTATION BRANCH

WRD Exp. (GW)  
April 1966

Well No. E 44

WELL SCHEDULE

U. S. DEPT. OF THE INTERIOR

GEOLOGICAL SURVEY

WATER RESOURCES DIVISION

MASTER CARD

Record by W.T. Oakley Source of data Walker Farms Date 10-31-67 Map \_\_\_\_\_

State Mississippi County Washington Sequential number: 76  
28

Latitude: 33 deg 25 min 22 sec N Longitude: 090 degrees 55 min 06 sec W  
12 degrees 13 min sec 18

Lat-long accuracy: 2 T. 8 S. R. 7 E Sec 10, NW SW SE NE

Local well number: E 0 4 4 B C 1 0 1 8 N 0 7 W Other number: \_\_\_\_\_ B & M

Local use: 064 Owner or name: G.B. Walker

Owner or name: G. B. WALKER Address: Stoneville, Miss.

Ownership: County, Fed Gov't, City, Corp or Co. (P) Private State Agency, Water Dist \_\_\_\_\_ 67 P

Use of water: (A) Air cond, Bottling, Comm, Dewater, Power, Fire, Dom, Irr, Med, Ind, P S, Rec, \_\_\_\_\_ 68 P  
(S) Stock, Instic, Unused, Reppure, Recharge, Desal-P S, Desal-other, Other \_\_\_\_\_

Use of well: (A) Anode, Drain, Seismic, Heat Res, Obs, Oil-gas, Recharge, Test, Unused, (W) Withdraw, Waste, Destroyed \_\_\_\_\_ 69 W  
(D) (G) (H) (φ) (P) (R) (T) (U) (X) (Z)

DATA AVAILABLE: Well data \_\_\_\_\_ 70 Freq. W/L meas.: \_\_\_\_\_ 71 N Field aquifer char. \_\_\_\_\_ 72

Hyd. lab. data: \_\_\_\_\_ 73

Qual. water data; type: \_\_\_\_\_ 74

Freq. sampling: \_\_\_\_\_ 75 Pumpage inventory: \_\_\_\_\_ 76  
yes no; period: \_\_\_\_\_

Aperture cards: \_\_\_\_\_ 77 yes

Log data: \_\_\_\_\_ 78 79

WELL-DESCRIPTION CARD

SAME AS ON MASTER CARD Depth well: 600+ ft 460 Meas. rept 24 6  
30 ft 430 Casing type: \_\_\_\_\_ 25 28; Diam: 4 in 6 29 30

Depth cased; (first perf.): \_\_\_\_\_ ft \_\_\_\_\_ 25 28

Finish: porous gravel w. gravel w. horiz. open perf., screen, sd. pt., shored, open hole, other \_\_\_\_\_ 31 S  
(C) (F) (G) (H) (φ) (P) (S) (T) (W) (X) (Z)

Method: (A) air bored, cable, dug, hyd, jetted, air reverse trenching, driven, drive rot, percussion, rotary, \_\_\_\_\_ 32 H  
(B) (C) (D) (H) (J) (P) (R) (T) (V) (W) (Z)

Date Drilled: 1966 9/6/6 Pump intake setting: \_\_\_\_\_ ft \_\_\_\_\_ 33 35 36 38

Driller: Layne Central, Cleveland, Miss.

Lift (type): (A) air, bucket, cent, jet, multiple, multiple, none, piston, rot, submerg, turb, other \_\_\_\_\_ 39 T Deep \_\_\_\_\_ 40  
(B) (C) (J) (L) (M) (N) (P) (R) (S) (T) (Z)

Power (type): diesel, (elec) gas, gasoline, hand, gas, wind; H.P. 10 \_\_\_\_\_ 41 4 Trans. or meter no. \_\_\_\_\_

Descrip. MP \_\_\_\_\_ ft above \_\_\_\_\_ below LSD. Alt. MP \_\_\_\_\_

Alt. LSD: 125 \_\_\_\_\_ 125 Accuracy: \_\_\_\_\_ 47 3  
(source)

Water Level \_\_\_\_\_ ft above \_\_\_\_\_ below MP; Ft below LSD \_\_\_\_\_ Accuracy: \_\_\_\_\_ 52

Date meas: \_\_\_\_\_ 53 Yield: \_\_\_\_\_ gpm \_\_\_\_\_ 54 130 Method determined \_\_\_\_\_ 61

Drawdown: \_\_\_\_\_ ft \_\_\_\_\_ Accuracy: \_\_\_\_\_ 55 \_\_\_\_\_ 56 Pumping period \_\_\_\_\_ 60 hrs \_\_\_\_\_ 68

QUALITY OF WATER DATA: Iron \_\_\_\_\_ ppm \_\_\_\_\_ 69 Sulfate \_\_\_\_\_ ppm \_\_\_\_\_ 70 Chloride \_\_\_\_\_ ppm \_\_\_\_\_ 71 Hard. \_\_\_\_\_ 72

Sp. Conduct \_\_\_\_\_ K x 10<sup>6</sup> \_\_\_\_\_ 73 Temp. \_\_\_\_\_ °F \_\_\_\_\_ 74 \_\_\_\_\_ 76 Date sampled \_\_\_\_\_ 77 \_\_\_\_\_ 79

Taste, color, etc. \_\_\_\_\_

Well No. E 44

