

PUNCHED

WELL SCHEDULE

U. S. DEPT. OF THE INTERIOR

GEOLOGICAL SURVEY

WATER RESOURCES DIVISION

MASTER CARD

Record by JCM Source of data BOWC Date 1-72 Map

State 28 County (or town) Washington 7.6

Latitude: 33<sup>deg</sup> 19<sup>min</sup> 40<sup>sec</sup> N Longitude: 09<sup>deg</sup> 10<sup>min</sup> 26<sup>sec</sup> W Sequential number: 1

Lat-long accuracy: 3<sup>min</sup> 17<sup>sec</sup> S, R 90<sup>sec</sup> E, 3<sup>min</sup> SW, SW

Local well number: G133CC0317NO9W Other number: B & M

Local use: 190 Owner or name: Guille Post Comm.

Owner or name: J. J. FERGUSON Address: Greenville

Ownership: County, Fed Gov't, City, Corp or Co, Private, State Agency, Water Dist M

Use of Air cond, Bottling, Comm, Dewater, Power, Fire, Dom, Irr, Med, Ind, P S, Rec, water: (S) (T) (U) (V) (W) (X) (Y) (Z)

Stock, Instrt, Unused, Reppure, Recharge, Desal-P S, Desal-other, Other NH

Use of well: Anode, Drain, Seismic, Heat Res, Obs, Oil-gas, Recharge, Test, Unused, Withdraw, Waste, Destroyed. W

DATA AVAILABLE: Well data  Freq. W/L meas.:  Field aquifer char.

Hyd. lab. data:

Qual. water data; type:

Freq. sampling:  Pumpage inventory: no, period:

Aperture cards:

Log data: D

WELL-DESCRIPTION CARD

SAME AS ON MASTER CARD Depth well: 440 ft Meas. 3

Depth cased: 400 ft Casing type: Blk Iron; Diam. 4X3 in 4

Finish: porous concrete, gravel w. screen, gravel w. gallery, horiz. open perf., screen, sd. pt., shored, open hole, other 3

Method Drilled: air bored, cable, dug, hyd jetted, air reverse, air reverse trenching, driven, drive rot., rot., percussion, rotary, wash, other H

Date Drilled: 9-7-71 Pump intake setting: 30 ft

Driller: Dyer name address

Lift (type): air, bucket, cent, jet, multiple, multiple, none, piston, rot, submerg, turb, other  Deep  Shallow 40

Power (type): diesel, X gas, gasoline, hand, gas, wind; H.P. 5  Trans. or meter no. 41

Descrip. MP 5 ft above below LSD, Alt. MP

Alt. LSD: 125 Accuracy: (source) 47

Water Level: 45 ft above below MP; Ft below LSD Accuracy: 52 D

Date meas: 10-7-71 Yield: 100 gpm Method determined 61

Drawdown: 62 ft Accuracy: 65 Pumping period 66 hrs 68

QUALITY OF WATER DATA: Iron 69 ppm Sulfate 70 ppm Chloride 71 ppm Hard. 72 ppm

Sp. Conduct 6 K x 10 Temp. °F Date sampled

Well No. G133

Latitude-longitude \_\_\_\_\_  
d m s d m s

**HYDROGEOLOGIC CARD**

NAME AS ON MASTER CARD \_\_\_\_\_ Physiographic Province: \_\_\_\_\_  
20 21 Section: **03**  
22 Drainage Basin: **E** 23 25 Subbasin: **151** 26

(D) depression, stream channel, dunes, flat, hilltop, sink, swamp,  
site: (A) offshore, pediment, hillside, terrace, undulating, valley flat 27

Hydrogeologic system series **TE** aquifer, formation, group **C6**

Geology: **US** Origin: **2** Aquifer Thickness: **80** ft  
Length of well open to: \_\_\_\_\_ ft **40** Depth to top of: \_\_\_\_\_ ft **360**

Hydrogeologic system series \_\_\_\_\_ aquifer, formation, group \_\_\_\_\_  
Geology: \_\_\_\_\_ Origin: \_\_\_\_\_ Aquifer Thickness: \_\_\_\_\_ ft

Length of well open to: \_\_\_\_\_ ft \_\_\_\_\_ Depth to top of: \_\_\_\_\_ ft \_\_\_\_\_

Materials used: **3" S.S.**


Depth to consolidated rock: \_\_\_\_\_ ft \_\_\_\_\_ Source of data: \_\_\_\_\_

Depth to cement: \_\_\_\_\_ ft \_\_\_\_\_ Source of data: \_\_\_\_\_

Hydrogeologic characteristics: \_\_\_\_\_ Infiltration characteristics: \_\_\_\_\_

Efficient storage: \_\_\_\_\_ gpd/ft \_\_\_\_\_ Coefficient Storage: \_\_\_\_\_

Efficient storage: \_\_\_\_\_ gpd/ft<sup>2</sup>; Spec cap: \_\_\_\_\_ gpm/ft; Number of geologic cards: \_\_\_\_\_



Well No. \_\_\_\_\_

**9133**