

WELL SCHEDULE

Log # 262

U. S. DEPT. OF THE INTERIOR GEOLOGICAL SURVEY WATER RESOURCES DIVISION

PUNCHED

MASTER CARD J.M

BOWC

Record by WTO Source of data Obs driller Date 6/16/71 Map WAYNESBORO

State 28 County (or town) WAYNE 77

Latitude: 314339N Longitude: 0883844 Sequential number: 1

Lat-long accuracy: 20 T. 90 S, R. 70 Sec 24 NE, NE, SW

Local well number: H134AC2409NO7W Other number: B & M

Local use: 055262 Owner or name: Mid South Paving Co.

Owner or name: MID STATE CO Address: WAYNEBORO, MISS

Ownership: County, Fed Gov't, City, Corp or Co, Private, State Agency, Water Dist N

Use of Air cond, Bottling, Comm, Dewater, Power, Fire, Dom, Irr, Med, Ind, P S, Rec, water: N

Use of (A) (D) (G) (H) (I) (P) (R) (T) (U) (W) (X) (Z) W

well: Anode, Drain, Seismic, Heat Res, Obs, Oil-gas, Recharge, Test, Unused, Withdraw, Waste, Destroyed.

DATA AVAILABLE: Well data  Freq. W/L meas.:  Field aquifer char.

Hyd. lab. data:

Qual. water data; type:

Freq. sampling:  Pumpage inventory: yes  no, period:

Aperture cards:

Log data: 54' - 1050 D/E

WELL-DESCRIPTION CARD

SAME AS ON MASTER CARD Depth well: 450 ft Meas. rept accuracy 3

Depth cased: 430 ft Casing type: BLK Diam. in 4

Finish: porous concrete, gravel w. (perf.), gravel w. (screen), horiz. gallery, open perf., screen, sd. pt., shored, open hole, other S

(A) (B) (C) (D) (H) (J) (P) (R) (T) (V) (W) (Z) H

air bored, cable, dug, hyd jetted, air percussion, rotary, reverse trenching, driven, drive wash, other

671 971 Pump intake setting: 36 ft 38

RY DRUG CO. name address MERIDIAN

(J) multiple, multiple, none, piston, rot, submerg, turb, other S Deep  Shallow

LP 1 1/2 Trans. or meter no. T

ft above below LSD, Alt. MP 750 Accuracy: (source) topo 4

86 Accuracy: 32 Method determined 0

gpm 32 Pumping period hrs 0

ppm 71 Hard. ppm 72

Date sampled 77 79

Well No.

H-134

UNCLASIFIED

Well No. \_\_\_\_\_  
Latitude-longitude \_\_\_\_\_ N S \_\_\_\_\_ m d \_\_\_\_\_

HYDROGEOLOGIC CARD

SAVE AS ON MASTER CARD  
Physiographic Province: \_\_\_\_\_  
Drainage Basin: D \_\_\_\_\_  
Subbasin: 13P \_\_\_\_\_  
Section: 03 \_\_\_\_\_

Top of depression, stream channel, dunes, flat, hilltop, sink, swamp, well site: \_\_\_\_\_  
(D) (C) (E) (F) (H) (K) (L) (N) (P) (S) (T) (U) (V) \_\_\_\_\_  
offshore, pediment, hillside, terrace, undulating, valley flat \_\_\_\_\_

MAJOR AQUIFER: TE \_\_\_\_\_ series \_\_\_\_\_  
aquifer formation, group \_\_\_\_\_  
Lithology: S \_\_\_\_\_ Origin: 2 \_\_\_\_\_  
aquifer thickness: \_\_\_\_\_  
Length of well open to: \_\_\_\_\_ ft \_\_\_\_\_  
Depth to top of: 42.5 \_\_\_\_\_ ft \_\_\_\_\_

MINOR AQUIFER: \_\_\_\_\_ series \_\_\_\_\_  
aquifer formation, group \_\_\_\_\_  
Lithology: \_\_\_\_\_ Origin: \_\_\_\_\_  
aquifer thickness: \_\_\_\_\_  
Length of well open to: \_\_\_\_\_ ft \_\_\_\_\_  
Depth to top of: \_\_\_\_\_ ft \_\_\_\_\_

Intervals Screened: \_\_\_\_\_  
2" S.S.

Depth to consolidated rock: \_\_\_\_\_ ft \_\_\_\_\_  
Source of data: \_\_\_\_\_  
Depth to basement: \_\_\_\_\_ ft \_\_\_\_\_  
Source of data: \_\_\_\_\_  
Surficial material: \_\_\_\_\_  
infiltration \_\_\_\_\_

Coefficient Trans: \_\_\_\_\_ gpd/ft.  
Coefficient Perm: \_\_\_\_\_ gpd/ft.  
Spec \_\_\_\_\_

Method Drilled: \_\_\_\_\_  
Date Drilled: \_\_\_\_\_  
Driller: TERA  
Lift (type): (A) (B) (C) \_\_\_\_\_  
air, bucket, cent.  
Power (type): diesel, elec, nat gas, gasoline.  
Descrip. MP \_\_\_\_\_  
Alt. LSD: \_\_\_\_\_  
Water Level \_\_\_\_\_  
Date meas: \_\_\_\_\_ ft above \_\_\_\_\_  
below MP; Ft above LSD  
below LSD  
Drawdown: \_\_\_\_\_ ft \_\_\_\_\_  
Yield: \_\_\_\_\_  
QUALITY OF WATER DATA: Iron \_\_\_\_\_ Accuracy: \_\_\_\_\_  
Sulfate \_\_\_\_\_ ppm \_\_\_\_\_  
Sp. Conduct \_\_\_\_\_ K x 10<sup>6</sup> \_\_\_\_\_ ppm \_\_\_\_\_  
Temp. \_\_\_\_\_ °F \_\_\_\_\_  
Chloride \_\_\_\_\_  
Taste, color, etc. \_\_\_\_\_

