

PUNCHED and VERIFIED  
ROLLS REPLETION BRANCH

WRD Exp. (GW)  
April 1966

Well No. \_\_\_\_\_

213

### WELL SCHEDULE

U. S. DEPT. OF THE INTERIOR

GEOLOGICAL SURVEY

WATER RESOURCES DIVISION

#### MASTER CARD

Record by J. HARRELL Source of data BOWC Date 5/17/68 Map \_\_\_\_\_

State 28 County (or town) WAYNE 77

Latitude: 31<sup>deg</sup> 29<sup>min</sup> 57<sup>sec</sup> N Longitude: 08<sup>deg</sup> 82<sup>min</sup> 73<sup>sec</sup> W Sequential number: 1

Lat-long accuracy: 3<sup>deg</sup> 0<sup>min</sup> 5<sup>sec</sup> E Sec 11, NW SW

Local well number: 2013BC1106N05W Other well number: \_\_\_\_\_ B & M

Local use: 033 Owner or name: \_\_\_\_\_

Owner or name: BABE DEARMAN Address: Buckatumna

Ownership: County, Fed Gov't, City, Corp or Co, Private, State Agency, Water Dist \_\_\_\_\_ P

Use of water: (A) Air cond, (B) Bottling, (C) Comm, (D) Dewater, (E) Power, (F) Fire, (G) Dom, (H) Irr, (I) Med, (J) P S, (K) Rec, (L) Stock, (M) Unused, (N) Recharge, (O) Desal-P S, (P) Desal-other, (Q) Other \_\_\_\_\_ H

Use of well: (A) Anode, (B) Drain, (C) Seismic, (D) Heat Res, (E) Obs, (F) Oil-gas, (G) Recharge, (H) Test, (I) Unused, (J) Withdraw, (K) Waste, (L) Destroyed \_\_\_\_\_ W

DATA AVAILABLE: Well data  Freq. W/L meas.:  Field aquifer char.

Hyd. lab. data: \_\_\_\_\_

Qual. water data; type: \_\_\_\_\_

Freq. sampling: \_\_\_\_\_ Pumpage inventory:  yes  no; period: \_\_\_\_\_

Aperture cards: \_\_\_\_\_ yes  no

Log data: \_\_\_\_\_ D

#### WELL-DESCRIPTION CARD

SAME AS ON MASTER CARD Depth well: 104 ft Meas. rept 104 accuracy 3

Depth cased; (first perf.) 99 ft Casing type: \_\_\_\_\_; Diam. 2 in

Finish: (A) porous concrete, (B) gravel w. (perf.), (C) (screen), (D) (H) horiz. gallery, (E) (J) open end, (F) (P) perf., (G) (S) screen, (H) (T) sd. pt., (I) (W) shored, (J) (X) open hole, (K) (Z) other \_\_\_\_\_ S

Method Drilled: (A) air rot, (B) bored, (C) cable, (D) dug, (E) (H) hyd jettted, (F) (J) air rot., (G) (P) percuss, (H) (R) rotary, (I) (T) reverse, (J) (V) trenching, (K) (W) driven, (L) (Z) wash, other \_\_\_\_\_ H

Date Drilled: 6/67 967 Pump intake setting: \_\_\_\_\_ ft

Driller: Porter Drilling Co address \_\_\_\_\_

Lift (type): (A) air, (B) bucket, (C) (J) cent., (D) (M) multiple, (E) (N) multiple, (F) (P) none, (G) (R) piston, (H) (S) rot., (I) (T) submerg, (J) (Z) turb, other \_\_\_\_\_ Deep  Shallow

Power (type): (A) diesel, (B) (nat) elec., (C) gas, (D) gasoline, (E) hand, (F) (LP) gas, (G) wind, (H) (H.P.) \_\_\_\_\_ 3/4 Trans. of meter no. \_\_\_\_\_

Descrip. MP \_\_\_\_\_ above ft below LSD. Alt. MP \_\_\_\_\_

Alt. LSD: \_\_\_\_\_ Accuracy: (source) \_\_\_\_\_

Water Level 55 ft above below MP; Ft. above below LSD 55 Accuracy: \_\_\_\_\_

Date meas: 6/67 667 Yield: 7 gpm Method determined \_\_\_\_\_

Drawdown: \_\_\_\_\_ ft Accuracy: \_\_\_\_\_ Pumping period \_\_\_\_\_ hrs

QUALITY OF WATER DATA: Iron \_\_\_\_\_ ppm Sulfate \_\_\_\_\_ ppm Chloride \_\_\_\_\_ ppm Hard. \_\_\_\_\_ ppm

Sp. Conduct \_\_\_\_\_ K x 10<sup>6</sup> Temp. \_\_\_\_\_ °F Date sampled \_\_\_\_\_

Taste, color, etc. \_\_\_\_\_

Well No. 213

Well No. 213

Latitude-longitude N  
S  
d m s d m s

HYDROGEOLOGIC CARD

SAME AS ON MASTER CARD 03 Section: \_\_\_\_\_  
Province: \_\_\_\_\_

D Drainage Basin: 13P Subbasin: \_\_\_\_\_

Topo of well site: (D) depression, stream channel, dunes, flat, hilltop, sink, swamp, (K) (L) (P) (S) (T) (U) (V) offshore, pediment, hillside, terrace, undulating, valley flat \_\_\_\_\_

MAJOR AQUIFER: \_\_\_\_\_ system \_\_\_\_\_ series \_\_\_\_\_ aquifer, formation, group \_\_\_\_\_

Lithology: \_\_\_\_\_ Origin: \_\_\_\_\_ Aquifer Thickness: \_\_\_\_\_ ft

Length of well open to: \_\_\_\_\_ ft \_\_\_\_\_ Depth to top of: \_\_\_\_\_ ft \_\_\_\_\_

MINOR AQUIFER: \_\_\_\_\_ system \_\_\_\_\_ series \_\_\_\_\_ aquifer, formation, group \_\_\_\_\_

Lithology: \_\_\_\_\_ Origin: \_\_\_\_\_ Aquifer Thickness: \_\_\_\_\_ ft

Length of well open to: \_\_\_\_\_ ft \_\_\_\_\_ Depth to top of: \_\_\_\_\_ ft \_\_\_\_\_

Intervals Screened: 1/4" 8 slot S.S.

Depth to consolidated rock: \_\_\_\_\_ ft \_\_\_\_\_ Source of data: \_\_\_\_\_


Depth to basement: \_\_\_\_\_ ft \_\_\_\_\_ Source of data: \_\_\_\_\_

Surficial material: \_\_\_\_\_ Infiltration characteristics: \_\_\_\_\_

Coefficient Trans: \_\_\_\_\_ gpd/ft \_\_\_\_\_ Coefficient Storage: \_\_\_\_\_

Coefficient Perm: \_\_\_\_\_ gpd/ft<sup>2</sup>; Spec cap: \_\_\_\_\_ gpm/ft; Number of geologic cards: \_\_\_\_\_

4 miles SE of Buckatanna



Well No.

213