

WELL SCHEDULE

U. S. DEPT. OF THE INTERIOR GEOLOGICAL SURVEY WATER RESOURCES DIVISION

MASTER CARD

Record by WTR Source of data Bowc Date 1/70 Map \_\_\_\_\_

State 28 County Yalo (or town) 8.1

Latitude: 34 10 00 N Longitude: 089 36 33 Sequential number: 1

Lat-long accuracy: 3 10 4 34 NE NE

Local well number: C026AA3410S04W Other well number: \_\_\_\_\_

Local use: 180 Owner or name: \_\_\_\_\_

Owner or name: DALEMEY GREEN Address: \_\_\_\_\_

Ownership: County, Fed Gov't, City, Corp or Co, Private, State Agency, Water Dist \_\_\_\_\_

Use of Air cond, Bottling, Comm, Dewater, Power, Fire, Dom, Irr, Med, Ind, P S, Rec, water: \_\_\_\_\_

Use of well: Anode, Drain, Seismic, Heat Res, Obs, Oil-gas, Recharge, Test, Unused, Withdraw, Waste, Destroyed \_\_\_\_\_

DATA AVAILABLE: Well data  Freq. W/L meas.  Field aquifer char.

Hyd. lab. data: \_\_\_\_\_

Qual. water data, type: \_\_\_\_\_

Freq. sampling: \_\_\_\_\_ Pumpage inventory: \_\_\_\_\_

Aperture cards: \_\_\_\_\_

Log data: D

WELL-DESCRIPTION CARD

SAME AS ON MASTER CARD Depth well: 115 Meas. rept. accuracy \_\_\_\_\_

Depth cased: 110 Casing type: PCV Diam. in 4

Finish: porous concrete, gravel w. (perf.), gravel w. (screen), horiz. gallery, end, open perf., screen, sd. pt., shored, open hole, other \_\_\_\_\_

Method: drilled: air rot, bored, cable, dug, hyd rot., jetted, air percussion, rotary, reverse, trenching, driven, wash, other \_\_\_\_\_

Date drilled: 9.6.7 Pump intake setting: \_\_\_\_\_ ft \_\_\_\_\_

Driller: Roberson name address \_\_\_\_\_

Lift (type): air, bucket, cent, jet, multiple (cent.), multiple (turb.), none, piston, rot, submerg, turb, other \_\_\_\_\_ Deep \_\_\_\_\_ Shallow \_\_\_\_\_

Power (type): diesel, elec, gas, gasoline, hand, gas, wind; H.P. 1/2 3 Trans. or meter no. \_\_\_\_\_

Descrip. MP \_\_\_\_\_ ft above \_\_\_\_\_ ft below LSD, Alt. MP \_\_\_\_\_

Alt. LSD: 400 Accuracy: (source) \_\_\_\_\_

Water Level: \_\_\_\_\_ ft above MP; \_\_\_\_\_ ft below LSD Accuracy: \_\_\_\_\_

Date meas: 8.6.7 Yield: \_\_\_\_\_ gpm Method determined \_\_\_\_\_

Drawdown: \_\_\_\_\_ ft Accuracy: \_\_\_\_\_ Pumping period \_\_\_\_\_ hrs \_\_\_\_\_

QUALITY OF WATER DATA: Iron \_\_\_\_\_ ppm Sulfate \_\_\_\_\_ ppm Chloride \_\_\_\_\_ ppm Hard. \_\_\_\_\_ ppm


Sp. Conduct \_\_\_\_\_ K x 10 \_\_\_\_\_ Temp. \_\_\_\_\_ °F Date sampled \_\_\_\_\_

Taste, color, etc. \_\_\_\_\_

PUNCHED and VERIFIED  
ROLLA COMPUTATION BRANCH

Well No.

C26



HYDROGEOLOGIC CARD

SAME AS ON MASTER CARD 03 Section: 03

D Drainage Basin: 15F Subbasin: 26

Topo of well site: (D) depression, stream channel, dunes, flat, hilltop, sink, swamp, (P) offshore, pediment, hillside, terrace, undulating, valley flat

MAJOR AQUIFER: system TE series TE aquifer, formation, group MW

Lithology: S Origin: 2 Aquifer Thickness: ≥ 35 ft

Length of well open to: 5 ft Depth to top of: 80 ft

MINOR AQUIFER: system TE series TE aquifer, formation, group MW

Lithology: S Origin: 2 Aquifer Thickness: ≥ 35 ft

Length of well open to: 5 ft Depth to top of: 80 ft

Intervals Screened: 110 - 115 ft 5' 6" gravel pack

Depth to consolidated rock: 60 ft Source of data: 64


Depth to basement: 65 ft Source of data: 69

Surficial material: 70 Infiltration characteristics: 72

Coefficient Trans: 73 gpd/ft 75 Coefficient Storage: 76

Coefficient Perm: 77 gpd/ft<sup>2</sup>; Spec cap: 78 gpm/ft; Number of geologic cards: 79

Sd + Red clay 0-40 ft  
Sd + blue clay 40-80  
White sand 80-115



Well No.

C26