

PUNCHED
MAR 24 1975

FORM 9-1642
(1-68)

Well No. G28

WELL SCHEDULE

U. S. DEPT. OF THE INTERIOR GEOLOGICAL SURVEY WATER RESOURCES DIVISION

PUNCHED and VERIFIED
ROLLA COMPUTATION BRANCH

MASTER CARD

Record by W.F. Powell Source of data SWPC Date 7-14-55 Map Valley Quad

State: Miss 28 County (or town) YA200 82

Latitude: 325114N Longitude: 0902400 Sequential number: 1

Lat-long accuracy: 3 12 0 2 28 SW SE SE

Local well number: G028DD2812N02W Other well number: B & M

Local use: 064 Owner or name: City of Yazoo

Ownership: County, Fed Gov't, City, Corp or Co, Private, State Agency, Water Dist M

Use of water: (S) (T) (U) (V) (W) (X) (Y) (Z) RK

Use of well: (A) (D) (G) (H) (I) (P) (R) (T) (U) (W) (X) (Z) W X Z

DATA AVAILABLE: Well data Freq. W/L meas. Field-aquifer char.

Hyd. lab. data: WELL CEMENTED - 11/22/89

Qual. water data; type:

Freq. sampling: Pumpage inventory: yes no; period:

Aperture cards: yes

Log data:

WELL-DESCRIPTION CARD

SAME AS ON MASTER CARD

Depth well: 954 ft Meas. rept accuracy 6

Depth cased: ft Casing type: Diam. 16X12 in 16

Finish: (C) porous concrete, (F) gravel v. concrete, (G) gravel v. (perf.), (H) horls. gallery, (I) open end, (J) screen, (K) open hole, (L) other 5

Method drilled: (A) air rot., (B) bored, (C) cable, (D) dug, (E) hyd rot., (F) jet, (G) percussion, (H) rotary, (I) air reverse, (J) reverse trenching, (K) driven, (L) wash, (M) other H

Date drilled: 945 Pump intake setting: ft

Driller: Gayne Central name address

Lift (type): (A) air, (B) bucket, (C) cent. jet, (D) multiple, (E) multiple, (F) none, (G) piston, (H) rot., (I) submerg, (J) turb., (K) other C Deep Shallow

Power (type): (A) diesel, (B) elec, (C) gas, (D) gasoline, (E) hand, (F) gas, (G) wind, (H) H.P. 30 Trans. or meter no.

Descrip. MP above ft below LSD, Alt. MP

Alt. LSD: 100 Accuracy: (source) Topo 4

Water Level + ft above MP; Ft below LSD F Accuracy: 6

Date meas: 845 Yield: 700 gpm Method determined

Drawdown: ft Accuracy: Pumping period hrs

QUALITY OF WATER DATA: Iron ppm Sulfate ppm Chloride ppm Hard. ppm

Sp. Conduct K x 10 Temp. °F Date sampled

Taste, color, etc.

Well No.

G28

HYDROGEOLOGIC CARD

SAME AS ON MASTER CARD **Physiographic Province:** AUCERHOE **Section:** 03

Drainage Basin: E **Subbasin:** 15J

Topo of well site: (D) (C) (E) (F) (H) (K) (L) (P) (S) (T) (U) (V) 27

MAJOR AQUIFER: T E **system series:** S S

Lithology: V S **Origin:** 2 **Aquifer Thickness:** ft

Length of well open to: ft **Depth to top of:** ft

MINOR AQUIFER: **system series:** **aquifer, formation, group:**

Lithology: **Origin:** **Aquifer Thickness:** ft

Length of well open to: ft **Depth to top of:** ft

Intervals Screened:


Depth to consolidated rock: ft **Source of data:**

Depth to basement: ft **Source of data:**

Surficial material: **Infiltration characteristics:**

Coefficient Trans: gpd/ft **Coefficient Storage:**

Coefficient Perm: gpd/ft; Spec cap: gpm/ft; **Number of geologic cards:**



Well No.

G 28

MISSISSIPPI DEPARTMENT OF NATURAL RESOURCES

Bureau of Land and Water Resources

G 28

P. O. Box 10631
Jackson, Mississippi 39209
WATER WELL PLUGGING
DECOMMISSIONING

COUNTY WELL LOCATED Yazoo		PERMIT NUMBER Unknown	
WELL NUMBER Unknown	CODED	NAME OF DRILLING FIRM LAYNE-CENTRAL COMPANY	
DATE WELL PLUGGED 11-22-89		JACKSON, MS.	
NAME & MAILING ADDRESS OF LANDOWNER Public Service Commission 125 West Commercial St. Yazoo City, Ms. 39194		NAME OF WELL CONTRACTOR WHO DRILLED THE WELL Unknown	
WELL LOCATION SEC TOWNSHIP RANGE 4th Street 28 12N 2W		NAME OF LANDOWNER WHEN WELL WAS DRILLED Public Service Comm.	
DISTANCE DIRECTION NEAREST TOWN		WELL DATA	
OTHER LANDMARK Next to Illinois Central R.R.		Well Depth 980±	Casing Diameter (In.) 12"
WELL PURPOSE: Home, Irrigation, Municipal, Industrial, Fish Pond, etc. Municipality		Casing Length (Ft.) 900±	Depth to Static Water Level 100' (11-22-
		Type of Casing Steel	Hole Depth 980±
		DATE WELL COMPLETED Unknown	

DESCRIBE HOW THE WELL OR HOLE WAS PLUGGED:
(AMOUNT OF CASING AND/OR SCREEN THAT WAS REMOVED, OR LEFT IN HOLE,
MATERIAL USED IN PLUGGING, ETC.)

On 11-21-89, approximately 210 sacks of a 14 pound per gallon mix was placed in the bottom of the well via a 4" cementing pipe. On 11-22-89 an additional 140 sacks were used to fill the remaining casing. Pump was pulled prior to cementing.

I CERTIFY THAT THE WELL WAS PLUGGED OR ABANDONED IN ACCORDANCE WITH THE STATE OF MISSISSIPPI REGULATIONS.

Ralph E. Hayes
SIGNATURE Ralph E. Hayes, P.E.

11-27-89
DATE

Updated 2-28-92
JRE